


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	02/05/04	M.C.CORMICK
B	ECN# 2731 - ADDED ROHS STAMP	10/23/07	D.GRIFFIN
C	ECN 4278: ADDED OPERATING TEMPERATURE RANGE AND PACKAGING	9/30/09	D.FRISIELLO



RoHS Compliant ✓

NOTES:

1. IP (INGRESS PROTECTION) RATING: 67.
2. OPERATING TEMPERATURE RANGE: -40° C TO +105° C.
3. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] DIMENSIONAL TOLERANCES: .X = ±.1 .XX = ±.03 .XXX = ±.005 ANGULAR TOLERANCES: ALL = ± 1° PROJECTION 	APPROVALS	DATE	 45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845	
	DRAWN BY C.MCCORMICK	02/05/2004		
	CHECKED BY D.PARHAM	02/05/2004	CATEGORY DATA CABLING	
	APPROVED BY R.CARRICK	02/05/2004	PRODUCT DESCRIPTION DB9 MALE WATERPROOF SOLDER	
CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY		SIZE A	FSCM NO. 43321	DWG. NO. WPSD9P
COLOR VARIATIONS MAY OCCUR		SCALE: NONE	CAD FILE: WPSD9P.SLDDRW	REV. C
REF		SHEET 1 OF 1		