


[About Us](#)
[Products](#)
[Services](#)
[Support](#)
[Projects](#)
[Web Shop](#)

Products

[Board Comparison Chart](#)
[Developer's Kits](#)
[OEM Boards](#)
[QuickStart Boards](#)
[Education Boards](#)
[LPCXpresso & mbed](#)
[LPCXpresso LPC1114](#)
[LPCXpresso LPC11U14](#)
[LPCXpresso LPC11C24](#)
[LPCXpresso LPC1227](#)
[LPCXpresso LPC1343](#)
[LPCXpresso LPC1769](#)
[LPCXpresso Prototype](#)
[LPCXpresso Base](#)
[LPCXpresso Value Pack](#)
[LPCXpresso Motor Control](#)
[mbed](#)
[Displays](#)
[Tools](#)
[Accessories](#)

LPC11U14 LPCXpresso Board



Picture not showing correct version of LPCXpresso board.

The LPC11U14 LPCXpresso board with NXP's ARM Cortex-M0 microcontroller has been designed to make it as easy as possible to get started with Cortex-M0. The LPCXpresso comprises a target board combined with a JTAG debugger. A free Eclipse-based IDE from Code Red is also included.

The LPC11U14 has 6 kB SRAM, 32 kB Flash, USB 2.0 Full-Speed Device, SSP, I2C, UART, ADC, etc. Embedded Artists also provides a [Prototype board](#) and a [Base board](#) that makes it possible to make experiments and prototyping with many peripherals.

Discount

Embedded Artists and Code Red offer LPCXpresso customers valuable discounts. Embedded Artists gives **15 EUR** discount on the regular [Developer's kits](#) and **7 EUR** off the LPCXpresso Base board. Code Red has an offer to upgrade to full-blown suites. For more information see [LPCXpresso discount](#).

Price Information

EUR

Art.no: **EA-XPR-007** [Buy](#)

Currently out-of-stock

Expected delivery date:
2011-07-30

Price Information

EUR

LPCXpresso Kit containing
LPC11U14 and [Base Board](#)

Art.no: **EA-XPR-107** [Buy](#)

Currently out-of-stock

Expected delivery date:
2011-07-30

[Overview](#)
[Specification](#)
[MCU](#)
[Related Products](#)
[Resources](#)
[FAQ](#)

LPC11U14 LPCXpresso Board

Processor	NXP's Cortex-M0 LPC11U14 microcontroller in LQFP48 package
Flash	32 kB
Data Memory	6 kB
Clock Crystals	12.000 MHz crystal for CPU
Dimensions	35 x 140 mm
Power	3.15V-3.3V external powering, or from USB via JTAG probe (LPC-LINK)
Connectors	• mini-B USB connector for LPC11U14 USB interface • All LPC11U14 pins available on expansion connector (2x27 pin rows, 100 mil pitch, 900 mil between rows)
Other	• Embedded JTAG (LPC-LINK) functionality via LPCXpresso toolchain • LPC-LINK can be connected to external target processor after modifications to the LPCXpresso board • LED on P100_7