



Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 19

SDS No. : 153626
V009.1

LOCTITE AA 3525 LC known as LOCTITE 3525 VIS/UV

Revision: 30.01.2014
printing date: 25.09.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE AA 3525 LC known as LOCTITE 3525 VIS/UV

Contains:

2-Hydroxyethyl methacrylate
Hydroxypropyl methacrylate
Acrylic acid
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Ultraviolet adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000
Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Toxic to reproduction	Category 2
H361f Suspected of damaging fertility.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

Classification (DPD):

Sensitizing

R43 May cause sensitisation by skin contact.

Xi - Irritant

R36/37/38 Irritating to eyes, respiratory system and skin.

N - Dangerous for the environment

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H318 Causes serious eye damage.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statement:
Prevention**

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Label elements (DPD):

Xi - Irritant



N - Dangerous for the environment



Risk phrases:

R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

S23 Do not breathe vapour.

S24/25 Avoid contact with skin and eyes.

S36/37 Wear suitable protective clothing and gloves.

S51 Use only in well-ventilated areas.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

2-Hydroxyethyl methacrylate,

Hydroxypropyl methacrylate,

Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide

2.3. Other hazards

None if used properly.

SECTION 3: Composition/information on ingredients

General chemical description:

UV curing acrylic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2-Hydroxyethyl methacrylate 868-77-9	212-782-2 01-2119490169-29	>= 10- < 20 %	Skin irritation 2 H315 Skin sensitizer 1 H317 Serious eye irritation 2 H319
Isobornyl methacrylate 7534-94-3	231-403-1	>= 10- < 20 %	Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315 Serious eye irritation 2 H319 Chronic hazards to the aquatic environment 2 H411
Isobornyl acrylate 5888-33-5	227-561-6	>= 2,5- < 10 %	Serious eye irritation 2 H319 Skin irritation 2 H315 Chronic hazards to the aquatic environment 2 H411 Specific target organ toxicity - single exposure 3 H335
Hydroxypropyl methacrylate 27813-02-1	248-666-3 01-2119490226-37	>= 1- < 10 %	Skin sensitizer 1; Dermal H317 Serious eye irritation 2 H319
Acrylic acid 79-10-7	201-177-9 01-2119452449-31	>= 3- < 5 %	Flammable liquids 3 H226 Acute toxicity 4; Oral H302 Acute toxicity 4; Dermal H312 Skin corrosion 1A H314 Acute toxicity 4; Inhalation H332 Specific target organ toxicity - single exposure 3 H335 Acute hazards to the aquatic environment 1 H400 Chronic hazards to the aquatic environment 1 H410
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	278-355-8 01-2119972295-29	>= 3- < 5 %	Toxic to reproduction 2 H361f Chronic hazards to the aquatic environment 2 H411 Skin sensitizer 1B H317
[3-(2,3- Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	219-784-2 01-2119513212-58	>= 1- < 3 %	Serious eye damage/eye irritation 1 H318 Chronic hazards to the aquatic environment 3 H412
Methacrylic acid 79-41-4	201-204-4 01-2119463884-26	>= 0,1- < 1 %	Acute toxicity 4; Oral H302 Acute toxicity 3; Dermal H311 Acute toxicity 4; Inhalation H332 Skin corrosion/irritation 1A H314

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2-Hydroxyethyl methacrylate 868-77-9	212-782-2 01-2119490169-29	>= 10 - < 20 %	Xi - Irritant; R36/38 R43
Isobornyl methacrylate 7534-94-3	231-403-1	>= 10 - < 20 %	N - Dangerous for the environment; R51/53 Xi - Irritant; R36/37/38
Isobornyl acrylate 5888-33-5	227-561-6	>= 2,5 - < 10 %	Xi - Irritant; R36/37/38 N - Dangerous for the environment; R51/53
Hydroxypropyl methacrylate 27813-02-1	248-666-3 01-2119490226-37	>= 1 - < 10 %	Xi - Irritant; R36, R43
Acrylic acid 79-10-7	201-177-9 01-2119452449-31	>= 3 - < 5 %	R10 C - Corrosive; R35 N - Dangerous for the environment; R50 Xn - Harmful; R20/21/22
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	278-355-8 01-2119972295-29	>= 3 - < 5 %	N - Dangerous for the environment; R51/53 Toxic for reproduction - category 3.; Xn - Harmful; R62 Xi - Irritant; R43
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	219-784-2 01-2119513212-58	>= 1 - < 3 %	Xi - Irritant; R41

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.
Consideration should be given to the possible effects of a faulty UV source (Stray radiation, ozone).

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

In case of fire, keep containers cool with water spray.

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Good industrial hygiene practices should be observed.

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

7.3. Specific end use(s)

Ultraviolet adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

Ingredient	ppm	mg/m ³	Type	Category	Remarks
METHACRYLIC ACID 79-41-4	40	143	Short Term Exposure Limit (STEL):		EH40 WEL
METHACRYLIC ACID 79-41-4	20	72	Time Weighted Average (TWA):		EH40 WEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2-Hydroxyethyl methacrylate 868-77-9	aqua (freshwater)					0,482 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (marine water)					0,482 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	STP					10 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	aqua (intermittent releases)					1 mg/L	
2-Hydroxyethyl methacrylate 868-77-9	sediment (freshwater)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	sediment (marine water)				3,79 mg/kg		
2-Hydroxyethyl methacrylate 868-77-9	soil				0,476 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (freshwater)					0,904 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (marine water)					0,904 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	STP					10 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	aqua (intermittent releases)					0,972 mg/L	
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sediment (freshwater)				6,28 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	sediment (marine water)				6,28 mg/kg		
Methacrylic acid, monoester with propane- 1,2-diol 27813-02-1	soil				0,727 mg/kg		
Acrylic acid 79-10-7	aqua (freshwater)					0,003 mg/L	
Acrylic acid 79-10-7	aqua (marine water)					0,0003 mg/L	
Acrylic acid 79-10-7	aqua (intermittent releases)					0,0013 mg/L	
Acrylic acid 79-10-7	STP					0,9 mg/L	
Acrylic acid 79-10-7	sediment (freshwater)				0,0236 mg/kg		
Acrylic acid 79-10-7	sediment (marine water)				0,00236 mg/kg		
Acrylic acid 79-10-7	soil				1 mg/kg		
Acrylic acid 79-10-7	oral				0,0023 mg/kg		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	aqua (freshwater)					0,00353 mg/L	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	aqua (marine water)					0,000353 mg/L	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	aqua (intermittent releases)					0,0353 mg/L	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	sediment (freshwater)				0,29 mg/kg		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	sediment (marine water)				0,029 mg/kg		
Diphenyl(2,4,6-trimethylbenzoyl)phosphine	soil				0,0557		

oxide 75980-60-8					mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (freshwater)					1 mg/L	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (marine water)					0,1 mg/L	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	aqua (intermittent releases)					1 mg/L	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	soil				0,13 mg/kg		
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	STP					10 mg/L	

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-Hydroxyethyl methacrylate 868-77-9	worker	Dermal	Long term exposure - systemic effects		1,3 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	worker	inhalation	Long term exposure - systemic effects		4,9 mg/m3	
2-Hydroxyethyl methacrylate 868-77-9	general population	Dermal	Long term exposure - systemic effects		0,83 mg/kg bw/day	
2-Hydroxyethyl methacrylate 868-77-9	general population	inhalation	Long term exposure - systemic effects		2,9 mg/m3	
2-Hydroxyethyl methacrylate 868-77-9	general population	oral	Long term exposure - systemic effects		0,83 mg/kg bw/day	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	worker	Dermal	Long term exposure - systemic effects		4,2 mg/kg bw/day	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	worker	inhalation	Long term exposure - systemic effects		14,7 mg/m3	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	general population	Dermal	Long term exposure - systemic effects		2,5 mg/kg bw/day	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	general population	inhalation	Long term exposure - systemic effects		8,8 mg/m3	
Methacrylic acid, monoester with propane-1,2-diol 27813-02-1	general population	oral	Long term exposure - systemic effects		2,5 mg/kg bw/day	
Acrylic acid 79-10-7	worker	inhalation	Long term exposure - local effects		30 mg/m3	
Acrylic acid 79-10-7	worker	inhalation	Acute/short term exposure - local effects		30 mg/m3	
Acrylic acid 79-10-7	worker	Dermal	Acute/short term exposure - local effects		1 mg/cm2	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	worker	inhalation	Long term exposure - systemic effects		3,5 mg/m3	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	worker	Dermal	Long term exposure - systemic effects		1 mg/kg	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide 75980-60-8	worker		Long term exposure - systemic effects			
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	worker	Dermal	Acute/short term exposure - systemic effects		21 mg/kg bw/day	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	worker	inhalation	Acute/short term exposure - systemic effects		147 mg/m3	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	worker	Dermal	Long term exposure - systemic effects		21 mg/kg bw/day	
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	worker	inhalation	Long term exposure - systemic effects		147 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

UV lamp should be designed, installed and operated in such a way as to eliminate exposure of the skin and eyes to stray radiation

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Suitable respiratory protection:

Filter type: A

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
	Clear
Odor	Sharp
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	> 140 °C (> 284 °F)
Flash point	71,1 °C (159.98 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	< 13,33 mbar
Density	1,113 g/cm ³
0	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Slight
(Solvent: Water)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.
Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

May cause respiratory irritation.

Skin irritation:

Causes skin irritation.

Eye irritation:

Causes serious eye damage.

Sensitizing:

May cause an allergic skin reaction.

Reproductive toxicity:

Suspected of damaging fertility.

Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	LD50	2.300 - 4.000 mg/kg	oral		rat	
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LD50	> 5.000 mg/kg	oral		rat	
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50		oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Methacrylic acid 79-41-4	LD50	1.320 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LC50	> 5,3 mg/l	inhalation		rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Methacrylic acid 79-41-4	LC50	4,7 mg/l	inhalation	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	LD50	> 5.000 mg/kg	dermal		rabbit	
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	LD50		dermal		rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg	dermal			Expert judgement
Methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg			rabbit	

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Methacrylic acid 79-41-4	Category 1A (corrosive)	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
[3-(2,3- Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Acrylic acid 79-10-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A Mutagenic potential cannot be excluded.	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	A Mutagenic potential cannot be excluded.			mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL=500 mg/kg	oral: unspecified	28 d	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
[3-(2,3-Epoxypropoxy)propyl]tri methoxysilane 2530-83-8	NOAEL=0,225 mg/kg	inhalation	14 d	rat	OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Toxic to aquatic life with long lasting effects.
Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
2-Hydroxyethyl methacrylate 868-77-9	LC50	227 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	345 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	160 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxyethyl methacrylate 868-77-9	NOEC	24,1 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Isobornyl methacrylate 7534-94-3	LC50	1,79 mg/l	Fish	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl methacrylate 7534-94-3	EC50	1,1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl methacrylate 7534-94-3	EC50	2,66 mg/l	Algae	96 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl acrylate 5888-33-5	IC50	4,2 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	1,87 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	Fish	48 h	Leuciscus idus melanotus	
Acrylic acid 79-10-7	LC50	27 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acrylic acid 79-10-7	EC50	47 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Acrylic acid 79-10-7	EC50	0,13 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC	0,008 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Acrylic acid 79-10-7	NOEC	19 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	LC50	1 - 10 mg/l	Fish	48 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	10 - 100 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Diphenyl-2,4,6- trimethylbenzoyl phosphine oxide 75980-60-8	EC50	10 - 100 mg/l	Algae	72 h		OECD Guideline 201 (Alga, Growth Inhibition Test)
[3-(2,3- Epoxypropoxy)propyl]trimeth oxysilane 2530-83-8	LC50	55 mg/l	Fish	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	EC50	473 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	NOEC	53 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	255 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	NOEC	100 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Methacrylic acid 79-41-4	LC50	100 - 180 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methacrylic acid 79-41-4	EC50	> 130 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methacrylic acid 79-41-4	EC10	8,2 mg/l	Algae			OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC50	> 8,2 mg/l	Algae			OECD Guideline 201 (Alga, Growth Inhibition Test)

12.2. Persistence and degradability**Persistence and Biodegradability:**

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Isobornyl methacrylate 7534-94-3			26,8 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Isobornyl acrylate 5888-33-5		no data	72,9 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroxypropyl methacrylate 27813-02-1	readily biodegradable	aerobic	94,2 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Acrylic acid 79-10-7	readily biodegradable	aerobic	81 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8			< 20 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8		aerobic	37 %	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
Methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

Cured adhesives are immobile.

Bioaccumulative potential:

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
---------------------------------	--------	-------------------------------	---------------	---------	-------------	--------

Isobornyl methacrylate 7534-94-3	5,09					OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Isobornyl acrylate 5888-33-5	4,21					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Hydroxypropyl methacrylate 27813-02-1	0,97					
Acrylic acid 79-10-7	0,46				25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Methacrylic acid 79-41-4	0,93					

12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
2-Hydroxyethyl methacrylate 868-77-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Hydroxypropyl methacrylate 27813-02-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Acrylic acid 79-10-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide 75980-60-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane 2530-83-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Methacrylic acid 79-41-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information**14.1. UN number**

ADR	3082
RID	3082
ADNR	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl methacrylate, Isobornyl acrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl methacrylate, Isobornyl acrylate)
ADNR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl methacrylate, Isobornyl acrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl methacrylate, Isobornyl acrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Isobornyl methacrylate, Isobornyl acrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADNR	9
IMDG	9
IATA	9

14.4. Packaging group

ADR	III
RID	III
ADNR	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADNR	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (E)
RID	not applicable
ADNR	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 5,00 %

(1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R35 Causes severe burns.
R36 Irritating to eyes.
R36/37/38 Irritating to eyes, respiratory system and skin.
R36/38 Irritating to eyes and skin.
R41 Risk of serious damage to eyes.
R43 May cause sensitisation by skin contact.
R50 Very toxic to aquatic organisms.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62 Possible risk of impaired fertility.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361f Suspected of damaging fertility.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.