PANDUIT® building a smarter, unified business foundation
Connect. Manage. Automate.

Unified Physical Infrastructure™

Worldwide |

-Search-   Entire Site ▼ GO

Home > Product On-Line Catalog > Search Results >

Search Results

Evaluate
- FAQ's
Design a Solution
- Part Drawings
  - DXF-Mini-Com TX6 ..
  - PDF-Mini-Com TX6 ..
  - DWG-Mini-Com TX6 ..
- Specification Sheets
  - PDF-Mini-Com TX6 ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ⊠ to remove)   Search Tips ⑦

⊠ Text Search: 'CJE688TGWH'

Your search criteria matched only one product, shown below

CJE688TGWH

• Injected gel and polymer material reduce area of exposed electrical contacts providing improved long term performance in corrosive environments
• Exceed requirements of ANSI/TIA-568-C.2 Category 6, IEEE 802.3an-2006, and ISO 11801 Class E channel standards
• Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
• Each jack is 100% tested to ensure NEXT and RL performance and is individually serialized for traceability
• Utilizes patent-pending enhanced Giga-TX™ Technology for jack termination which optimizes performance by maintaining cable pair geometry and eliminating conductor untwist
• Contacts plated with 50 microinches of gold for superior performance
• No punchdown tool required; termination tool (EGJT) ensires conductors are fully terminated by utilizing a smooth forward motion without impact on critical internal components for maximum reliability
• Optional termination tool (TGJT) reduces termination time by 25%, ideal for high volume installations
• Can be re-terminated a minimum of twenty times
• White termination cap designates Category 6 performance and provides positive strain relief; helps control cable bend radius and securely retains wires
• Terminates 4-pair, 22 — 26 AWG, 100 ohm, solid or stranded twisted pair cable
• Universal termination cap is color-coded for T568A and T568B wiring schemes
• Accepts 6 and 8-position modular plugs without damage
• Can be clearly identified with optional labels and icons
• Compatible with Mini-Com® Modular Patch Panels, Faceplates and Surface Mount Boxes
• Optional RJ45 blockout device blocks out unauthorized access to jack modules and potentially harmful foreign objects, saving time and money associated with data security breaches, network downtime, repair, and hardware replacement
• Optional dust cap keeps out dust and debris while not in use

• Part Number	CJE688TGWH
• RoHS Compliancy Status	Compliant
• Part Description	Category 6, RJ45, 8-position, 8-wire, universal, corrosive resistant UTP jack module
• Product Type	UTP Jack Module
• Color	White
• No. of Module Spaces	1
• Performance Level	Category 6/Class E
• Pricing Description	Mini-Com Corrosive Resistant Module, Cat 6, UTP, White, TG Style
• Min. Order UOM	PC
• Min. Order Qty.	1
• BOM Qty. (# of Pkgs.)	0
• Add to Favorite Product List	☐

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.