

Silicon Power Schottky Diode



$$V_{RRM} = 10\text{ V} - 40\text{ V}$$

$$I_{F(AV)} = 60\text{ A}$$

Features

- High Surge Capability
- Types from 10 V to 40 V V_{RRM}
- Not ESD Sensitive

D61-3M Package



Maximum ratings, at $T_j = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	FST6310M	FST6315M	FST6320M	FST6330M	FST6335M	Unit
Repetitive peak reverse voltage	V_{RRM}		10	15	20	30	35	V
RMS reverse voltage	V_{RMS}		7	11	14	21	25	V
DC blocking voltage	V_{DC}		10	15	20	30	35	V
Operating temperature	T_j		-55 to 150	-55 to 150	-55 to 150	-55 to 150	-55 to 150	$^{\circ}\text{C}$
Storage temperature	T_{stg}		-55 to 150	-55 to 150	-55 to 150	-55 to 150	-55 to 150	$^{\circ}\text{C}$

Electrical characteristics, at $T_j = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	FST6310M	FST6315M	FST6320M	FST6330M	FST6335M	Unit
Average forward current (per pkg)	$I_{F(AV)}$	$T_C = 125\text{ }^{\circ}\text{C}$	60	60	60	60	60	A
Peak forward surge current (per leg)	I_{FSM}	$t_p = 8.3\text{ ms}$, half sine	600	600	600	600	600	A
Maximum instantaneous forward voltage (per leg)	V_F	$I_{FM} = 30\text{ A}$, $T_j = 25\text{ }^{\circ}\text{C}$	0.70	7.0	0.70	0.70	0.70	V
Maximum Instantaneous reverse current at rated DC blocking voltage (per leg)	I_R	$T_j = 25\text{ }^{\circ}\text{C}$	1	1	1	1	1	mA
		$T_j = 100\text{ }^{\circ}\text{C}$	10	10	10	10	10	
		$T_j = 150\text{ }^{\circ}\text{C}$	30	30	30	30	30	

Thermal characteristics

Thermal resistance, junction - case (per leg)	$R_{\theta JC}$		1.20	1.20	1.20	1.20	1.20	$^{\circ}\text{C/W}$
---	-----------------	--	------	------	------	------	------	----------------------

Figure .1- Typical Forward Characteristics




Figure .2- Forward Derating Curve




Figure.3-Peak Forward Surge Current






Figure .4- Typical Reverse Characteristics



Package dimensions and terminal configuration

Product is marked with part number and terminal configuration.



DIMENSIONS					
DIM	IN CHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	1.180	1.195	29.97	30.35	
B	.200	NOM	5.08	NOM	2PL
C	.027	.037	0.69	0.94	
D	.088	.098	2.24	2.49	
E	.350	.370	8.89	9.40	
F	1.490	1.510	37.85	38.35	
G	.695	.715	17.65	18.16	
J	.24	.26	6.1	6.6	
K	.115	.135	2.92	3.43	
L	.457	.477	11.61	12.12	
M	.065	.085	1.65	2.16	
N	.151	.161	3.84	4.09	Ø
P	.015	.025	0.38	0.64	