FIND DISTRIBUTOR

FAQ

PRODUCTS

English 日本語 한국어 简体中文 Deutsch Español Русский

RESOURCES

Home: I/O Connectors >

Ω

Part Number: 56381-1200

CRC™ Shielded Rectangular I/O Shell Cover, For Plug Assembly, 12 Circuits

Category:

INDUSTRY SOLUTIONS



Status: **OBSOLETE** Replacement: 56381-1228 Series:

56381 I/O Connectors

Go to Part Detail▼

CHECK DISTRIBUTOR INVENTORY

CONTACT MOLEX

Add to My Parts

Email this page

Application Tooling

Specification document.

Series image - Reference only

Use With Part(s):

56380 Plug Shell Body, 56382 Cable Clamp, 51235 and 51236 Mold Cover, 58203 Cross Recesseα Head Screw

CAREERS

Product Environmental Compliance

EU ELV:Product not active

EU RoHS: Product not active

EU RoHS Phthalates: Product not active

China RoHS:

REACH SVHC: Product not active

Low-Halogen Status: Product not active

EU RoHS Certificate of Compliance (PDF) Multiple Part Product Compliance Statements

Documents

*IPC 1752A Class C *IPC 1752A Class D

*Molex Product Compliance Declaration

EU RoHS, REACH SVHC, & Low-Halogen

Multiple Part Industry Compliance

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then

contained in the Application Tooling

Previously Available Application

Check our list of old tooling that used to be available for this part

Questions on Product Environmental Compliance? EmailProductCompliance@molex.com

Request Molex's CMRT from conflictminerals@molex.com

Part Detail

COLLAPSE ALL

General

Status	Obsolete
Category	I/O Connectors
Series	<u>56381</u>
Application	N/A
Component Type	Plug Shell Cover
Product Name	CRC™
Туре	N/A
UPC	800756194080

Physical

Circuits (Loaded)	N/A
Circuits (maximum)	12
Durability (mating cycles max)	100
Lock to Mating Part	Yes
Material - Metal	Phosphor Bronze
Material - Plating Mating	N/A
Net Weight	5978.190/mg
Orientation	Vertical
Packaging Type	Tray
Panel Mount	N/A
Pitch - Mating Interface	N/A
Polarized to Mating Part	N/A
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	N/A
Waterproof / Dustproof	No
▼ Floctrical	

Electrical

Current - Maximum per	4.04
	4.0A

(Please review the Product Specification for specific details.)

Contact	
Voltage - Maximum	250V AC (RMS)/DC

PRODUCTS

Antennas

Application Tooling Cable Assemblies Connected Lighting Connectors Copper Flex Electrical Products Industrial Automation Membrane Switches Optical Solutions Printed Electronic Solutions

Company Information

QUICK LINKS

Contact Molex Cross-Reference Koch Industries Industries Investor Relations Literature Molex Racing Press Room / Press Releases Product Index Sitemap

Terms & Conditions

Supply Chain Transparency

RESOURCES

Tradeshows

Business Continuity Compliance ecocare Feedback | Help Jobs Legal | Trademarks Mobile Site Supplier Portal Privacy Policy

STAY CONNECTED









