


# Axial Lead & Cartridge Fuses

5×20 mm > Fast-Acting > 235 Series

## 235 Series, 5×20 mm, Fast-Acting Fuse



### Agency Approvals

| Agency | Agency File Number              | Ampere Range    |
|--------|---------------------------------|-----------------|
|        | Cartridge:<br>NBK030609-JP1021A | 1A - 3.5A       |
|        | NBK190609-JP1021A               | 4A - 5A         |
|        | NBK030609-JP1021B               | 6A - 7A         |
|        | Leaded:<br>NBK030609-JP1021C    | 1A - 3.5A       |
|        | NBK190609-JP1021B               | 4A - 5A         |
|        | SU05001 - 3007                  | 0.100A - 0.400A |
|        | SU05001 - 2002                  | 0.500A - 3A     |
|        | SU05001 - 2003                  | 4A - 6A         |
|        | E10480                          | 0.100A - 7A     |
|        | 29862                           | 0.100A - 7A     |
|        | N/A                             | 0.100A - 7A     |

### Description

5×20mm fast-acting glass body cartridge fuse designed to UL specification.

### Features

- Designed to UL/CSA/ANCE 248 Standard
- RoHS compliant and lead-free
- Available in cartridge and axial lead format

### Applications

Used as supplementary protection in appliance or utilization equipment to provide individual protection for components or internal circuits.

### Electrical Characteristics for Series

| % of Ampere Rating | Ampere Rating | Opening Time       |
|--------------------|---------------|--------------------|
| 100%               | 0.100A - 7A   | 4 hours, Minimum   |
| 135%               |               | 1 hour, Maximum    |
| 200%               |               | 5 seconds, Maximum |

### Additional Information



**Datasheet**



**Resources**



**Samples**




**Accessories**

For recommended fuse accessories for this product series, see '[Recommended Accessories](#)' section.

## Electrical Characteristic Specifications by Item


| Amp Code | Amp Rating (A) | Voltage Rating (V) | Interrupting Rating            | Nominal Cold Resistance (Ohms) | Nominal Melting $I^2t$ (A <sup>2</sup> sec) | Agency Approvals |    |    |      |    |
|----------|----------------|--------------------|--------------------------------|--------------------------------|---------------------------------------------|------------------|----|----|------|----|
|          |                |                    |                                |                                |                                             | CE               | UL | SP | PS E | RC |
| .100     | 0.1            | 250                | 35A @ 250VAC<br>10kA @ 125VAC  | 8.4000                         | 0.00127                                     | x                | x  | x  |      | x  |
| .125     | 0.125          | 250                |                                | 5.7500                         | 0.00273                                     | x                | x  | x  |      | x  |
| .200     | 0.2            | 250                |                                | 3.1500                         | 0.00867                                     | x                | x  | x  |      | x  |
| .250     | 0.25           | 250                |                                | 2.2500                         | 0.01660                                     | x                | x  | x  |      | x  |
| .300     | 0.3            | 250                |                                | 1.6000                         | 0.03215                                     | x                | x  | x  |      | x  |
| .400     | 0.4            | 250                |                                | 1.075                          | 0.05845                                     | x                | x  | x  |      | x  |
| .500     | 0.5            | 250                |                                | 0.4265                         | 0.06915                                     | x                | x  | x  |      | x  |
| .600     | 0.6            | 250                |                                | 0.3195                         | 0.11200                                     | x                | x  | x  |      | x  |
| .700     | 0.7            | 250                |                                | 0.2625                         | 0.15600                                     | x                | x  | x  |      | x  |
| .800     | 0.8            | 250                |                                | 0.1920                         | 0.25300                                     | x                | x  | x  |      | x  |
| 001.     | 1              | 250                | 100A @ 250VAC<br>10kA @ 125VAC | 0.1530                         | 0.46750                                     | x                | x  | x  | x    | x  |
| 1.25     | 1.25           | 250                |                                | 0.1055                         | 1.08500                                     | x                | x  | x  | x    | x  |
| 01.6     | 1.6            | 250                |                                | 0.0758                         | 2.02500                                     | x                | x  | x  | x    | x  |
| 002.     | 2              | 250                |                                | 0.0603                         | 2.64500                                     | x                | x  | x  | x    | x  |
| 02.5     | 2.5            | 250                |                                | 0.0437                         | 5.44500                                     | x                | x  | x  | x    | x  |
| 003.     | 3              | 250                |                                | 0.0347                         | 8.39500                                     | x                | x  | x  | x    | x  |
| 03.5     | 3.5            | 250                |                                | 0.0331                         | 17.14000                                    | x                | x  |    | x    |    |
| 004.     | 4              | 125                | 10kA @ 125VAC                  | 0.0246                         | 17.14000                                    | x                | x  | x  | x    | x  |
| 005.     | 5              | 125                |                                | 0.0184                         | 27.41000                                    | x                | x  | x  | x    | x  |
| 006.     | 6              | 125                |                                | 0.0148                         | 47.32500                                    | x                | x  | x  | x    | x  |
| 007.     | 7              | 125                |                                | 0.0157                         | 64.81500                                    | x                | x  |    | x    |    |

## Temperature Re-rating Curve




Note:  
Rerating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

## Average Time Current Curves



Please contact Littelfuse for details on T-C curve for 7A rating

### Soldering Parameters - Wave Soldering



### Recommended Process Parameters:

| Wave Parameter                                                                                | Lead-Free Recommendation |
|-----------------------------------------------------------------------------------------------|--------------------------|
| <b>Preheat:</b><br>(Depends on Flux Activation Temperature) (Typical Industry Recommendation) |                          |
| Temperature Minimum:                                                                          | 100°C                    |
| Temperature Maximum:                                                                          | 150°C                    |
| Preheat Time:                                                                                 | 60-180 seconds           |
| <b>Solder Pot Temperature:</b>                                                                | 260°C Maximum            |
| <b>Solder Dwell Time:</b>                                                                     | 2-5 seconds              |

### Recommended Hand-Solder Parameters:

Solder Iron Temperature: 350°C +/- 5°C  
Heating Time: 5 seconds max.

**Note: These devices are not recommended for IR or Convection Reflow process.**


### Product Characteristics

|                          |                                                                                             |
|--------------------------|---------------------------------------------------------------------------------------------|
| <b>Materials</b>         | Body: Glass<br>Cap: Nickel-plated brass<br>Leads: Tin-plated Copper                         |
| <b>Terminal Strength</b> | MIL-STD-202, Method 211 .<br>Test Condition A                                               |
| <b>Solderability</b>     | MIL-STD-202 Method 208                                                                      |
| <b>Product Marking</b>   | Cap 1: Brand logo, current and voltage rating<br>Cap 2: Series and agency approval markings |
| <b>Packaging</b>         | Available in Bulk (M=1000 pcs/pkg) or on Tape/Reel (MRET1=1000 pcs/reel)                    |


|                              |                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------|
| <b>Operating Temperature</b> | -55°C to +125°C                                                                                       |
| <b>Thermal Shock</b>         | MIL-STD-202, Method 107, Test Condition B: (5 cycles -65°C + 125°C)                                   |
| <b>Vibration</b>             | MIL-STD-202, Method 201                                                                               |
| <b>Humidity</b>              | MIL-STD-202, Method 103, Test Condition A high RH (95%) and elevated temperature (40°C) for 240 hours |
| <b>Salt Spray</b>            | MIL-STD-202, Method 101, Test Condition B                                                             |

## Dimensions


**0235000P**



**0235.100 XEP  
to  
0235.400 XEP**



**0235.500 XEP  
to  
0235006.XEP**




All dimensions in mm

Notes:

\* Ratings above 6.3A have 0.8±0.05 diameter lead.

## Part Numbering System



## Packaging

| Packaging Option  | Packaging Specification | Quantity | Quantity & Packaging Code | Taping Width     |
|-------------------|-------------------------|----------|---------------------------|------------------|
| <b>235 Series</b> |                         |          |                           |                  |
| Bulk              | N/A                     | 1000     | MX                        | N/A              |
| Bulk              | N/A                     | 1000     | MXE                       | N/A              |
| Reel and Tape     | EIA 296-E               | 1000     | MRET1                     | T1=53mm (2.087") |

## Recommended Accessories

| Accessory Type | Series                  | Description                                                               | Max Application Voltage | Max Application Amperage |
|----------------|-------------------------|---------------------------------------------------------------------------|-------------------------|--------------------------|
| Holder         | <a href="#">345_ISF</a> | Panel Mount Shock-Safe Fuseholder                                         | 250                     | 10                       |
|                | <a href="#">345</a>     | Shock-Safe Fuseholder with PC Mount, Solder Mount and Panel Mount options |                         | 20                       |
|                | <a href="#">830</a>     | PC Mount Shock-Safe Miniature Fuseholder                                  |                         | 16                       |
| Block          | <a href="#">520</a>     | Metric OMNI-BLOK® Fuse Block                                              |                         | 10                       |
|                | <a href="#">646</a>     | PC Mount Miniature Fuse Block                                             |                         | 6.3                      |
|                | <a href="#">658</a>     | Surface Mount Miniature Fuse Block                                        |                         | 10                       |
| Clip           | <a href="#">520_W</a>   | PC Mount Miniature Fuse Clip                                              |                         | 6.3                      |
|                | <a href="#">111</a>     | PC Board Mount Fuse Clip                                                  |                         | 10                       |
|                | <a href="#">445</a>     | PC Board Mount Fuse Clip                                                  |                         | 10                       |

Notes:

- Do not use in applications above rating.
- Please refer to fuseholder data sheet for specific re-rating information.
- Please contact factory for applications greater than the max voltage and amperage shown.

**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).