

# M62352P,FP,GP

## 8-BIT 12CH D-A CONVERTER WITH BUFFER AMPLIFIERS

### DESCRIPTION

The M62352 is an integrated circuit semiconductor of CMOS structure with 12 channels of built-in D-A converters with output buffer operational amplifiers.

The 3-wire serial interface method is used for the transfer format mum wiring.

It is able to cascading serial use with Do terminal.

The output buffer operational amplifier operates in the whole voltage range from power supply to ground for both input/output.


### FEATURES

- 12bit serial data input(3-wire serial data transfer method)
- Highly stable output buffer operational amplifier allow operation in the all voltage range from power supply to ground.

### APPLICATION


Adjustment/control of industrial or home-use electronic equipment,such as VTR camera,VTR set,TV,and CRT display.

### PIN CONFIGURATION (TOP VIEW)




Outline 20P4B(P)  
20P2N-A(FP)  
20P2E-A(GP)

### BLOCK DIAGRAM



**M62352P,FP,GP****8-BIT 12CH D-A CONVERTER WITH BUFFER AMPLIFIERS****EXPLANATION OF TERMINALS**


| Pin No. | Symbol | Function                                                  |
|---------|--------|-----------------------------------------------------------|
| ①⑦      | DI     | Serial data input terminal                                |
| ①④      | DO     | Serial data output terminal                               |
| ①⑥      | CLK    | Serial clock input terminal                               |
| ①⑤      | LD     | LD terminal input high level than latch circuit data load |
| ①⑧      | Ao1    | 8-bit D-A converter output terminal                       |
| ①⑨      | Ao2    |                                                           |
| ②       | Ao3    |                                                           |
| ③       | Ao4    |                                                           |
| ④       | Ao5    |                                                           |
| ⑤       | Ao6    |                                                           |
| ⑥       | Ao7    |                                                           |
| ⑦       | Ao8    |                                                           |
| ⑧       | Ao9    |                                                           |
| ⑨       | Ao10   |                                                           |
| ⑫       | Ao11   |                                                           |
| ⑬       | Ao12   |                                                           |
| ⑪       | Vcc    | Power supply terminal                                     |
| ⑳       | GND    | Digital and analog common GND                             |
| ⑩       | VDD    | D-A converter upper reference voltage input terminal      |
| ①       | VSS    | D-A converter lower reference voltage input terminal      |

**BLOCK DIAGRAM FOR EXPLANATION OF TERMINALS**

# M62352P,FP,GP

## 8-BIT 12CH D-A CONVERTER WITH BUFFER AMPLIFIERS

### DIGITAL DATA FORMAT




| D0 | D1 | D2 | D3 | D4 | D5 | D6 | D7 | D-A output                                      |
|----|----|----|----|----|----|----|----|-------------------------------------------------|
| 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | $(V_{refU}-V_{refL})/256 \times 1 + V_{refL}$   |
| 1  | 0  | 0  | 0  | 0  | 0  | 0  | 0  | $(V_{refU}-V_{refL})/256 \times 2 + V_{refL}$   |
| 0  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | $(V_{refU}-V_{refL})/256 \times 3 + V_{refL}$   |
| 1  | 1  | 0  | 0  | 0  | 0  | 0  | 0  | $(V_{refU}-V_{refL})/256 \times 4 + V_{refL}$   |
| ⋮  | ⋮  | ⋮  | ⋮  | ⋮  | ⋮  | ⋮  | ⋮  | ⋮                                               |
| 0  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | $(V_{refU}-V_{refL})/256 \times 255 + V_{refL}$ |
| 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1  | $V_{refU}$                                      |

| D8 | D9 | D10 | D11 | DAC selection |
|----|----|-----|-----|---------------|
| 0  | 0  | 0   | 0   | Don't care    |
| 0  | 0  | 0   | 1   | Ao1 selection |
| 0  | 0  | 1   | 0   | Ao2           |
| 0  | 0  | 1   | 1   | Ao3           |
| 0  | 1  | 0   | 0   | Ao4           |
| 0  | 1  | 0   | 1   | Ao5           |
| 0  | 1  | 1   | 0   | Ao6           |
| 0  | 1  | 1   | 1   | Ao7           |
| 1  | 0  | 0   | 0   | Ao8           |
| 1  | 0  | 0   | 1   | Ao9           |
| 1  | 0  | 1   | 0   | Ao10          |
| 1  | 0  | 1   | 1   | Ao11          |
| 1  | 1  | 0   | 0   | Ao12          |
| 1  | 1  | 0   | 1   | Don't care    |
| 1  | 1  | 1   | 0   | Don't care    |
| 1  | 1  | 1   | 1   | Don't care    |

\* $V_{refU}=V_{DD}$   
 $V_{refL}=V_{SS}$

### TIMING CHART (MODEL)



# M62352P,FP,GP

## 8-BIT 12CH D-A CONVERTER WITH BUFFER AMPLIFIERS

### ABSOLUTE MAXIMUM RATINGS

| Symbol           | Parameter                             | Conditions | Ratings                   | Unit |
|------------------|---------------------------------------|------------|---------------------------|------|
| V <sub>CC</sub>  | Supply voltage                        |            | -0.3~7.0                  | V    |
| V <sub>DD</sub>  | D-A converter upper reference voltage |            | -0.3~7.0                  | V    |
| V <sub>IN</sub>  | Input voltage                         |            | -0.3~V <sub>CC</sub> +0.3 | V    |
| V <sub>O</sub>   | Output voltage                        |            | -0.3~V <sub>CC</sub> +0.3 | V    |
| P <sub>d</sub>   | Power dissipation                     |            | 350(P)/350(FP)/150(GP)    | mW   |
| T <sub>opr</sub> | Operating temperature                 |            | -20~+85                   | °C   |
| T <sub>stg</sub> | Storage temperature                   |            | -55~+125                  | °C   |

### ELECTRICAL CHARACTERISTICS

**Digital part**(V<sub>CC</sub>,V<sub>refU</sub>=+5V±10%,V<sub>CC</sub>≥V<sub>refU</sub>,GND,V<sub>refL</sub>=0V,T<sub>a</sub>=-20°C~+85°C, unless otherwise noted)

| Symbol           | Parameter           | Test conditions                            | Limits             |                      |                    | Unit |
|------------------|---------------------|--------------------------------------------|--------------------|----------------------|--------------------|------|
|                  |                     |                                            | Min.               | Typ.                 | Max.               |      |
| V <sub>CC</sub>  | Supply voltage      |                                            | 4.5                | 5.0                  | 5.5                | V    |
| I <sub>CC</sub>  | Circuit current     | CLK=1MHz operation<br>I <sub>OA</sub> =0μA |                    | 1.6                  | 3.2                | mA   |
| I <sub>ILK</sub> | Input leak current  | V <sub>IN</sub> =0~V <sub>CC</sub>         | -10                |                      | 10                 | μA   |
| V <sub>IL</sub>  | Input low voltage   |                                            |                    |                      | 0.2V <sub>CC</sub> | V    |
| V <sub>IH</sub>  | Input high voltage  |                                            | 0.8V <sub>CC</sub> |                      |                    | V    |
| V <sub>OL</sub>  | Output low voltage  | I <sub>OL</sub> =2.5mA                     |                    |                      | 0.4                | V    |
| V <sub>OH</sub>  | Output high voltage | I <sub>OH</sub> =-400μA                    |                    | V <sub>CC</sub> -0.4 |                    | V    |

**Analog part**(V<sub>CC</sub>,V<sub>refU</sub>=+5V±10%,V<sub>CC</sub>≥V<sub>refU</sub>,T<sub>a</sub>=-20°C~+85°C, unless otherwise noted)

| Symbol            | Parameter                                   | Test conditions                                                                                                                                                                        | Limits |      |                      | Unit |
|-------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------|----------------------|------|
|                   |                                             |                                                                                                                                                                                        | Min.   | Typ. | Max.                 |      |
| I <sub>DD</sub>   | Current dissipation                         | V <sub>refU</sub> =5V,V <sub>refL</sub> =0V<br>Data condition;at maximum current                                                                                                       |        | 1.4  | 2.5                  | mA   |
| V <sub>DD</sub>   | D-A converter upper reference voltage range | The output dose not necessarily be the value within the reference voltage setting range. The output value is determined by the buffer amplifier output voltage range(V <sub>AO</sub> ) | 3.5    |      | V <sub>CC</sub>      | V    |
| V <sub>SS</sub>   | D-A converter lower reference voltage range |                                                                                                                                                                                        | GND    |      | V <sub>CC</sub> -3.5 | V    |
| V <sub>AO</sub>   | Buffer amplifier output voltage range       | I <sub>OA</sub> =±100μA                                                                                                                                                                | 0.1    |      | V <sub>CC</sub> -0.1 | V    |
|                   |                                             | I <sub>OA</sub> =±500μA                                                                                                                                                                | 0.2    |      | V <sub>CC</sub> -0.2 |      |
| I <sub>AO</sub>   | Buffer amplifier output drive range         | Upper side saturation voltage=0.3V<br>Lower side saturation voltage=0.2V                                                                                                               | -1     |      | 1                    | mA   |
| SD <sub>L</sub>   | Differential nonlinearity error             | V <sub>refU</sub> =4.79V                                                                                                                                                               | -1.0   |      | 1.0                  | LSB  |
| SL                | Nonlinearity error                          | V <sub>refL</sub> =0.95V                                                                                                                                                               | -1.5   |      | 1.5                  | LSB  |
| S <sub>ZERO</sub> | Zero code error                             | V <sub>CC</sub> =5.5V(15mV/LSB)                                                                                                                                                        | -2     |      | 2                    | LSB  |
| S <sub>FULL</sub> | Full scale error                            | Without load(I <sub>OA</sub> =±0)                                                                                                                                                      | -2     |      | 2                    | LSB  |
| C <sub>O</sub>    | Output capacitive load                      |                                                                                                                                                                                        |        |      | 0.1                  | μF   |
| R <sub>O</sub>    | Buffer amplifier output impedance           |                                                                                                                                                                                        |        | 5    |                      | Ω    |


# M62352P,FP,GP

## 8-BIT 12CH D-A CONVERTER WITH BUFFER AMPLIFIERS

**AC CHARACTERISTICS**( $V_{CC}, V_{REFU}=+5V \pm 10\%$ ,  $V_{CC} \geq V_{REFU}, GND, V_{REFL}=0V$ ,  $T_a=-20 \sim +85^{\circ}C$ , unless otherwise noted)

| Symbol | Parameter               | Test conditions                                                                                                 | Limits |     |     | Unit    |
|--------|-------------------------|-----------------------------------------------------------------------------------------------------------------|--------|-----|-----|---------|
|        |                         |                                                                                                                 | Min    | Typ | Max |         |
| tCLK   | Clock "L" pulse width   |                                                                                                                 | 200    |     |     | ns      |
| tCKH   | Clock "H" pulse width   |                                                                                                                 | 200    |     |     | ns      |
| tCR    | Clock rise time         |                                                                                                                 |        |     | 200 | ns      |
| tCF    | Clock fall time         |                                                                                                                 |        |     | 200 | ns      |
| tdCH   | Data setup time         |                                                                                                                 | 30     |     |     | ns      |
| tCHD   | Data hold time          |                                                                                                                 | 60     |     |     | ns      |
| tCHL   | LD setup time           |                                                                                                                 | 200    |     |     | ns      |
| tLDC   | LD hold time            |                                                                                                                 | 100    |     |     | ns      |
| tLDH   | LD "H" pulse width      |                                                                                                                 | 100    |     |     | ns      |
| tDO    | Data output delay time  | $C_L \leq 100pF$                                                                                                | 70     |     | 350 | ns      |
| tLDD   | D-A output setting time | $C_L \leq 100pF$ $V_{AQ}: 0.5 \rightarrow 4.5V$<br>The time until the output becomes the final value of 1/2 LSB |        |     | 300 | $\mu s$ |



### TIMING CHART



# M62352P,FP,GP

## 8-BIT 12CH D-A CONVERTER WITH BUFFER AMPLIFIERS

### TYPICAL CHARACTERISTICS



### SATURATION VOLTAGE VS.OUTPUT CURRENT