

HDC enclosures**HDC HQM TSLU 1PG21****Weidmüller Interface GmbH & Co. KG**

Klingenbergsstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection. The HQ version now offers particular protection - the bulkhead housing (cover and metal clamp) can be secured with a padlock.

General ordering data

Order No.	1003100000
Type	HDC HQM TSLU 1PG21
Version	HDC enclosures, Size: HQ, Protection degree: IP 65, Cable entry from side, Plug housing, Side-locking clamp on lower side, Standard, Size of cable entries: PG 21
GTIN (EAN)	4032248698035
Qty.	1 pc(s).

HDC enclosures
HDC HQM TSLU 1PG21

Weidmüller Interface GmbH & Co. KG
Klingenbergsstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Dimensions and weights**

Length	50 mm	Width	35 mm
Height	60.5 mm	Net weight	173 g

Dimensions

Total length housing	50 mm	Width housing C	29 mm
Height of housing B	60.5 mm	Cable entry	w. threading

General data

Housing main material	Zinc diecast
-----------------------	--------------

Version

Design of housing	Cable entry from side, Plug housing	Size	HQ
Design	Standard	Top part/bottom part/lid	upper part
Design of locking system	Side-locking clamp on lower side	Cable entry	w. threading
Size of cable entries	PG 21	Number of cable entry on top	0
Number of cable entry sideways	1		

Classifications

ETIM 2.0	EC000437	ETIM 3.0	EC000437
UNSPSC	30-21-18-01	eClass 4.1	27-14-08-05
eClass 5.1	27-14-34-19	eClass 6.2	27-14-34-19
eClass 7.1	27-44-02-05		

Approvals

ROHS	Conform
------	---------