

7 outlet, 7-ft cord, 2160 joule black strip - Protect It! Surge Suppressor

MODEL NUMBER: SUPER7B











Highlights

- 7 outlets/7 ft. cord
- 2160 joule rating
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

Applications

Personal computers,
CAD/CAM/CAE workstations,
network nodes, fileservers,
point-of-sale terminals,
audio/visual devices, and more.

Package Includes

- SUPER7B Surge Suppressor
- Instruction manual with warranty information

Description

The SUPER7B Surge Suppressor from Tripp Lite has 7 outlets, a 7-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2160 joules to handle the strongest surges. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 7 outlets
- 7-ft. cord with space-saving right-angle plug
- Surge suppression rating: 2160 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment
- Diagnostic LEDs indicate protection present & ground present
- . Keyhole supports for wall mounting

Specifications

General Info		
Product Group	SURGE PROTECTORS	
OVERVIEW		
Intended Application	Home/Office	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	





Shipping Dimensions (hwd / in.)	12.40 x 5.90 x 1.77
PHYSICAL	
Network (Ethernet) Protection	No
Cable (Coax) Protection	No
Telephone/DSL Protection	No
DATALINE SURGE SUPPRESSION	
EMI / RFI Filtering	Up to 20 dB
UL1449 Let Through Rating	330 L-G, 400 L-N, 400 N-G
Clamping Voltage (RMS)	150
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC Suppression Response Time	< 1 ns
AC Suppression Joule Rating	2160
SURGE / NOISE SUPPRESSION	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Switches	Two position on/off power switch
LEDS ALARMS & SWITCHES	
Maximum Surge Amps	144000
Voltage Compatibility (VAC)	120
Input Cord Gauge Type	14 gauge, SJT
Input Cord Length (m)	2.1
Input Cord Length (ft.)	7
Input Connection Type	NEMA 5-15P
Recommended Electrical Service	120V (110-125V)
Nominal Input Voltage(s) Supported	120V AC
INPUT	
Outlet Orientation	Single row of 5, plus 2 side mounted outlets
Transformer Accommodation	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total
Number of Outlets	7
Outlet Quantity / Type	7 NEMA 5-15R
Circuit Breaker (amps)	15





Shipping Dimensions (hwd / cm)	31.50 x 14.99 x 4.50	
Shipping Weight (lbs.)	1.56	
Shipping Weight (kg)	0.71	
Unit Dimensions (hwd / in.)	1.54 x 2.72 x 10.30	
Unit Dimensions (hwd / cm)	3.91 x 6.91 x 26.16	
Unit Weight (lbs.)	1.39	
Unit Weight (kg)	0.63	
Material of Construction	Plastic	
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs enable wall mounting	
Housing Color	Black	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Style	Strip	
Outlets Measurement (Center to Center)	Between Standard Outlets = 29mm; Between Transformer Outlets = 48mm	
Keyhole Slot Mounting Measurement (Center to Center)	Distance Between Slots = 78mm; Distance Between Slot Height = 24mm	
SPECIAL FEATURES		
Right-Angle Plug	Yes	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$75,000 Ultimate Lifetime Insurance	

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.