

### PE42359

**SPDT UltraCMOS® RF Switch**  
10 MHz – 3 GHz

#### Product Description


The PE42359 UltraCMOS® RF switch is designed to cover a broad range of applications from 10 MHz through 3 GHz. This reflective switch integrates on-board CMOS control logic with a low voltage CMOS-compatible control interface, and can be controlled using either single-pin or complementary control inputs. Using a nominal +3-volt power supply voltage, a typical input 1 dB compression point of +33.5 dBm can be achieved. PE42359 also meets the quality and performance standards for automotive applications and has received AEC-Q100 Grade 2 certification.

The PE42359 is manufactured on Peregrine's UltraCMOS® process, a patented variation of silicon-on-insulator (SOI) technology on a sapphire substrate, offering the performance of GaAs with the economy and integration of conventional CMOS.

#### Features

- AEC-Q100 Grade 2 certified
- Supports operating temperature up to +105°C
- Single-pin or complementary CMOS logic control inputs
- Low insertion loss
  - 0.35 dB @ 1000 MHz
  - 0.50 dB @ 2000 MHz
- Isolation of 30 dB @ 1000 MHz
- High ESD tolerance of 2kV HBM
- Typical input 1 dB compression point of +33.5 dBm
- 1.8V minimum power supply voltage
- Small SC-70 package

**Figure 1. Functional Diagram**



**Figure 2. Package Type**  
6-lead SC-70



**Table 1. Electrical Specifications @ +25°C, V<sub>DD</sub> = 3.0V (Z<sub>S</sub> = Z<sub>L</sub> = 50Ω )**


Parameter	Conditions	Minimum	Typical	Maximum	Units
Operation Frequency <sup>1</sup>		10		3000	MHz
Insertion Loss <sup>2</sup>	10-1000 MHz		0.35	0.45	dB
	1000-2000 MHz		0.50	0.60	dB
	2000-3000 MHz <sup>2</sup>		1.1	1.3	dB
Isolation - RFX to RFX	10-1000 MHz	32	35		dB
	1000-2000 MHz	20	21		dB
	2000-3000 MHz	13	14		dB
Isolation - RFC to RFX	10-1000 MHz	28	29		dB
	1000-2000 MHz	19	20		dB
	2000-3000 MHz	12	13		dB
Return Loss - RFX to RFC <sup>2</sup>	10-1000 MHz	21	25		dB
	1000-2000 MHz	15	18		dB
	2000-3000 MHz <sup>2</sup>	9	11		dB
Switching Time	50% CTRL to 90% or 10% RF		2		us
Video Feedthrough <sup>3</sup>			15		mV <sub>pp</sub>
Input 1 dB Compression	1000 MHz @ 2.3 - 3.3V	31.5	33.5		dBm
	1000 MHz @ 1.8 - 2.3V	29.5	30.5		
	2500 MHz @ 2.3 - 3.3V	28.5	30.5		
	2500 MHz @ 1.8 - 2.3V	28	29		
Input IP3	2500 MHz, 20 dBm input power		55		dBm

Notes: 1. Device linearity will begin to degrade below 10 MHz  
2. High frequency performance can be improved by external matching (see Figure 20 through Figure 25 and Figure 28)  
3. The DC transient at the output of any port of the switch when the control voltage is switched from Low to High or High to Low in a 50Ω test set-up, measured with 1ns risetime pulses and 500 MHz bandwidth

**Table 1A. Electrical Specifications @ -40°C to +105°C, V<sub>DD</sub> = 3.0V (Z<sub>S</sub> = Z<sub>L</sub> = 50Ω )**

Parameter	Conditions	Minimum	Typical	Maximum	Units
Operation Frequency		10		3000	MHz
Insertion Loss	10-1000 MHz		0.35	0.6	dB
	1000-2000 MHz		0.5	0.75	dB
	2000-3000 MHz		1.1	1.4	dB
Isolation - RFX to RFX	10-1000 MHz	31	35		dB
	1000-2000 MHz	19	21		dB
	2000-3000 MHz	12	14		dB
Isolation - RFC to RFX	10-1000 MHz	27	29		dB
	1000-2000 MHz	18	20		dB
	2000-3000 MHz	11	13		dB
Return Loss - RFX to RFC	10-1000 MHz	20	25		dB
	1000-2000 MHz	14	18		dB
	2000-3000 MHz	9	11		dB
Switching Time	50% CTRL to 90% or 10% RF		3.6		us
Video Feedthrough			15		mV <sub>pp</sub>
Input 1 dB Compression	1000 MHz @ 2.3 - 3.3V	30.5	33.5		dBm
	1000 MHz @ 1.8 - 2.3V	28.5	30.5		
	2500 MHz @ 2.3 - 3.3V	27.5	30.5		
	2500 MHz @ 1.8 - 2.3V	27	29		
Input IP3	2500 MHz, 20 dBm input power		54		dBm

**Figure 3. Pin Configuration (Top View)**



**Table 2. Pin Descriptions**

Pin No.	Pin Name	Description
1	RF1 <sup>1</sup>	RF Port1
2	GND	Ground connection. Traces should be physically short and connected to ground plane for best performance.
3	RF2 <sup>1</sup>	RF Port2
4	CTRL	Switch control input, CMOS logic level.
5	RFC <sup>1</sup>	RF Common
6	$\overline{\text{CTRL}}$ or $V_{DD}$	This pin supports two interface options: <i>Single-pin control mode.</i> A nominal 3-volt supply connection is required.  <i>Complementary-pin control mode.</i> A complementary CMOS control signal to CTRL is supplied to this pin. Bypassing on this pin is not required in this mode.

Note 1: All RF pins must be DC blocked with an external series capacitor or held at 0 VDC

**Table 3. Operating Ranges**

Parameter	Min	Typ	Max	Units
$V_{DD}$ Power Supply Voltage	1.8	3.0	3.3	V
$I_{DD}$ Power Supply Current ( $V_{DD} = 2.3$ to $5.5V$ [+25°C only])		9	20	$\mu A$
Control Voltage High	$0.7 \times V_{DD}$			V
Control Voltage Low			$0.3 \times V_{DD}$	V

### Moisture Sensitivity Level

The Moisture Sensitivity Level rating for the PE42359 in the SC70 package is MSL1.


**Table 4. Absolute Maximum Ratings**

Symbol	Parameter/Conditions	Min	Max	Units
$V_{DD}$	Power supply voltage	-0.3	4.0	V
$V_I$	Voltage on any DC input	-0.3	$V_{DD} + 0.3$	V
$T_{ST}$	Storage temperature range	-65	150	°C
$T_{OP}$	Operating temperature range	-40	105	°C
$P_{IN}^1$	Input power (50 $\Omega$ )		see fig. 4	
$V_{ESD,HBM}$	ESD voltage HBM <sup>2</sup> , all pins		2000	V
$V_{ESD,CDM}$	ESD voltage CDM <sup>3</sup> , all pins		1000	V

Notes: 1. To maintain optimum device performance, do not exceed Max  $P_{IN}$  at desired operating frequency (see Figure 4)  
2. Human Body Model (MIL-STD 883 Method 3015)  
3. Charged Device Model (JEDEC JESD22-C101)

Exceeding absolute maximum ratings may cause permanent damage. Operation should be restricted to the limits in the Operating Ranges table. Operation between operating range maximum and absolute maximum for extended periods may reduce reliability.

**Figure 4. Maximum Power Handling**



### Electrostatic Discharge (ESD) Precautions

When handling this UltraCMOS® device, observe the same precautions that you would use with other ESD-sensitive devices. Although this device contains circuitry to protect it from damage due to ESD, precautions should be taken to avoid exceeding the specified rating.

**Table 5. Single-pin Control Logic Truth Table**

Control Voltages	Signal Path
Pin 6 ( $V_{DD}$ ) = $V_{DD}$ Pin 4 (CTRL) = High	RFC to RF1
Pin 6 ( $V_{DD}$ ) = $V_{DD}$ Pin 4 (CTRL) = Low	RFC to RF2

**Table 6. Complementary-pin Control Logic Truth Table**

Control Voltages	Signal Path
Pin 6 ( $\overline{CTRL}$ or $V_{DD}$ ) = Low Pin 4 (CTRL) = High	RFC to RF1
Pin 6 ( $\overline{CTRL}$ or $V_{DD}$ ) = High Pin 4 (CTRL) = Low	RFC to RF2

### Latch-Up Avoidance

Unlike conventional CMOS devices, UltraCMOS<sup>®</sup> devices are immune to latch-up.

### Switching Frequency

The PE42359 has a maximum 25 kHz switching rate.

### Control Logic Input

The PE42359 is a versatile RF CMOS switch that supports two operating control modes; single-pin control mode and complementary-pin control mode.

*Single-pin control mode* enables the switch to operate with a single control pin (pin 4) supporting a +3-volt CMOS logic input, and requires a dedicated +3-volt power supply connection on pin 6 ( $V_{DD}$ ). This mode of operation reduces the number of control lines required and simplifies the switch control interface typically derived from a CMOS  $\mu$ Processor I/O port.

*Complementary-pin control mode* allows the switch to operate using complementary control pins CTRL and  $\overline{CTRL}$  (pins 4 and 6), that can be directly driven by +3-volt CMOS logic or a suitable  $\mu$ Processor I/O port. This enables the PE42359 to be used as a potential alternate source for SPDT RF switch products used in positive control voltage mode and operating within the PE42359 operating limits.

Typical Performance Data @ +25°C,  $V_{DD} = 3.0V$  unless otherwise specified

Figure 5. Insertion Loss (RFX Nominal Condition)<sup>1</sup>




Figure 6. Insertion Loss vs Temp (RF1-RFC)<sup>1</sup>






Figure 7. Insertion Loss vs VDD (RF1-RFC)<sup>1</sup>




Note 1: High frequency performance can be improved by external matching (see Figure 20 through Figure 25 and Figure 28)

Typical Performance Data @ +25°C,  $V_{DD} = 3.0V$  unless otherwise specified


**Figure 8. RFC-RFX Isolation vs Temp**




**Figure 9. RFC-RFX Isolation vs VDD**



**Figure 10. RFX-RFX Isolation vs Temp**



**Figure 11. RFX-RFX Isolation vs VDD**



Typical Performance Data @ +25°C,  $V_{DD} = 3.0V$  unless otherwise specified

Figure 12. RFC Port Return Loss vs Temp (RF1 Active)<sup>1</sup>




Figure 13. RFC Port Return Loss vs VDD (RF1 Active)<sup>1</sup>




Figure 14. RFC Port Return Loss vs Temp (RF2 Active)<sup>1</sup>






Figure 15. RFC Port Return Loss vs VDD (RF2 Active)<sup>1</sup>




Note 1: High frequency performance can be improved by external matching (see Figure 20 through Figure 25 and Figure 28)

Typical Performance Data @ +25°C,  $V_{DD} = 3.0V$  unless otherwise specified


**Figure 16. Active Port Return Loss vs Temp (RF1 Active)<sup>1</sup>**




**Figure 17. Active Port Return Loss vs VDD (RF1 Active)<sup>1</sup>**



**Figure 18. Active Port Return Loss vs Temp (RF2 Active)<sup>1</sup>**



**Figure 19. Active Port Return Loss vs VDD (RF2 Active)<sup>1</sup>**




Note 1: High frequency performance can be improved by external matching (see Figure 20 through Figure 25 and Figure 28)




**Performance Comparison @ 25°C and  $V_{DD} = 3.0V$  with or without matching**


**Figure 20. Insertion Loss RF1<sup>1</sup>**




**Figure 21. Insertion Loss RF2<sup>1</sup>**




**Figure 22. Active Port Return Loss (RF1 Active)<sup>1</sup>**




**Figure 23. Active Port Return Loss (RF2 Active)<sup>1</sup>**



**Figure 24. RFC Port Return Loss (RF1 Active)<sup>1</sup>**



**Figure 25. RFC Port Return Loss (RF2 Active)<sup>1</sup>**



Note 1: High frequency performance can be improved by external matching (see Figure 20 through Figure 25 and Figure 28)


## Evaluation Kit

The SPDT switch EK Board was designed to ease customer evaluation of Peregrine's PE42359. The RF common port is connected through a 50 $\Omega$  transmission line via the top SMA connector, J1. RF1 and RF2 are connected through 50 $\Omega$  transmission lines via SMA connectors J2 and J3, respectively. A through 50 $\Omega$  transmission is available via SMA connectors J4 and J5. This transmission line can be used to estimate the loss of the PCB over the environmental conditions being evaluated.

The board is constructed of a two metal layer FR4 material with a total thickness of 0.031". The bottom layer provides ground for the RF transmission lines. The transmission lines were designed using a coplanar waveguide with ground plane model using a trace width of 0.0476", trace gaps of 0.030", dielectric thickness of 0.028", metal thickness of 0.0021" and  $\epsilon_r$  of 4.4.


J6 and J7 provide a means for controlling DC and digital inputs to the device. J6-1 is connected to the device  $V_{DD}$  or  $\overline{CTRL}$  input. J7-1 is connected to the device CTRL input.

**Figure 26. Evaluation Board Layouts**




DOC-02396

**Figure 27. Evaluation Board Schematic**



102-0889

**Figure 28. Evaluation Board Schematic with Matching**



102-0925

**Top View**

Dimensions: 2.10±0.05, 1.30, 1.25±0.10, 2.10±0.10, 0.65, 0.225±0.075, 0.10 (2X), 0.05 (2X).

Feature Callouts: A, B, C, SEATING PLANE, 0.10 C, 0.05 C.

**Side View**

Dimensions: 0.90±0.10, 0.05±0.05, 0.10 C.

**Recommended Land Pattern**

Dimensions: 0.65, 1.90, 0.50 MIN, 0.40 MIN, 1.30.

**End View**


Dimensions: 0.165±0.085, 0.36±0.10.

**Feature Callouts:**  $\Phi 0.10 \text{ (M)}$  A B, ALL FEATURES.

DOC-01923

● = Pin 1 Indicator  
 PPP = Part Number  
 YWW = Date Code

**Figure 31. Tape and Reel Specifications**



**Table 7. Ordering Information**

Order Code	Description	Package	Shipping Method
PE42359SCAA-Z	PE42359 SPDT RF switch	6-lead SC-70	3000 units / T&R
EK42359-01	PE42359 Evaluation kit	Evaluation kit	1 / Box

## Sales Contact and Information

For sales and contact information please visit [www.psemi.com](http://www.psemi.com).

**Advance Information:** The product is in a formative or design stage. The datasheet contains design target specifications for product development. Specifications and features may change in any manner without notice. **Preliminary Specification:** The datasheet contains preliminary data. Additional data may be added at a later date. Peregrine reserves the right to change specifications at any time without notice in order to supply the best possible product. **Product Specification:** The datasheet contains final data. In the event Peregrine decides to change the specifications, Peregrine will notify customers of the intended changes by issuing a CNF (Customer Notification Form).

The information in this datasheet is believed to be reliable. However, Peregrine assumes no liability for the use of this information. Use shall be entirely at the user's own risk.

No patent rights or licenses to any circuits described in this datasheet are implied or granted to any third party. Peregrine's products are not designed or intended for use in devices or systems intended for surgical implant, or in other applications intended to support or sustain life, or in any application in which the failure of the Peregrine product could create a situation in which personal injury or death might occur. Peregrine assumes no liability for damages, including consequential or incidental damages, arising out of the use of its products in such applications.

The Peregrine name, logo, UltraCMOS and UTSi are registered trademarks and HaRP, MultiSwitch and DuNE are trademarks of Peregrine Semiconductor Corp. Peregrine products are protected under one or more of the following U.S. Patents: <http://patents.psemi.com>.