


# 1/4" Square Single-Turn Cermet Sealed Trimmer



## FEATURES

- Industrial grade
- Fully sealed
- Miniature package
- Rotor designed for automatic machine adjust interface
- Withstands harsh environments and immersion cleaning process
- Tests according to CECC 41000 or IEC 60393-1
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)
















**RoHS**  
COMPLIANT

## LINKS TO ADDITIONAL RESOURCES



## DIMENSIONS in millimeters ( $\pm 0.25$ mm)

|                                                                                                                                              |                                                                                                         |                                                                                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <p><b>Common dimensions</b><br/>Top adjust<br/>T73Y</p>    | <p><b>T73YP</b></p>   | <p><b>T73YE</b></p>   |
| <p><b>Common dimensions</b><br/>Side adjust<br/>T73X</p>  | <p><b>T73YU</b></p>  | <p><b>T73YB</b></p>  |
| <p><b>Common dimensions</b><br/>Side adjust<br/>T73X</p>  | <p><b>T73XX</b></p>  | <p><b>T73XH</b></p>  |
|                                                                                                                                              | <p><b>T73XW</b></p>  | <p><b>T73XF</b></p>  |

| ELECTRICAL SPECIFICATIONS                    |                                                                                                                                 |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Resistive element                            | Cermet                                                                                                                          |
| Electrical travel                            | 240° nominal                                                                                                                    |
| Resistance range                             | 10 $\Omega$ to 2 M $\Omega$                                                                                                     |
| Standard series                              | 1 - 2 - 5                                                                                                                       |
| Tolerance standard                           | 10 %                                                                                                                            |
| Power rating                                 | <div>linear</div> <div>0.5 W at +70 °C</div>  |
| Circuit diagram                              |                                               |
| Temperature coefficient                      | $\pm 100$ ppm/°C                                                                                                                |
| Limiting element voltage                     | 300 V                                                                                                                           |
| Contact resistance variation                 | 1 % R <sub>n</sub> or 3 $\Omega$ max. whichever is greater                                                                      |
| Absolute minimum resistance                  | 1 % R <sub>n</sub> or 2 $\Omega$ max. whichever is greater                                                                      |
| Adjustability                                | $\pm 0.05$ % voltage<br>$\pm 0.15$ % resistance                                                                                 |
| Resolution                                   | infinite                                                                                                                        |
| Insulation resistance (500 V <sub>DC</sub> ) | 10 <sup>3</sup> M $\Omega$ minimum                                                                                              |
| Dielectric strength                          | 900 V <sub>AC</sub> sea level<br>350 V <sub>AC</sub> 80 000 feet                                                                |

| MECHANICAL SPECIFICATIONS   |                   |
|-----------------------------|-------------------|
| Mechanical travel           | 270°              |
| Operating torque (max. Ncm) | 2.1               |
| End stop torque (max. Ncm)  | 4.9               |
| Unit weight (max. g)        | 0.6               |
| Terminals                   | Pure Sn (code e3) |

| ENVIRONMENTAL SPECIFICATIONS |                     |
|------------------------------|---------------------|
| Temperature range            | -55 °C to +125 °C   |
| Climatic category            | 55/100/56           |
| Sealing                      | Fully sealed - IP67 |

**PERFORMANCES**

| TESTS           | CONDITIONS                   | TYPICAL VALUES AND DRIFTS |                                                 |
|-----------------|------------------------------|---------------------------|-------------------------------------------------|
| Load life       | 1000 h - 0.5 W at +70 °C     | $\Delta R_T/R_T$ (%)      | CRV < 3 $\Omega$ or 3 %<br>whichever is greater |
|                 |                              | 3 %                       |                                                 |
| Shock           | 100 g                        | $\pm 1$ %                 | $\Delta V/V \leq \pm 1$ %                       |
| Vibration       | 30 g                         | $\pm 1$ %                 | $\Delta V/V \leq \pm 1$ %                       |
| Humidity        | MIL-STD202 method 103 - 96 h | $\pm 2$ %                 | i.R. 10 M $\Omega$                              |
| Rotational life | 200 cycles                   | $\pm 4$ %                 | CRV < 3 $\Omega$ or 3 %<br>whichever is greater |

**Note**

- Nothing stated herein shall be construed as a guarantee of quality or durability

**STANDARD RESISTANCE ELEMENT DATA**

| STANDARD<br>RESISTANCE<br>VALUES | LINEAR LAW             |                         |                       | TYPICAL<br>TCR<br>-55 °C<br>+125 °C |
|----------------------------------|------------------------|-------------------------|-----------------------|-------------------------------------|
|                                  | MAX. POWER<br>AT 70 °C | MAX. WORKING<br>VOLTAGE | MAX. WIPER<br>CURRENT |                                     |
| $\Omega$                         | W                      | V                       | mA                    | ppm/°C                              |
| 10                               | 0.50                   | 2.2                     | 224                   | $\pm 100$                           |
| 20                               | 0.50                   | 3.2                     | 160                   |                                     |
| 50                               | 0.50                   | 5.0                     | 100                   |                                     |
| 100                              | 0.50                   | 7.1                     | 70                    |                                     |
| 200                              | 0.50                   | 10.0                    | 50                    |                                     |
| 500                              | 0.50                   | 15.8                    | 32                    |                                     |
| 1K                               | 0.50                   | 22.4                    | 22                    |                                     |
| 2K                               | 0.50                   | 31.6                    | 16                    |                                     |
| 5K                               | 0.50                   | 50                      | 10                    |                                     |
| 10K                              | 0.50                   | 70.7                    | 7.1                   |                                     |
| 20K                              | 0.50                   | 100                     | 5.0                   |                                     |
| 50K                              | 0.50                   | 158.1                   | 3.2                   |                                     |
| 100K                             | 0.50                   | 223.6                   | 2.2                   |                                     |
| 200K                             | 0.45                   | 300                     | 1.5                   |                                     |
| 500K                             | 0.18                   | 300                     | 0.60                  |                                     |
| 1M                               | 0.09                   | 300                     | 0.30                  |                                     |
| 2M                               | 0.05                   | 300                     | 0.15                  |                                     |

**MARKING**

- Vishay trademark
- Resistance code
- Terminal numbers
- Date code
- Model

**PACKAGING**

- In tube of 50 pieces code T20 (TU50)
- On request: tape and reel for style YU, code R32 (TR750) and style XW code R15 (TR1000)



### ORDERING INFORMATION (part number)

|       |   |                                                    |   |   |                                                              |   |   |                                |   |                                                                                                                    |   |  |                                                               |  |  |
|-------|---|----------------------------------------------------|---|---|--------------------------------------------------------------|---|---|--------------------------------|---|--------------------------------------------------------------------------------------------------------------------|---|--|---------------------------------------------------------------|--|--|
| T     | 7 | 3                                                  | Y | P | 5                                                            | 0 | 4 | K                              | T | 2                                                                                                                  | 0 |  |                                                               |  |  |
| MODEL |   | STYLE                                              |   |   | OHMIC VALUE                                                  |   |   | TOLERANCE                      |   | PACKAGING                                                                                                          |   |  | SPECIAL NUMBER                                                |  |  |
| T73   |   | XF<br>XH<br>XW<br>XX<br>YB<br>YE<br>YM<br>YP<br>YU |   |   | From<br>10 $\Omega$ to 2.2 M $\Omega$<br>103 = 10 k $\Omega$ |   |   | K = 10 %<br>on request J = 5 % |   | T20 = tube<br>50 pieces<br>On request:<br>R15 = reel 1000<br>pieces for style XW<br>R32 = reel 750 for<br>style YU |   |  | (If applicable)<br>Given by<br>Vishay<br>for custom<br>design |  |  |

### DESCRIPTION (for information only)

|       |       |       |           |           |             |
|-------|-------|-------|-----------|-----------|-------------|
| T73   | YP    | 500K  | 10 %      | TU        | e3          |
| MODEL | STYLE | VALUE | TOLERANCE | PACKAGING | LEAD FINISH |

### RELATED DOCUMENTS

#### APPLICATION NOTES

|                                                                   |                                                                        |
|-------------------------------------------------------------------|------------------------------------------------------------------------|
| Potentiometers and Trimmers                                       | <a href="http://www.vishay.com/doc?51001">www.vishay.com/doc?51001</a> |
| Guidelines for Vishay Sfernice Resistive and Inductive Components | <a href="http://www.vishay.com/doc?52029">www.vishay.com/doc?52029</a> |
| Selector guide                                                    | <a href="http://www.vishay.com/doc?49286">www.vishay.com/doc?49286</a> |

### ACCESSORIES

|                                    |                                                                        |
|------------------------------------|------------------------------------------------------------------------|
| Screwdrivers (to order separately) | <a href="http://www.vishay.com/doc?57015">www.vishay.com/doc?57015</a> |
|------------------------------------|------------------------------------------------------------------------|



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.