

.102

.119

75 OHM. AWG 28. 7 STRANDS OF AWG 36, TRIAXIAL CABLE Date:

Revision:

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

## **CONSTRUCTION DETAILS**

# **ELECTRICAL CHARACTERISTICS**

**CHARACTERISTICIMPEDANCE** 75 ± 3 ohms, Method B

CAPACITANCE 17.8 pF/ft. (nominal) at 1 kHz

19.0 pF/ft. (maximum) at 1 kHz

**VELOCITY OF PROPAGATION** 

76% (nominal)

# DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE CONDUCTOR .015 AWG 28, 7 Strands of AWG 36, Silver-Coated High Strength Copper DIELECTRIC .065 Rayfoam® L Color - Natural

### ADDITIONAL REQUIREMENTS

### **ELECTRICAL**

**CONDUCTOR RESISTANCE** 74.0 ohms/1000 ft. (nominal) INSULATION RESISTANCE 10,000 megohms (minimum)

for 1000 ft. (CONDUCTOR TO SHIELD) JACKET FLAWS

**SPARKTEST** 1.0 kV (rms) **IMPULSETEST** 6.0 kV, (peak)

**VOLTAGE WITHSTAND** (DIELECTRIC)

CONDUCTORTOSHIELD 1000 volts (rms) (minimum) **SHIELD TO SHIELD** 500 volts (rms) (minimum)

**ENVIRONMENTAL** 

**FLAMMABILITY** Method C **HEAT SHOCK** 225°C

LOWTEMPERATURE--55°C/3.75 inch mandrel

COLDBEND

VOLTAGE WITHSTAND

(POSTENVIRONMENTAL) 1000 volts (rms), 1 minute

### **PHYSICAL**

INSULATION (DIELECTRIC)

**ELONGATION** 50% (minimum) **TENSILE STRENGTH** 1000 lbf/in² (minimum)

JACKET (EACH)

200% (minimum) **ELONGATION** 2000 lbf/in² (minimum) **TENSILE STRENGTH** JACKET THICKNESS (EACH) .010 inch (nominal) SHIELD COVERAGE (EACH) 90% (minimum)

CABLE IDENTIFICATION Mark outer jacket in contrasting color

at 12 inch (nominal) intervals:

"7528A5314 - 06090"

# DESIGNATED.

.082 AWG 38, **Tin-Coated Copper** 

> **1**<sup>ST</sup> **JACKET** Thermorad<sup>®</sup> S Color - Black

1ST SHIELD

2ND SHIELD AWG 38,

**Tin-Coated Copper** 

2ND JACKET Thermorad<sup>®</sup> S

.139 (nominal) .146 (maximum)

Outer jacket color will be black (designated by a "-0" appended to the part number, e.g. 7528A5314-0) unless otherwise specified.

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

WEIGHT

15.3 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



