


REVISIONS

NOTES:
I. TECHNICAL CHARACTERISTICS:
HOUSING MATERIAL: DIE CAST ALUMINIUM ALLOY
SURFACE: POWDER COATED, GREY
OPERATION TEMPERATURE: -40-+125°C
DEGREE OF PROTECTION: IP65 (MATED)

注释：
1. 技术参数：
表面安装下壳材料：铝合金
表面处理：粉末涂层，灰色
工作温度：-40~+125℃
防护等级：IP65（配合）



T1620064316-000	H6B-SDRMS-PG16	PG16	-
T1620064320-000	H6B-SDRMS-M20	M20	-
T1620064325-000	H6B-SDRMS-M25	M25	-
T1620064416-000	H6B-SDRMS-2PG16	PG16	PG16
T1620064420-000	H6B-SDRMS-2M20	M20	M20
T1620064425-000	H6B-SDRMS-2M25	M25	M25
PART NUMBER	DESCRIPTION	IG1	IG2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 23JUN2015 David Wang CHK 23JUN2015 Chris Wang APVD 23JUN2015 Xiang Xu		 TE Connectivity	
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 1 PLC ±. 2 PLC ±. 3 PLC ±. 4 PLC ±. ANGLES ±.		NAME H6B-SDRMS-M/PG	
MATERIAL - -		PRODUCT SPEC 108-137013 APPLICATION SPEC 114-137013 WEIGHT -		SIZE A2	CAGE CODE 00779
FINISH - -		CUSTOMER DRAWING Customer Drawing		DRAWING NO C-T1620064XXX000	RESTRICTED TO -
		SCALE 1:1		SHEET 1 OF 1	REV A