

2SD2607

- 1) Darlington connection for high DC current gain.
- 2) Built-in resistor between base and emitter.
- 3) Built-in damper diode.
- 4) Complements the 2SB1668.

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CB0}	100	V
Collector-emitter voltage	V_{CE0}	100	V
Emitter-base voltage	V_{EB0}	7	V
Collector current	I_C	8	A (DC)
		10	A (Pulse) *
Power dissipation	P_C	2	W
		30	W ($T_C = 25^\circ\text{C}$)
Junction temperature	T_J	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55--+150	$^\circ\text{C}$

Type	2SD2607
Package	TO-220FN
hfe	1k~20k
Code	-
Basic ordering unit (pieces)	500

$R1 \approx 5k\Omega$ B : Base
 $R2 \approx 300k\Omega$ C : Collector
 E : Emitter

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	100	-	-	V	$I_C = 50 \mu A$
Collector-emitter breakdown voltage	BV_{CEO}	100	-	-	V	$I_C = 5 mA$
Collector cutoff current	I_{CO}	-	-	10	μA	$V_{CE} = 100V$
Emitter cutoff current	I_{EO}	-	-	3	mA	$V_{ES} = 5V$
Collector-emitter saturation voltage	$V_{CE(SAT)}$	-	-	1.5	V	$I_C/I_E = 3A/8mA$
DC current transfer ratio	h_{FE}	1000	-	20000	-	$V_{CE}/I_C = 3V/2A$
Transition frequency	f_T	-	40	-	MHz	$V_{CE} = 5V, I_E = -0.2A, f = 10MHz$
Output capacitance	C_{ob}	-	50	-	pF	$V_{CE} = 10V, I_E = 0A, f = 1MHz$

The drawing shows the mechanical specifications of the TO-220FN package. The top view includes dimensions for the base (16.0 mm), collector/drain (10.0 mm), emitter/source (1.3 mm), and various mounting and lead dimensions (15.0 mm, 14.0 mm, 8.0 mm, 3.5 mm, 2.54 mm, 1.27 mm, 0.8 mm, 1.27 mm, 2.54 mm). The side view shows the package height (4.5 mm) and lead dimensions (2.8 mm, 0.75 mm, 2.6 mm).

ROHM : TO-220FN