News

NEW MK193 LED CUBE

CubeAnimator software available for download here!!!

Posted on 04-06-12

Read more...

New Ring scanners

Velleman invests again in its logistics system.

Posted on 14-05-12

Read more...

Glass Touch Panels

Glass Touch Panels with or without OLED. Coming soon.

Posted on 04-04-12

Read more...

New cable range

Discover our new audio, video & computer cables range!

Posted on 12-03-12

Read more...

PROLYTE Product news

Due to its recent increased raw material costs, ProLyte...

Posted on 19-07-11

Read more...

Advertisements

K8090 / VM8090
iPad/iPod/iPhone app

K8055(N) / VM110(N)
Android Application

K8055(N) / VM110(N)
iPhone application

Subscribe to our
NEWSLETTER

velleman

PRODUCT OVERVIEW ADAPTERS & POWER SUPPLIES DC CONNECTORS AND PLUGS

DC PLUG 5.5x2.1MM FEMALE TO SCREW TERMINAL (5pcs)

CD021
Support

Infosheet
Support

Features

- female to fixed screw terminal

Specifications

- max. voltage: 25V
- max. current: 4A
- max. operating temperature: 30°C

All registered trademarks and trade names are properties of their respective owners and are used only for the clarification of the compatibility of our products with the products of the different manufacturers.
Due to constant product improvements the actual product appearance might differ from the shown images. Product images are for illustrative purposes only.

REACH communicating information according to article 33
WEEE

© 2012
All rights reserved