



## SY89296U

2.5V/3.3V 1.5GHz Precision  
LVPECL Programmable Delay  
with Fine Tune Control

Precision Edge®

### General Description

The SY89296U is a programmable delay line that delays the input signal using a digital control signal. The delay can vary from 3.2ns to 14.8ns in 10ps increments. Further, the delay may be varied continuously in about 40ps range by setting the voltage at the FTUNE pin. In addition, the input signal is LVPECL, uses either a 2.5V  $\pm 5\%$  or 3.3V  $\pm 10\%$  power supply, and is guaranteed over the full industrial temperature range ( $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ ).

The delay varies in discrete steps based on a control word. The control word is 10-bits long and controls the delay in 10ps increments. The eleventh bit is D[10] and is used to simultaneously cascade the SY89296U for a larger delay range. In addition, the input pins IN and /IN default to an equivalent low state when left floating. Further, for maximum flexibility, the control register interface accepts CMOS or TTL level signals.

For applications that do not require an analog delay input, see the SY89295U. The SY89295U and SY89296U are part of Micrel's high-speed, Precision Edge® product line.

Data sheets and support documentation can be found on Micrel's web site at: [www.micrel.com](http://www.micrel.com).



Precision Edge®

### Features

- Precision LVPECL programmable delay time
- Guaranteed AC performance over temperature and voltage:
  - $>1.5\text{GHz } f_{\text{MAX}}$
  - $<160\text{ps}$  rise/fall times
- Low jitter design:
  - $<10\text{ps}_{\text{PP}}$  total jitter
  - $<2\text{ps}_{\text{RMS}}$  cycle-to-cycle jitter
  - $<1\text{ps}_{\text{RMS}}$  random jitter
- Programmable delay range: 3.2ns to 14.8ns in 10ps increments
- Increased monotonicity over the MC100EP195
- $\pm 10\text{ps}$  INL
- VBB output reference voltage
- Parallel inputs accept LVPECL or CMOS/LVTTL
- 40ps/V fine tune range
- Low voltage operation: 2.5V  $\pm 5\%$  and 3.3V  $\pm 10\%$
- Industrial  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$  temperature range
- Available in 32-pin (5mm  $\times$  5mm) MLF® package or 32-pin TQFP package

### Applications

- Clock de-skewing
- Timing adjustments
- Aperture centering

Precision Edge is a registered trademark of Micrel, Inc.  
MLF and MicroLeadFrame are registered trademarks of Amkor Technology, Inc.

Micrel Inc. • 2180 Fortune Drive • San Jose, CA 95131 • USA • tel +1 (408) 944-0800 • fax + 1 (408) 474-1000 • <http://www.micrel.com>

November 2011

M9999-112211  
[hbwhelp@micrel.com](mailto:hbwhelp@micrel.com) or (408) 955-1690


## Ordering Information<sup>(1)</sup>

Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY89296UMI	MLF-32	−40°C to +85°C	SY89296U	Sn-Pb
SY89296UMITR <sup>(2)</sup>	MLF-32	−40°C to +85°C	SY89296U	Sn-Pb
SY89296UTI	T32-1	−40°C to +85°C	SY89296U	Sn-Pb
SY89296UTITR <sup>(2)</sup>	T32-1	−40°C to +85°C	SY89296U	Sn-Pb
SY89296UMG <sup>(3)</sup>	MLF-32	−40°C to +85°C	SY89296U with Pb-Free bar-line indicator	Pb-Free NiPdAu
SY89296UMGTR <sup>(2, 3)</sup>	MLF-32	−40°C to +85°C	SY89296U with Pb-Free bar-line indicator	Pb-Free NiPdAu
SY89296UTG <sup>(3)</sup>	T32-1	−40°C to +85°C	SY89296U with Pb-Free bar-line indicator	Pb-Free NiPdAu
SY89296UTGTR <sup>(2, 3)</sup>	T32-1	−40°C to +85°C	SY89296U with Pb-Free bar-line indicator	Pb-Free NiPdAu


### Notes:

1. Contact factory for die availability. Dice are guaranteed at T<sub>A</sub> = 25°C, DC electricals only.
2. Tape and Reel.
3. Pb-Free package recommended for new designs.

## Pin Configuration



**32-Pin MLF<sup>®</sup> (MLF-32)**



**32-Pin TQFP (T32-1)**

## Pin Description

Pin Number	Pin Name	Pin Function	
23, 25, 26, 27, 29, 30, 31, 32, 1, 2	D[9:0]	CMOS, ECL, or TTL Control Bits: These control signals adjust the delay from IN to Q. See “AC Electrical Characteristics” for delay values. In addition, see “Interface Applications” section which illustrates the proper interfacing techniques for different logic standards. D[9:0] contains pull-downs and defaults LOW when left floating. D0 (LSB), and D9 (MSB). See “Typical Operating Characteristics” for delay information.	
3	D10	CMOS, ECL, or TTL Control Bit: This bit is used to cascade devices for an extended delay range. In addition, it drives CASCADE and /CASCADE. Further, D[10] contains a pull-down and defaults LOW when left floating.	
4, 5	IN, /IN	LVPECL/ECL Signal Input: Input signal to be delayed. IN contains a 75kΩ pull-down and will default to a logic LOW if left floating.	
6	VBB <sup>(1)</sup>	Reference Voltage Output: When using a single-ended input signal source to IN or /IN, connect the unused input of the differential pair to this pin. This pin can also be used to rebias AC-coupled inputs to IN and /IN. When used, de-couple to Vcc using a 0.01μF capacitor, otherwise leave floating if not used. Maximum sink/source is ±0.5mA.	
7	VEF	Reference Voltage Output: Connect this pin to Vcf when D[9:0], and D[10] is ECL.	
		Logic Standard	Vcf Connects to:
		LVPECL	VEF(1)
		CMOS	No Connect
		TTL	1.5V Source
8	VCF	Reference Voltage Input: The voltage driven on VCF sets the logic transition threshold for D[9:0], and D[10].	
9, 24, 28	GND, Exposed Pad <sup>(2)</sup>	Negative Supply: For MLF® package, exposed pad must be connected to a ground plane that is the same potential as the ground pin.	
10	LEN	ECL Control Input: When HIGH latches the D[9:0] and D[10] bits. When LOW, the D[9:0] and D[10] latches are transparent.	
11	SETMIN	ECL Control Input: When HIGH, D[9:0] registers are reset. When LOW, the delay is set by SETMAX or D[9:0] and D[10]. SETMIN contains a pull-down and defaults LOW when left floating.	
12	SETMAX	ECL Control Input: When SETMAX is set HIGH and SETMIN is set LOW, D[9:0] = 1111111111. When SETMAX is LOW, the delay is set by SETMIN or D[9:0] and D[10]. SETMAX contains a pull-down and defaults LOW when left floating.	
13, 18, 19, 22	VCC	Positive Power Supply: Bypass with 0.1μF and 0.01μF low ESR capacitors.	
14, 15	/Cascade, Cascade	LVPECL Differential Output: The outputs are used when cascading two or more SY89296U to extend the delay range.	
16	/EN	LVPECL Single-Ended Control Input: When LOW, Q is delayed from IN. When HIGH, Q is a differential LOW. /EN contains a pull-down and defaults LOW when left floating.	
20, 21	/Q, Q	LVPECL Differential Output: Q is a delayed version of IN, Always terminates the output with 50Ω to VCC – 2V. See “Output Interface Applications” section.	
17	FTUNE	Voltage Control Input: By varying the voltage, the delay is fine tuned, see the graph, “Propagation Delay vs. FTUNE Voltage.” Leave pin floating if not used.	

### Notes:

1. Single-ended operation is only functional at 3.3V.
2. MLF<sup>®</sup> package only.

## Truth Tables

### Input/Output

Inputs		Outputs	
IN	/IN	OUT	/OUT
0	1	0	1
1	0	1	0


### Digital Control Latch

LEN	Latch Action
0	Pass Through D[10:0]
1	Latched D[10:0]

### Input Enable

/EN	Q, /Q
0	IN, /IN Delayed
1	Latched D[10:0]

## Functional Block Diagram



**SY89296U Block Diagram**

**Absolute Maximum Ratings<sup>(1)</sup>**

Supply Voltage ( $V_{CC}$ )	–0.5V to +4.0V
Input Voltage ( $V_{IN}$ )	–0.5V to $V_{CC}$
LVPECL Output Current ( $I_{OUT}$ )	
Continuous	50mA
Surge	100mA
Lead Temperature (soldering, 20sec.)	+260°C
Storage Temperature ( $T_s$ )	–65°C to +150°C

**Operating Ratings<sup>(2)</sup>**

Supply Voltage ( $V_{IN}$ )	+2.375V to +3.6V
Ambient Temperature ( $T_A$ )	–40°C to +85°C
Package Thermal Resistance	
MLF <sup>®</sup> ( $\theta_{JA}$ )	
Still-Air	35°C/W
MLF <sup>®</sup> ( $\Psi_{JB}$ )	
Junction-to-Board	28°C/W
TQFP ( $\theta_{JA}$ )	
Still-Air	28°C/W
TQFP ( $\Psi_{JB}$ )	
Junction-to-Board	20°C/W

**DC Electrical Characteristics<sup>(4)</sup>**

$T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ , unless otherwise stated.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
VCC	Power Supply	VCC = 2.5V	2.375	2.5	2.625	V
		VCC = 3.3V	3	3.3	3.6	
IEE	Power Supply Current	No load, max. VCC			220	mA
VIN	Input Voltage Swing (IN, /IN)	See Figure 1a.	150		1200	mV
VDIFF_IN	Differential Input Voltage Swing (IN, /IN)	See Figure 1b.	300		2400	mV
VIHCMR	Input High Common Mode Range	IN, /IN	VEE + 1.2		VCC	V

$V_{CC} = 3.3\text{V}$ ,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ , unless otherwise stated.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
V <sub>IH</sub>	Input High Voltage (IN, /IN)		2.075		2.420	V
V <sub>IL</sub>	Input Low High Voltage (IN, /IN)		1.355		1.675	V
V <sub>BB</sub>	Output Voltage Reference		1.775	1.875	1.975	V
V <sub>EF</sub>	Mode Connection		1.9	2.0	2.1	V
V <sub>CF</sub>	Input Select Voltage		1.55	1.65	1.75	V

**Notes:**

1. Permanent device damage may occur if "Absolute Maximum Ratings" are exceeded. This is a stress rating only and functional operation is not implied at conditions other than those detailed in the operational sections of this data sheet. Exposure to "Absolute Maximum Rating" conditions for extended periods may affect device reliability.
2. The data sheet limits are not guaranteed if the device is operated beyond the operating ratings.
3. Thermal performance on MLF<sup>®</sup> packages assumes exposed pad is soldered (or equivalent) to the device most negative potential (GND).
4. The circuit is designed to meet the DC specifications shown in the table above after thermal equilibrium has been established. Input and output parameters vary 1:1 with  $V_{CC}$ , with the exception of  $V_{CF}$ .

## DC Electrical Characteristics<sup>(4)</sup> (Continued)

$V_{CC} = 2.5V$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ , unless otherwise stated.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
$V_{IH}$	Input High Voltage (IN, /IN)		1.275		1.62	V
$V_{IL}$	Input Low High Voltage (IN, /IN)		0.555		0.875	V
$V_{BB}$	Output Voltage Reference		0.925	1.075	1.175	V
$V_{EF}$	Mode Connection		1.10	1.20	1.30	V
$V_{CF}$	Input Select Voltage		1.15	1.25	1.35	V

## LVPECL Outputs DC Electrical Characteristics<sup>(5)</sup>

$V_{CC} = 3.3V$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ ;  $R_{LOAD} = 500\Omega$  to  $V_{CC} - 2V$ , unless noted.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
$V_{OH}$	Output HIGH Voltage (Q, /Q)		2.155	2.280	2.405	V
$V_{OL}$	Output LOW Voltage (Q, /Q)		1.355	1.480	1.605	V
$V_{OUT}$	Output Voltage Swing (Q, /Q)	See Figure 1a.	550	800		mV
$V_{DIFF\_OUT}$	Differential Output Voltage Swing (Q, /Q)	See Figure 1b.	1.1	1.6		V

$V_{CC} = 2.5V$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ ;  $R_{LOAD} = 50\Omega$  to  $V_{CC} - 2V$ , unless noted.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
$V_{OH}$	Output HIGH Voltage (Q, /Q)		1.355	1.48	1.605	V
$V_{OL}$	Output LOW Voltage (Q, /Q)		0.555	0.680	0.805	V
$V_{OUT}$	Output Voltage Swing (Q, /Q)	See Figure 1a.	550	800		mV
$V_{DIFF\_OUT}$	Differential Output Voltage Swing (Q, /Q)	See Figure 1b.	1.1	1.6		V

## LVTTL/CMOS Outputs DC Electrical Characteristics<sup>(6)</sup>

$V_{CC} = 2.5V \pm 5\%$  or  $3.3V \pm 10\%$ ;  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ ; unless noted.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
VCC	Power Supply	$V_{CC} = 2.5V$	2.375	2.5	2.625	V
		$V_{CC} = 3.3V$	3	3.3	3.6	
IEE	Power Supply Current	No load, max. VCC			220	mA
VIN	Input Voltage Swing (IN, /IN)	See Figure 1a.	150		1200	mV
VDIFF_IN	Differential Input Voltage Swing (IN, /IN)	See Figure 1b.	300		2400	mV

### Notes:

- The circuit is designed to meet the DC specifications shown in the table above after thermal equilibrium has been established.  $V_{OH}$  and  $V_{OL}$  parameters vary 1:1 with  $V_{CC}$ .
- The circuit is designed to meet the DC specifications shown in the table above after thermal equilibrium has been established

## AC Electrical Characteristics<sup>(7)</sup>

T<sub>A</sub> = –40°C to +85°C, unless otherwise stated.

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
f <sub>MAX</sub>	Maximum Operating Frequency	Clock	1.5			GHz
t <sub>PD</sub>	Propagation Delay IN to Q; D[0–10]=0		3200		4200	ps
	IN to Q; D[0–10]=1023		11500		14800	
	/EN to Q; D[0–10]=0		3400		4400	
	D10 to CASCADE		350		670	
t <sub>RANGE</sub>	Programmable Range t <sub>pd</sub> (max.) – t <sub>pd</sub> (min.)		8300			ps
t <sub>SKEW</sub>	Duty Cycle Skew t <sub>PHL</sub> – t <sub>PLH</sub>	<b>Note 8</b>			25	ps
Δt	Step Delay			10		ps
	D0 High			15		
	D1 High			35		
	D2 High			70		
	D3 High			145		
	D4 High			290		
	D5 High			575		
	D6 High			1150		
	D7 High			2300		
	D8 High			4610		
	D9 High			9220		
	D0 – D9 High					
INL	Integral Non-Linearity	<b>Note 9</b>		±10		ps

### Notes:

7. High-frequency AC electricals are guaranteed by design and characterization.
8. Duty cycle skew guaranteed only for differential operation measured from the crosspoint of the input to the crosspoint of the output.
9. INL (Integral Non-Linearity) is defined from its corresponding point on the ideal delay vs. D[9:0] curve as the deviation from its ideal delay. The maximum difference is the INL. Theoretical Ideal Linearity (TIL) = measured maximum delay – measured minimum delay ÷ 1024. INL = measured delay – measured minimum delay + (step number × TIL).



## AC Electrical Characteristics<sup>(7)</sup> (Continued)

T<sub>A</sub> = -40°C to +85°C, unless otherwise stated.




Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
t <sub>S</sub>	Set-Up Time D t+o LEN D to IN /EN to IN	<b>Note 10</b>	200			ps
		<b>Note 11</b>	350			
			300			
t <sub>H</sub>	Hold Time LEN to D IN to /EN		200			ps
		<b>Note 12</b>	400			
t <sub>R</sub>	Release Time /EN to IN SETMAX to LEN SETMIN to LEN		500			ps
			500			
			450			
t <sub>JITTER</sub>	Cycle-to-Cycle Jitter	<b>Note 13</b>			2	pS <sub>RMS</sub>
	Total Jitter	<b>Note 14</b>			10	pS <sub>PP</sub>
	Random Jitter	<b>Note 15</b>			1	pS <sub>RMS</sub>
t <sub>r</sub> , t <sub>f</sub>	Output Rise/Fall Time	20% to 80% (Q)	50	85	160	ps
		20% to 80% (CASCADE)	90		300	ps
	Duty Cycle		45		55	%
f <sub>T</sub>	F <sub>TUNE</sub>	0 ≤ F <sub>TUNE</sub> ≤ 1.25V		47	52	Ps/V

### Notes:


10. This setup time defines the amount of time prior to the input signal. The delay tap of the device must be set.
11. This setup time defines the amount of the time that /EN must be asserted prior to the next transition of IN, /IN to prevent an output response greater than ±75mV to the IN, /IN transition.
12. Hold time is the minimum time that /EN must remain asserted after a negative going IN or a positive going /IN to prevent an output response greater than ±75mV to that IN, /IN transition.
13. Cycle-to-cycle jitter definition: the variation of periods between adjacent cycles over a random sample of adjacent cycle pairs  
 $T_{\text{jitter\_cc}} = T_n - T_{n-1} + 1$ , where T is the time between rising edges of the output signal.
14. Total jitter definition: with an ideal clock input, no more than one output edge in 10<sup>12</sup> output edges will deviate by more than the specified peak-to-peak jitter value.
15. Random jitter definition: jitter that is characterized by a Gaussian distribution, unbounded and is quantified by its standard deviation and mean. Random jitter is measured with a K28.7 comma defect pattern, measured at 1.5Gbps.

## Typical Operating Characteristics

$V_{CC} = 3.3V$ ,  $GND = 0$ ,  $D_{IN} = 100mV$ ,  $T_A = 25^\circ C$ , unless otherwise noted.



## Timing Diagram



## Single-Ended and Differential Swings



Figure 1a. Single-Ended Voltage Swing




Figure 1b. Differential Voltage Swing

## Input and Output Stages




Figure 2a. Differential Input Stage




Figure 2b. Single-Ended Input Stage




Figure 3. LVPECL Output Stage

## Output Interface Applications




Figure 4. Parallel Termination




Figure 5. Y-Termination




Figure 6. Terminating Unused I/O

## Application Information

For best performance, use good high frequency layout techniques, filter  $V_{CC}$  supplies, and keep ground connections short. Use multiple vias where possible. Also, use controlled impedance transmission lines to interface with the SY89296U data inputs and outputs.

### $V_{BB}$ Reference

The  $V_{BB}$  pin is an internally generated reference and is available for use only by the SY89296U. When unused, this pin should be left unconnected. The two common uses for  $V_{BB}$  are to handle a single-ended PECL input, and to re-bias inputs for AC-coupling applications.

If either IN or /IN is driven by a single-ended output,  $V_{BB}$  is used to bias the unused input. Please refer to Figure 10. The PECL signal driving the SY89296U may optionally be inverted in this case.

When the signal is AC-coupled,  $V_{BB}$  is used, as shown in Figure 13, to re-bias IN and/or /IN. This ensures that SY89296U inputs are within acceptable common mode range.

In all cases,  $V_{BB}$  current sinking or sourcing must be limited to 0.5mA or less.

### Setting D Input Logic Thresholds

In all designs where the SY89296U GND supply is at zero volts, the D inputs can accommodate CMOS and TTL level signals, as well as PECL or LVPECL. Figures 11, 12, and 14 show how to connect VCF and VEF for all possible cases.

### Cascading

Two or more SY89296U may be cascaded in order to extend the range of delays permitted. Each additional SY89296U adds about 3.2ns to the minimum delay and adds another 10240ps to the delay range.

Internal cascade circuitry has been included in the SY89296U. Using this internal circuitry, the SY89296U may be cascaded without any external gating.

Examples of cascading 2, 3, or 4 SY89296U appear in Figures 7, 8, and 9.




Figure 7. Cascading Two SY89296U




Figure 8. Cascading Three SY89296U






Figure 9. Cascading Four SY89296U


## Interface Applications




**Figure 10. Interfacing to a Single-Ended LVPECL Signal**  
To invert the signal, connect the LVPECL input to /IN and connect  $V_{CC}$  to IN




**Figure 11.  $V_{CF}$  /  $V_{EF}$  Biasing for LVPECL Control (D) Input**



**Figure 12.  $V_{CF}$  /  $V_{EF}$  Biasing for CMOS Control (D) Input**



**Figure 13. Re-Biasing an AC-Coupled Signal**




**Figure 14.  $V_{CF}$  /  $V_{EF}$  Biasing for LVTTTL Control (D) Input**


## Related Product and Support Documentation

Part Number	Function	Data Sheet Link
SY89295U	2.5/3.3V 1.5GHz Precision LVPECL Programmable Delay	<a href="http://www.micrel.com/product-info/products/sy89295u.shtml">www.micrel.com/product-info/products/sy89295u.shtml</a>
SY89296U	2.5/3.3V 1.5GHz Precision LVPECL Programmable Delay with Fine Tune Control	<a href="http://www.micrel.com/product-info/products/sy89296u.shtml">www.micrel.com/product-info/products/sy89296u.shtml</a>
	16-MLF <sup>®</sup> Manufacturing Guidelines Exposed Pad Application Note	<a href="http://www.amkor.com/products/notes_papers/MLF_appnote_0902.pdf">www.amkor.com/products/notes_papers/MLF_appnote_0902.pdf</a>
	HBW Solutions	<a href="http://www.micrel.com/product-info/as/solutions.shtml">www.micrel.com/product-info/as/solutions.shtml</a>


## Package Information



TOP VIEW




BOTTOM VIEW



SIDE VIEW

- NOTE:
1. ALL DIMENSIONS ARE IN MILLIMETERS.
  2. MAX. PACKAGE WARPAGE IS 0.05 mm.
  3. MAXIMUM ALLOWABLE BURRS IS 0.076 mm IN ALL DIRECTIONS.
  4. PIN #1 ID ON TOP WILL BE LASER/INK MARKED.



PCB Thermal Consideration for 32-Pin MLF <sup>\*</sup> Package  
(Always solder, or equivalent, the exposed pad to the PCB)

Package Notes:

1. Package meets Level 2 qualification.
2. All parts are dry-packaged before shipment.
3. Exposed pads must be soldered to a ground for proper thermal management.

### 32-Pin MLF<sup>®</sup> (MLF-32)



**TOP VIEW**

Dimensions (mm [inches]):

- 9.00 [0.354] BSC (Pin 1 to Pin 25)
- 9.00 [0.354] BSC (Pin 25 to Pin 17)
- 0.37  $\begin{smallmatrix} +0.08 \\ -0.07 \end{smallmatrix}$  [0.015  $\begin{smallmatrix} +0.003 \\ -0.003 \end{smallmatrix}$ ] (Pin 1 to datum)
- 0.80 [0.031] BSC (Pin 8 to datum)
- 0.10  $\begin{smallmatrix} +0.05 \\ -0.05 \end{smallmatrix}$  [0.004  $\begin{smallmatrix} +0.003 \\ -0.003 \end{smallmatrix}$ ] (Datum to Pin 1)
- 1.00 [0.039] REF. (Datum to Pin 17)
- 0.21 [0.008] / 0.12 [0.005] (Pin 17 to Pin 16)
- 0.60  $\begin{smallmatrix} +0.15 \\ -0.15 \end{smallmatrix}$  [0.024  $\begin{smallmatrix} +0.006 \\ -0.006 \end{smallmatrix}$ ] (Pin 16 to Pin 15)
- 0° MIN. (Lead angle)
- 8 PLACES (Lead placement)

**BOTTOM VIEW**

Dimensions (mm [inches]):

- 7.00 [0.276] BSC (Pin 3 to Pin 7)
- 7.00 [0.276] BSC (Pin 7 to Pin 11)
- 7.00 [0.276] BSC (Pin 11 to Pin 15)
- 7.00 [0.276] BSC (Pin 15 to Pin 19)
- 7.00 [0.276] BSC (Pin 19 to Pin 23)
- 7.00 [0.276] BSC (Pin 23 to Pin 27)
- 7.00 [0.276] BSC (Pin 27 to Pin 31)
- 7.00 [0.276] BSC (Pin 31 to Pin 35)
- 7.00 [0.276] BSC (Pin 35 to Pin 39)
- 7.00 [0.276] BSC (Pin 39 to Pin 43)
- 7.00 [0.276] BSC (Pin 43 to Pin 47)
- 7.00 [0.276] BSC (Pin 47 to Pin 51)
- 7.00 [0.276] BSC (Pin 51 to Pin 55)
- 7.00 [0.276] BSC (Pin 55 to Pin 59)
- 7.00 [0.276] BSC (Pin 59 to Pin 63)
- 7.00 [0.276] BSC (Pin 63 to Pin 67)
- 7.00 [0.276] BSC (Pin 67 to Pin 71)
- 7.00 [0.276] BSC (Pin 71 to Pin 75)
- 7.00 [0.276] BSC (Pin 75 to Pin 79)
- 7.00 [0.276] BSC (Pin 79 to Pin 83)
- 7.00 [0.276] BSC (Pin 83 to Pin 87)
- 7.00 [0.276] BSC (Pin 87 to Pin 91)
- 7.00 [0.276] BSC (Pin 91 to Pin 95)
- 7.00 [0.276] BSC (Pin 95 to Pin 99)
- 7.00 [0.276] BSC (Pin 99 to Pin 103)
- 7.00 [0.276] BSC (Pin 103 to Pin 107)
- 7.00 [0.276] BSC (Pin 107 to Pin 111)
- 7.00 [0.276] BSC (Pin 111 to Pin 115)
- 7.00 [0.276] BSC (Pin 115 to Pin 119)
- 7.00 [0.276] BSC (Pin 119 to Pin 123)
- 7.00 [0.276] BSC (Pin 123 to Pin 127)
- 7.00 [0.276] BSC (Pin 127 to Pin 131)
- 7.00 [0.276] BSC (Pin 131 to Pin 135)
- 7.00 [0.276] BSC (Pin 135 to Pin 139)
- 7.00 [0.276] BSC (Pin 139 to Pin 143)
- 7.00 [0.276] BSC (Pin 143 to Pin 147)
- 7.00 [0.276] BSC (Pin 147 to Pin 151)
- 7.00 [0.276] BSC (Pin 151 to Pin 155)
- 7.00 [0.276] BSC (Pin 155 to Pin 159)
- 7.00 [0.276] BSC (Pin 159 to Pin 163)
- 7.00 [0.276] BSC (Pin 163 to Pin 167)
- 7.00 [0.276] BSC (Pin 167 to Pin 171)
- 7.00 [0.276] BSC (Pin 171 to Pin 175)
- 7.00 [0.276] BSC (Pin 175 to Pin 179)
- 7.00 [0.276] BSC (Pin 179 to Pin 183)
- 7.00 [0.276] BSC (Pin 183 to Pin 187)
- 7.00 [0.276] BSC (Pin 187 to Pin 191)
- 7.00 [0.276] BSC (Pin 191 to Pin 195)
- 7.00 [0.276] BSC (Pin 195 to Pin 199)
- 7.00 [0.276] BSC (Pin 199 to Pin 203)
- 7.00 [0.276] BSC (Pin 203 to Pin 207)
- 7.00 [0.276] BSC (Pin 207 to Pin 211)
- 7.00 [0.276] BSC (Pin 211 to Pin 215)
- 7.00 [0.276] BSC (Pin 215 to Pin 219)
- 7.00 [0.276] BSC (Pin 219 to Pin 223)
- 7.00 [0.276] BSC (Pin 223 to Pin 227)
- 7.00 [0.276] BSC (Pin 227 to Pin 231)
- 7.00 [0.276] BSC (Pin 231 to Pin 235)
- 7.00 [0.276] BSC (Pin 235 to Pin 239)
- 7.00 [0.276] BSC (Pin 239 to Pin 243)
- 7.00 [0.276] BSC (Pin 243 to Pin 247)
- 7.00 [0.276] BSC (Pin 247 to Pin 251)
- 7.00 [0.276] BSC (Pin 251 to Pin 255)
- 7.00 [0.276] BSC (Pin 255 to Pin 259)
- 7.00 [0.276] BSC (Pin 259 to Pin 263)
- 7.00 [0.276] BSC (Pin 263 to Pin 267)
- 7.00 [0.276] BSC (Pin 267 to Pin 271)
- 7.00 [0.276] BSC (Pin 271 to Pin 275)
- 7.00 [0.276] BSC (Pin 275 to Pin 279)
- 7.00 [0.276] BSC (Pin 279 to Pin 283)
- 7.00 [0.276] BSC (Pin 283 to Pin 287)
- 7.00 [0.276] BSC (Pin 287 to Pin 291)
- 7.00 [0.276] BSC (Pin 291 to Pin 295)
- 7.00 [0.276] BSC (Pin 295 to Pin 299)
- 7.00 [0.276] BSC (Pin 299 to Pin 303)
- 7.00 [0.276] BSC (Pin 303 to Pin 307)
- 7.00 [0.276] BSC (Pin 307 to Pin 311)
- 7.00 [0.276] BSC (Pin 311 to Pin 315)
- 7.00 [0.276] BSC (Pin 315 to Pin 319)
- 7.00 [0.276] BSC (Pin 319 to Pin 323)
- 7.00 [0.276] BSC (Pin 323 to Pin 327)
- 7.00 [0.276] BSC (Pin 327 to Pin 331)
- 7.00 [0.276] BSC (Pin 331 to Pin 335)
- 7.00 [0.276] BSC (Pin 335 to Pin 339)
- 7.00 [0.276] BSC (Pin 339 to Pin 343)
- 7.00 [0.276] BSC (Pin 343 to Pin 347)
- 7.00 [0.276] BSC (Pin 347 to Pin 351)
- 7.00 [0.276] BSC (Pin 351 to Pin 355)
- 7.00 [0.276] BSC (Pin 355 to Pin 359)
- 7.00 [0.276] BSC (Pin 359 to Pin 363)
- 7.00 [0.276] BSC (Pin 363 to Pin 367)
- 7.00 [0.276] BSC (Pin 367 to Pin 371)
- 7.00 [0.276] BSC (Pin 371 to Pin 375)
- 7.00 [0.276] BSC (Pin 375 to Pin 379)
- 7.00 [0.276] BSC (Pin 379 to Pin 383)
- 7.00 [0.276] BSC (Pin 383 to Pin 387)
- 7.00 [0.276] BSC (Pin 387 to Pin 391)
- 7.00 [0.276] BSC (Pin 391 to Pin 395)
- 7.00 [0.276] BSC (Pin 395 to Pin 399)
- 7.00 [0.276] BSC (Pin 399 to Pin 403)
- 7.00 [0.276] BSC (Pin 403 to Pin 407)
- 7.00 [0.276] BSC (Pin 407 to Pin 411)
- 7.00 [0.276] BSC (Pin 411 to Pin 415)
- 7.00 [0.276] BSC (Pin 415 to Pin 419)
- 7.00 [0.276] BSC (Pin 419 to Pin 423)
- 7.00 [0.276] BSC (Pin 423 to Pin 427)
- 7.00 [0.276] BSC (Pin 427 to Pin 431)
- 7.00 [0.276] BSC (Pin 431 to Pin 435)
- 7.00 [0.276] BSC (Pin 435 to Pin 439)
- 7.00 [0.276] BSC (Pin 439 to Pin 443)
- 7.00 [0.276] BSC (Pin 443 to Pin 447)
- 7.00 [0.276] BSC (Pin 447 to Pin 451)
- 7.00 [0.276] BSC (Pin 451 to Pin 455)
- 7.00 [0.276] BSC (Pin 455 to Pin 459)
- 7.00 [0.276] BSC (Pin 459 to Pin 463)
- 7.00 [0.276] BSC (Pin 463 to Pin 467)
- 7.00 [0.276] BSC (Pin 467 to Pin 471

**MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA**  
TEL +1 (408) 944-0800 FAX +1 (408) 474-1000 WEB <http://www.micrel.com>

Micrel makes no representations or warranties with respect to the accuracy or completeness of the information furnished in this data sheet. This information is not intended as a warranty and Micrel does not assume responsibility for its use. Micrel reserves the right to change circuitry, specifications and descriptions at any time without notice. No license, whether express, implied, arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Micrel's terms and conditions of sale for such products, Micrel assumes no liability whatsoever, and Micrel disclaims any express or implied warranty relating to the sale and/or use of Micrel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is a Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.