




Features

- Controller IC is not necessary
- Compatible with NTSC or PAL system
- High Resolution: 112,320 dots
- High Brightness
- Optimum Viewing Direction: 6 o'clock
- Up/Down and Left/Right Image Reversion
- Accepts Analog RGB input
- Requires external chroma decoder to accept composite video card

AND-TFT-25EN

480 x 234 Pixels LCD Color Monitor

The AND-TFT-25EN is a compact full color TFT LCD module, that is suitable for applications such as a portable television (NTSC), camcorder, digital camera application and other electronic products which require high quality flat panel displays. This device consists of a twisted nematic (TN) liquid crystal cell, that incorporates a TFT-array that has 480 x 234 pixels on a 2.5 inch diagonal screen, X and Y drivers, an LSI controller, and a built-in CCFL backlight.

Mechanical Characteristics

Item	Specification	Unit
Screen Size	2.5 inch (6.4 cm) diagonal	inch
Outline Dimensions	62.6 (H) x 54.25 (V) x 6.2 (D)	mm
Active Area	50.88 (H) x 37.67 (V)	mm
Input Signal	NTSC/PAL	—
Sub Pixel No.	480 (H) x 234 (V)	—
Sub Pixel Arrangement	Delta	—
Dot Pitch	0.106 (H) x 0.161 (V)	mm
Weight	36	g

Absolute Maximum Rating

Item		Symbol	Conditions	Absolute Maximum Rating		Unit
				Min.	Max.	
Supply Voltage	for Source Driver	$DV_{EE}, AV_{EE}, OV_{EE}, VP+$	$T_a = 25^{\circ}C$	0	+16.0	V
	for Gate Driver	H Level	$T_a = 25^{\circ}C$	0	+26.0	V
		L Level	$T_a = 25^{\circ}C$	-7.0	+20.0	V
	for Controller	PV_{DD}, V_{DD}	$T_a = 25^{\circ}C$	0	+6.5	V
DC Bias Voltage for Common Electrode		Vcom	$T_a = 25^{\circ}C$	+2	+6.0	V
Analog Input Signals		V_B, V_R, V_G	—	—	+12.0	V
Digital Input Signals			—	-0.5	+5.5	V
Digital Output Signals			—	-0.5	+5.5	V
Operating Temperature		Top	—	-10	+60	$^{\circ}C$
Storage Temperature		Tstg	—	-30	+80	$^{\circ}C$
Humidity (No condensation of water)		—	+60 $^{\circ}C$	—	95%	RH



Electrical Specification

Item		Symbol	Conditions	Specifications			Units
				Min.	Typ.	Max.	
Current Consumption	for Video Circuit	ICC		–	0.18	–	W
	for Backlight Lamp	IBL		–	0.66	–	W
	Supply Voltage	IDD	VDD= +5V	–	4.8	–	mA

(Ta = RT, VSS = 0V)

Recommended Operating Conditions

Item			Symbol	Conditions	Specifications			Unit
					Min.	Typ.	Max.	
Supply Voltage	for Source Driver		DV _{EE} , AV _{EE} , OV _{EE} , VP+	Ta = 25°C	+13.5	+14.0	+15.0	V
	for Gate Driver	H Level	V _{CC}	Ta = 25°C	+19.0	+20.0	+24.0	V
		L Level	V _{BBA} , V _{BBC}	Ta = 25°C	-5.5	-5.0	-4.0	
	for Controller		PV _{DD} , V _{DD}	Ta = 25°C	4.7	5.0	5.3	V
Digital Input Voltage (1)		H Level		Ta = 25°C	2.4	4.0	5.0	V
		L Level		Ta = 25°C	-0.3	–	0.8	
Voltage		H Level		Ta = 25°C	2.4	4.0	5.0	V
		L Level		Ta = 25°C	0.0	–	0.45	
DC Bias Voltage			V _{COM}	compatible	+2.0	–	+6.0	V
Analog Input Voltage		Amplitude	V _B , V _R , V _G		+1.12	–	12	
		DC component			+4.0	+6.0	+8.0	

Optical Specifications

Item		Symbol	Conditions	Specifications			Unit
				Min.	Typ.	Max.	
Luminance		LUM		–	200	–	cd/m ²
Contrast Ratio (1)		CR	$\frac{\text{Luminance when LCD is White}}{\text{Luminance when LCD is Black}}$	80	120	–	–
Reflectance Ratio		R		–	2.0	–	%
Viewing Angle	Horizontal	θ	CR>10	± 45	± 55	–	deg
	Vertical	θ (to 12 o'clock)		10	15	–	deg
		θ (to 6 o'clock)		30	35	–	deg
Response time	Rise	Tr	θ = 0°	–	–	30	ms
	Fall	Tf	φ = 0°	–	–	50	ms
Lamp Life + 25°C		Time	–	10,000	–	–	hr.

Note 1: CR= $\frac{\text{Luminance when LCD is White}}{\text{Luminance when LCD is Black}}$

Contrast Ratio is measured in optimum common electrode voltage.



Power Consumption

Parameter	Conditions	Typ.	Unit
Current for V_{CC}	$V_{CC} = +20V$	1.5	mA
Current for V_{BBA}	$V_{BBA} = -5V$	1.3	mA
Current for V_{BBC}	$V_{BBC} = -5V$	0.05	mA
Current for DV_{EE}	$DV_{EE} = +14V$	0.5	mA
Current for AV_{EE}	$AV_{EE} = +14V$	3.0	mA

Parameter	Conditions	Typ.	Unit
Current for OV_{EE}	$OV_{EE} = +14V$	4.0	mA
Current for PV_{DD}	$PV_{DD} = +5V$	0.2	mA
Current for V_{DD}	$V_{DD} = +5V$	4.8	mA
LCD Panel Power Consumption	—	0.18	W
Backlight Power Consumption	—	0.6	W
Total Power Consumption	—	0.78	W

Input/Output Timing

Parameter	Symbol	Min	Typ	Max	Unit	Remarks
Horizontal Sync Output Pulse	Width	T_{HO}	4.2	4.7	5.2	μs
	Phase Difference	T_{HP}	0	2	—	μs
	Rising Time	T_{HR}	—	—	0.5	μs
	Falling Time	T_{HF}	—	—	0.5	μs
Vertical Sync Output Pulse	Width	T_{VO}	—	4H	—	μs H=1/15.75KHz
	Phase Difference	T_{VPO}	—	1H	—	μs odd field
	Phase Difference	T_{VPE}	—	1.5H	—	μs even field
	Rising Time	T_{VR}	—	—	2	μs
	Frequency	f_{FRP}	7.67	7.87	8.07	KHz
Polarity Alternating Signal	Delay time	T_{FD}	—	—	4	μs
	Falling time	T_{VF}	—	—	2	μs



Interface Pin Assignment

Pin No.	Symbol	Function	Input/Output	Remarks
1	V_{COM}	Common electrode voltage	Input	Should be adjusted accurately to get the best contrast ratio
2	V_{BBA}	Supply voltage for level shifter (low level)	Input	-5V (Typ.)
3	PV_{DD}	Supply voltage for panel	Input	+5V (Typ.)
4	V_{BBC}	Supply voltage for panel	Input	-5V (Typ.)
5	V_{SS}	Ground for panel	Input	
6	V_{CC}	Supply voltage for level shifter (high level)	Input	+20V (Typ.)
7	V_{PIN}	Pulse high level for level shifter (high level)	Input	Must be more positive than V_{MIN} . (1)
8	V_{MIN}	Pulse low level for level shifter (low level)	Input	Must be more positive than V_{MIN} . (1)
9	FRP	Control signal for video inversion	Output	
10	$\overline{VSY}$	Vertical sync.	In/Out	
11	$\overline{HSY}$	Horizontal sync.	In/Out	
12	C_{SYNC}	Composite sync.	Input	
13	PD	Phase detector	Output	Output (0-5V range) from phase detector loop which is included in source driver
14	OSC	Clock input for LC oscillator	Input	OSC should be around 9.45 MHz, 0-5V input
15	V_{DD}	Supply voltage for logic circuit	Input	+5V (Typ.)
16	CKC	Control pin for select I/O signal	Input	Pin 16 (CKC) can select the function for Pin 11 (HSY) and Pin 10 (VSY). (2)
17	UD	Up/Down control	Input	Up/Down shift
18	LR	Left/Right shift control	Input	Left/Right shift
19	NP	NTSC/PAL selector	Input	Hi (+5V) for NTSC; Low (0V) for PAL
20	V_B	Video input B	Input	
21	V_G	Video input G	Input	
22	V_R	Video input R	Input	
23	GND	Ground for high voltage logic	Input	
24	GND	Ground for logic	Input	
25	DV_{EE}	Voltage supply for source driver high logic	Input	Equal to +14V
26	C_{COM}	Reference for sample and hold	Input	+5V (Typ.)
27	AV_{EE}	Voltage supply for sample and hold	Input	Equal to +14V
28	GND	Ground	Input	
29	OV_{EE}	Voltage supply for operation amplifier	Input	Equal to +14V
30	VP+	Pre-charge high level	Input	Equal to +14V

Note 1:

Pin	Symbol	Min	Typical	Max	Unit
7	V_{PIN}	12	13	14	V
8	V_{MIN}	5	6	7	V

Note 2: Pin 16(CKC) can select the function for Pin11 (HSY) and Pin 10(VSY).

CKC	$\overline{HSY}$	CSY	$\overline{VSY}$
Hi	HSY Output	CSY Input	$\overline{VSY}$ Output
Low	External $\overline{HSY}$ Input	External Clock Input	External $\overline{VSY}$ Input



Dimensional Outline

