

SOT323 NPN SILICON PLANAR
GENERAL PURPOSE TRANSISTOR

ISSUE 1 - DECEMBER 1998

ZUMT848B

Partmarking Detail: - T14



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	30	V
Collector-Emitter Voltage	V_{CES}	30	V
Collector-Emitter Voltage	V_{CEO}	30	V
Emitter-Base Voltage	V_{EBO}	5	V
Continuous Collector Current	I_C	100	mA
Peak Pulse Current	I_{EM}	200	mA
Base Current	I_{BM}	200	mA
Power Dissipation at $T_{amb}=25^{\circ}C$	P_{tot}	330	mW
Operating and Storage Temperature Range	T_j, T_{stg}	-55 to +150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector Cut-Off Current	I_{CBO}			15 5	nA μA	$V_{CB} = 30V$ $V_{CB} = 30V, T_{amb}=150^{\circ}C$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		90	250	mV	$I_C=10mA, I_B=0.5mA$
			200	600	mV	$I_C=100mA, I_B=5mA$
			300	600	mV	$I_C=10mA^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		700 900		mV	$I_C=10mA, I_B=0.5mA$ $I_C=100mA, I_B=5mA$
Base-Emitter Voltage	V_{BE}	580	650	750 770	mV	$I_C=2mA, V_{CE}=5V$ $I_C=10mA, V_{CE}=5V$

* Collector-Emitter Saturation Voltage at $I_C = 10mA$ for the characteristics going through the operating point $I_C = 11mA, V_{CE} = 1V$ at constant base current.

TYPICAL CHARACTERISTICS

ZUMT848B

ELECTRICAL CHARACTERISTICS (Continued)

PARAMETER		SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Noise Figure		N	–	2	10	dB	$V_{CB} = 5V, I_C=200\mu A, R_G=2k\Omega, f=1kHz, \Delta f=200Hz$
			–	–	–	dB	$V_{CB} = 5V, I_C=200\mu A, R_G=2k\Omega, f=30Hz \text{ to } 15kHz$ at 3dB points
Equivalent Noise Voltage		e_n	–	–	–	nV	$V_{CB} = 5V, I_C=200\mu A, R_G=2k\Omega, f=10Hz \text{ to } 50Hz$ at 3dB points
Dynamic Characteristics	Group B	h_{ie}	3.2	4.5	8.5	k Ω	$V_{CE}=5V$ $I_C=2mA$ $f=1kHz$
	Group B	h_{re}		2		$\times 10^{-4}$	
	Group B	h_{fe}	240	330	500		
	Group B	h_{oe}	–	30	60	μs	
Static Forward Current Ratio	Group B	h_{FE}		150			$I_C=0.01mA, V_{CE}=5V$
			200	290	450		$I_C=2mA, V_{CE}=5V$
			–	200	–		$I_C=100mA, V_{CE}=5V$
Transition Frequency		f_T	–	300	–	MHz	$I_C=10mA, V_{CE}=5V$ $f=100MHz$
Collector-Base Capacitance		C_{obo}		2.5	4.5	pF	$V_{CB}=10V, f=1MHz$
Emitter-Base Capacitance		C_{ibo}		9		pF	$V_{EB}=0.5V, f=1MHz$

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Diodes Incorporated:](#)

[ZUMT848BTA](#) [ZUMT848BTC](#)