

The technical drawing illustrates the dimensions and application of a Nylon Plastic Cinch Ring. The top view shows the ring's profile with dimensions: $C_{REF.}$ for the ring's width, E for the ring's height, and B for the length of the strap. A dimension line labeled $F_{REF.}$ indicates the total length of the strap. The bottom view shows the ring being used to cinch a strap, with dimension A indicating the distance from the ring to the end of the strap, and dimension D indicating the thickness of the strap.

PANDUIT PART NO.	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	MIN. LOOP TENSILE lbs. (N)	CROSS SECTION	APPROXIMATE WEIGHT lbs/100 PARTS (g)
	MIN. in (mm)	MAX. in (mm)									
UCT3S	.63 (16.0)	3.0 (76.2)	.100 (2.5)	.85 (21.6)	.45 (11.4)	.14 (3.6)	1.10 (27.9)	12.0 (305)	50 (222)	STANDARD	.59 (267)
UCT5S	.63 (16.0)	5.0 (127)	.100 (2.5)	.85 (21.6)	.45 (11.4)	.14 (3.6)	1.10 (27.9)	18.0 (457)	50 (222)	STANDARD	.81 (366)

1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND COLOR.
2) MINIMUM 2" OVERLAP REQUIRED TO ACHIEVE LOOP TENSILE RATING.

SS_27366_00.PRT

PANDUIT CORP. TINLEY PARK, ILLINOIS

TAK-TY HOOK & LOOP CABLE TIES
ULTRA-CINCH HOOK & LOOP TIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± .25 (.XXX) ± .030
(.XX) ± .125 ANGLES ±

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
JABO

MAT'L:

SCALE NONE

DATE	6/19/02
------	---------

WOVEN NYLON
HOOK/LOOP
COLOR: BLACK

DRAWING NO.

SS-27366

DWG
A
SIZE

7	4/12/06	FAB		ADDED PART WEIGHTS	27366	7			
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP	