


REVISIONS			
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Make changes to V _{IO} , +I _{IB} , -I _{IB} , I _{IO} , +A _{VOL} , -A _{VOL} , +I _{CC} , -I _{CC} , t _R , t _F tests and footnote three as specified under TABLE I. - ro	99-03-19	R. MONNIN
B	Make change to 1.5 and glassivation as specified in APPENDIX A. - ro	99-04-15	R. MONNIN
C	Replaced reference to MIL-STD-973 with reference to MIL-PRF-38535. -gt	03-10-03	R. MONNIN
D	Update boilerplate paragraphs. - ro	09-05-12	J. RODENBECK
E	Add device type 02. Make changes to footnote 2/, delete footnote 3/, and renumber footnotes as specified under Table I. Delete figure 2 irradiation circuit and device class M references. - ro	13-06-11	C. SAFFLE

REV																																	
SHEET																																	
REV	E	E	E	E	E																												
SHEET	15	16	17	18	19																												
REV STATUS				REV		E	E	E	E	E	E	E	E	E	E	E	E	E	E	E													
OF SHEETS				SHEET		1	2	3	4	5	6	7	8	9	10	11	12	13	14														
PMIC N/A				PREPARED BY RICK OFFICER				DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990 http://www.landandmaritime.dla.mil																									
STANDARD MICROCIRCUIT DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A				CHECKED BY RAJESH PITHADIA																													
				APPROVED BY RAYMOND MONNIN																													
				DRAWING APPROVAL DATE 98-10-15																													
				REVISION LEVEL E																													
				SIZE A		CAGE CODE 67268		5962-95687																									
				SHEET 1 OF 19																													

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device class Q) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels is reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

Device type	Generic number	Circuit function
01	HS-3530ARH	Radiation hardened, dielectric isolated, low power programmable operational amplifier
02	HS-3530AEH	Radiation hardened, dielectric isolated, low power programmable operational amplifier

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

Device class	Device requirements documentation
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

Outline letter	Descriptive designator	Terminals	Package style
G	MACY1-X8	8	Can
X	CDFP3-F10	10	Flat pack

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 2

1.3 Absolute maximum ratings. 1/

Voltage between +V _S and -V _S terminals	40 V
Differential input voltage	20 V
Voltage at either input terminal	+V _S to -V _S
I _{SET} (current at I _{SET})	500 μ A
V _{SET} (voltage to GND at I _{SET})	(+V _S - 2.0 V) < V _{SET} < +V _S
Output short circuit duration	Indefinite <u>2/</u>
Maximum power dissipation (P _D) (T _A = +125°C):	
Case outline G	0.31 W
Case outline X	0.35 W
Junction temperature (T _J)	+175°C
Storage temperature range	-65°C to +150°C
Lead temperature (soldering 10 seconds)	275°C
Thermal resistance, junction-to-case (θ_{JC}):	
Case outline G	70°C/W
Case outline X	36°C/W
Thermal resistance, junction-to-ambient (θ_{JA}):	
Case outline G	160°C/W
Case outline X	140°C/W

1.4 Recommended operating conditions.

Supply voltage range (V _S)	± 3 V to ± 15 V
Common mode input voltage (V _{INCM})	$\leq \frac{1}{2} (+V_S - -V_S)$
Load resistance (R _L)	≥ 2 k Ω
Ambient operating temperature range (T _A)	-55°C to +125°C

1.5 Radiation features:

Maximum total dose available (dose rate = 50 – 300 rads(Si)/s) :	
Device types 01	300 krad(Si) <u>3/</u>
Device types 02	300 krad(Si) <u>4/</u>
Maximum total dose available (dose rate $\leq .010$ rad(Si)/s):	
Device type 02	50 krad(Si) <u>4/</u>

- 1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
- 2/ Caution. Continuous long duration short-circuit operation may degrade the operating life of the device.
- 3/ Device type 01 may be dose rate sensitive in a space environment and may demonstrate enhanced low dose rate effects. The radiation end point limits for the noted parameters are guaranteed only for the conditions as specified in MIL-STD-883, method 1019, condition A to a maximum total dose of 300 krad(Si).
- 4/ Device type 02 radiation end point limits for the noted parameters are guaranteed only for the conditions as specified in MIL-STD-883, method 1019, condition A to a maximum total dose of 300 krad(Si) and condition D to a maximum total dose of 50 krad(Si).

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 3

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-883 - Test Method Standard Microcircuits.

MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.

MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <http://quicksearch.dla.mil/> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 as specified herein, or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

3.1.1 Microcircuit die. For the requirements of microcircuit die, see appendix A to this document.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.4 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.3 Radiation exposure circuit. The radiation exposure circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing and acquiring activity upon request.

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	±V _S	Group A subgroups	Device type	Limits		Unit
						Min	Max	
Input offset voltage	V _{IO}	V _{CM} = 0 V, I _{SET} = 1.5 μA and 15 μA M,D,P,L,R,F <u>2/</u>	±15 V	1	01,02	-3	3	mV
				2,3		-5	5	
				1		-5	5	
		V _{CM} = 0 V, I _{SET} = 1.5 μA and 15 μA M,D,P,L,R,F <u>2/</u>	±3 V	1		-3	3	
				2,3		-5	5	
				1		-5	5	
Input bias current	+I _{IB}	V _{CM} = 0 V, +R _S = 10 kΩ, -R _S = 100 Ω, I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>	±15 V	1	01,02	-40	40	nA
				2		-50	50	
				3		-60	60	
				1		-100	100	
	-I _{IB}	V _{CM} = 0 V, +R _S = 100 Ω, -R _S = 10 kΩ, I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>	±15 V	1		-40	40	
				2		-50	50	
				3		-60	60	
				1		-100	100	
Input offset current	I _{IO}	V _{CM} = 0 V, +R _S = 10 kΩ, -R _S = 100 Ω, I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>	±15 V	1	01,02	-15	15	nA
				2		-20	20	
				3		-30	30	
				1		-30	30	
Large signal voltage gain	+A _{VOL}	V _{OUT} = 0 V and +10 V, <u>3/</u> I _{SET} = 1.5 μA M,D,P,L,R,F <u>2/</u>	±15 V	1	01,02	65		kV/V
				2,3		25		
				1		15		
		V _{OUT} = 0 V and +10 V, <u>3/</u> I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>		1		80		
				2,3		50		
				1		30		
		V _{OUT} = 0 V and +1 V, <u>3/</u> I _{SET} = 1.5 μA M,D,P,L,R,F <u>2/</u>	±3 V	1		25		
				2,3		15		
				1		10		
		V _{OUT} = 0 V and +1 V, <u>3/</u> I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>		1		25		
				2,3		25		
				1		10		

See footnote at end of table.

**STANDARD
MICROCIRCUIT DRAWING**DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990SIZE
AREVISION LEVEL
E**5962-95687**SHEET
5

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	±V _S	Group A subgroups	Device type	Limits		Unit	
						Min	Max		
Large signal voltage gain	-A _{VOL}	V _{OUT} = 0 V and -10 V, <u>3/</u> I _{SET} = 1.5 μA M,D,P,L,R,F <u>2/</u>	±15 V	1	01,02	65		kV/V	
				2,3		25			
				1		15			
		V _{OUT} = 0 V and -10 V, <u>3/</u> I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>		1		80			
				2,3		50			
				1		30			
		V _{OUT} = 0 V and -1 V, <u>3/</u> I _{SET} = 1.5 μA M,D,P,L,R,F <u>2/</u>	±3 V	1		25			
				2,3		15			
				1		10			
				V _{OUT} = 0 V and -1 V, <u>3/</u> I _{SET} = 15 μA M,D,P,L,R,F <u>2/</u>		1	25		
						2,3	25		
						1	10		
Common mode rejection ratio	+CMRR	ΔV _{CM} = +5 V, V _{OUT} = -5 V, +V _S = +10 V, -V _S = -20 V, I _{SET} = 1.5 μA and 15 μA	±15 V	1,2,3	01,02	80		dB	
	-CMRR	ΔV _{CM} = -5 V, V _{OUT} = +5 V, +V _S = +20 V, -V _S = -10 V, I _{SET} = 1.5 μA and 15 μA	±15 V	1,2,3		80			
	+CMRR	ΔV _{CM} = +1.5 V, V _{OUT} = -1.5 V, +V _S = +1.5 V, -V _S = -4.5 V, I _{SET} = 1.5 μA and 15 μA	±3 V	1,2,3		80			
	-CMRR	ΔV _{CM} = -1.5 V, V _{OUT} = +1.5 V, +V _S = +4.5 V, -V _S = -1.5 V, I _{SET} = 1.5 μA and 15 μA	±3 V	1,2,3		80			

See footnotes at end of table.

**STANDARD
MICROCIRCUIT DRAWING**DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990SIZE
AREVISION LEVEL
E**5962-95687**SHEET
6

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	±V _S	Group A subgroups	Device type	Limits		Unit
						Min	Max	
Output voltage swing	+V _{OUT}	<u>3/</u>	±15 V	1	01,02	12.5		V
			2,3	10.5				
		<u>3/</u>	±3 V	1,2,3		2.0		
	-V _{OUT}	<u>3/</u>	±15 V	1			-12.5	
			2,3			-10.5		
		<u>3/</u>	±3 V	1,2,3			-2.0	
Output current	+I _{OUT}	I _{SET} = 1.5 μA, R _L = 2 kΩ	±15 V	1	01,02	0.25		mA
		I _{SET} = 15 μA, R _L = 2 kΩ				2.5		
	-I _{OUT}	I _{SET} = 1.5 μA, R _L = 2 kΩ		1			-0.25	
		I _{SET} = 15 μA, R _L = 2 kΩ					-2.5	
Quiescent power supply current	+I _{CC}	I _{SET} = 1.5 μA, I _{OUT} = 0 mA	±15 V	1,2,3	01,02		15	μA
				M,D,P,L,R,F <u>2/</u>		1		
		I _{SET} = 15 μA, I _{OUT} = 0 mA		1			150	
				2,3			160	
		M,D,P,L,R,F <u>2/</u>		1			160	
				I _{SET} = 1.5 μA, I _{OUT} = 0 mA		±3 V	1,2,3	
		M,D,P,L,R,F <u>2/</u>	1					
		I _{SET} = 15 μA, I _{OUT} = 0 mA	1				150	
			2,3				160	
		M,D,P,L,R,F <u>2/</u>	1				160	

See footnotes at end of table.

**STANDARD
MICROCIRCUIT DRAWING**
DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990

SIZE
A

REVISION LEVEL
E

5962-95687

SHEET
7

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	±V _S	Group A subgroups	Device type	Limits		Unit				
						Min	Max					
Quiescent power supply current	-I _{CC}	I _{SET} = 1.5 μA, I _{OUT} = 0 mA	±15 V	1,2,3	01,02	-15		μA				
		M,D,P,L,R,F <u>2/</u>		1		-15						
		I _{SET} = 15 μA, I _{OUT} = 0 mA		1		-150						
		M,D,P,L,R,F <u>2/</u>		2,3		-160						
				1		-160						
		I _{SET} = 1.5 μA, I _{OUT} = 0 mA		±3 V		1,2,3	-15					
		M,D,P,L,R,F <u>2/</u>	1	-15								
		I _{SET} = 15 μA, I _{OUT} = 0 mA	1	-150								
		M,D,P,L,R,F <u>2/</u>	2,3	-160								
			1	-160								
		Power supply rejection ratio	+PSRR	ΔV _S = 10 V, I _{SET} = 1.5 μA and 15 μA, +V _S = +10 V, -V _S = -15 V, +V _S = +20 V, -V _S = -15 V		±15 V	1,2,3		01,02	80		dB
				ΔV _S = 1.5 V, I _{SET} = 1.5 μA and 15 μA, +V _S = +3 V, -V _S = -3 V, +V _S = +4.5 V, -V _S = -3 V		±3 V				80		
-PSRR	ΔV _S = 10 V, I _{SET} = 1.5 μA and 15 μA, +V _S = +15 V, -V _S = -10 V, +V _S = +15 V, -V _S = -20 V		±15 V	1,2,3	80		dB					
	ΔV _S = 1.5 V, I _{SET} = 1.5 μA and 15 μA, +V _S = +3 V, -V _S = -3 V, +V _S = +3 V, -V _S = -4.5 V		±3 V		80							

See footnotes at end of table.

**STANDARD
MICROCIRCUIT DRAWING**DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990SIZE
AREVISION LEVEL
E**5962-95687**SHEET
8

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	±V _S	Group A subgroups	Device type	Limits		Unit
						Min	Max	
Slew rate <u>4/</u>	+SR	V _{OUT} = -10 V to +10 V, I _{SET} = 1.5 μA	±15 V	4	01,02	0.025		V/μs
		V _{OUT} = -10 V to +10 V, I _{SET} = 15 μA				0.25		
		V _{OUT} = -2 V to +2 V, I _{SET} = 1.5 μA	±3 V	4		0.01		
		V _{OUT} = -2 V to +2 V, I _{SET} = 15 μA				0.1		
	-SR	V _{OUT} = +10 V to -10 V, I _{SET} = 1.5 μA	±15 V	4		0.025		
		V _{OUT} = +10 V to -10 V, I _{SET} = 15 μA				0.25		
		V _{OUT} = +2 V to -2 V, I _{SET} = 1.5 μA	±3 V	4		0.01		
		V _{OUT} = +2 V to -2 V, I _{SET} = 15 μA				0.1		
Rise and fall <u>4/</u> time	t _R	V _{OUT} = 0 mV to +400 mV, I _{SET} = 1.5 μA, t _R measured at 10 % and 90 % points	±15 V	9	01,02		10	μs
		V _{OUT} = 0 mV to +400 mV, I _{SET} = 15 μA, t _R measured at 10 % and 90 % points				1.0		
	t _F	V _{OUT} = 0 mV to -400 mV, I _{SET} = 1.5 μA, t _F measured at 10 % and 90 % points		9			10	
		V _{OUT} = 0 mV to -400 mV, I _{SET} = 15 μA, t _F measured at 10 % and 90 % points					1.0	
Overshoot <u>4/</u>	+OS	V _{OUT} = 0 mV to +400 mV, I _{SET} = 1.5 μA and 15 μA	±15 V	4	01,02		35	%
	-OS	V _{OUT} = 0 mV to -400 mV, I _{SET} = 1.5 μA and 15 μA					35	

See footnotes at end of table.

**STANDARD
MICROCIRCUIT DRAWING**DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990SIZE
AREVISION LEVEL
E**5962-95687**SHEET
9

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions <u>1/</u> -55°C ≤ T _A ≤ +125°C unless otherwise specified	±V _S	Group A subgroups	Device type	Limits		Unit
						Min	Max	
Full power bandwidth <u>5/ 6/ 7/</u>	FPBW	V _{PEAK} = 10 V, I _{SET} = 1.5 μA	±15 V	4	01,02	0.39		kHz
		V _{PEAK} = 10 V, I _{SET} = 15 μA				3.9		
Quiescent power consumption <u>5/ 6/ 8/</u>	PC	V _{OUT} = 0 V, I _{OUT} = 0 mA, I _{SET} = 1.5 μA and 15 μA	±15 V	1,2,3	01,02		4.8	mW

1/ Unless otherwise specified, output voltage (V_{OUT}) = 0 V, source resistance (R_S) = 100 Ω, and load resistance (R_L) = 500 kΩ.

2/ RHA device type 01 supplied to this drawing will meet all levels M, D, P, L, R, and F of irradiation. However, device type 01 is only tested at the "F" level in accordance with MIL-STD-883 method 1019 condition A (see 1.5 herein). Device type 01 may be dose rate sensitive in a space environment and may demonstrate enhanced low dose rate effects.

RHA device type 02 supplied to this drawing will meet all levels M, D, P, L, R, and F of irradiation for condition A and levels M, D, P, and L for condition D. However, device type 02 is only tested at the "F" level in accordance with MIL-STD-883, method 1019, condition A and tested at the "L" level in accordance with MIL-STD-883, method 1019, condition D (see 1.5 herein).

Devices supplied to this drawing are only radiation tested for the parameters referencing this footnote. When performing post irradiation electrical measurements for any RHA level, T_A = +25°C.

3/ R_L = 86 kΩ at I_{SET} = 1.5 μA and R_L = 5 kΩ at I_{SET} = 15 μA.

4/ Unless otherwise specified, load capacitance (C_L) = 100 pF, gain (A_{VCL}) = +1, and load resistance (R_L) = 75 kΩ.

5/ If not tested, shall be guaranteed to the limits specified in table I herein.

6/ Unless otherwise specified, load capacitance (C_L) = 100 pF, gain (A_{VCL}) = +1, and source resistance (R_S) = 50 Ω.

7/ Full power bandwidth guarantee based on slew rate measurement using FPBW = slew rate / (2 × π × V_{PEAK}).

8/ Quiescent power consumption based upon quiescent supply current test maximum. No load on outputs.

**STANDARD
MICROCIRCUIT DRAWING**

DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990

SIZE
A

5962-95687

REVISION LEVEL
E

SHEET
10

Device types	01, 02	
Case outlines	G	X
Terminal number	Terminal symbol	
1	OFFSET NULL	NC
2	-INPUT	OFFSET NULL
3	+INPUT	-INPUT
4	-V _S	+INPUT
5	OFFSET NULL	-V _S
6	OUTPUT	NC
7	+V _S	OFFSET NULL
8	I _{SET}	OUTPUT
9	---	+V _S
10	---	I _{SET}

NC = Not connected

FIGURE 1. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 11

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). The certificate of compliance submitted to DLA Land and Maritime-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 shall be provided with each lot of microcircuits delivered to this drawing.

4. VERIFICATION

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection.

4.2.1 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections, and as specified herein.

4.4.1 Group A inspection.

- a. Tests shall be as specified in table IIA herein.
- b. Subgroups 7, 8, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table IIA herein.

4.4.2.1 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table IIA herein.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 12

TABLE IIA. Electrical test requirements.

Test requirements	Subgroups (in accordance with MIL-PRF-38535, table III)	
	Device class Q	Device class V
Interim electrical parameters (see 4.2)	1,4,9	1,4,9
Final electrical parameters (see 4.2)	1,2,3,4, <u>1</u> / 5,6,9	1,2,3, <u>1</u> / <u>2</u> / 4,5,6,9
Group A test requirements (see 4.4)	1,2,3,4,5,6,9	1,2,3,4,5,6,9
Group C end-point electrical parameters (see 4.4)	1,2,3,4,5,6,9	1,2,3,4, <u>2</u> / 5,6,9
Group D end-point electrical parameters (see 4.4)	1,4,9	1,4,9
Group E end-point electrical parameters (see 4.4)	1,4,9	1,4,9

- 1/ PDA applies to subgroup 1. For class V, PDA applies to subgroup 1 and Δ 's.
2/ Delta limits as specified in table IIB shall be required where specified, and the delta limits shall be computed with reference to the zero hour electrical parameters (see Table I).

Table IIB. Burn-in and operating life test delta parameters. ($T_A = +25^\circ\text{C}$).

Parameter	Symbol	Conditions	Delta limits
Input offset voltage	V_{IO}	$\pm V_S = \pm 15\text{ V}$, $I_{SET} = 1.5\text{ }\mu\text{A}$ and $15\text{ }\mu\text{A}$	$\pm 1.5\text{ mV}$
Input bias current	$\pm I_{IB}$	$\pm V_S = \pm 15\text{ V}$, $I_{SET} = 15\text{ }\mu\text{A}$	$\pm 30\text{ nA}$

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table IIA herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at $T_A = +25^\circ\text{C} \pm 5^\circ\text{C}$, after exposure, to the subgroups specified in table IIA herein.

4.4.4.1 Total dose irradiation testing. Total dose irradiation testing shall be performed in accordance with MIL-STD-883 method 1019, condition A and as specified herein for device types 01 and 02. In addition, for device type 02 a low dose rate test shall be performed in accordance with MIL-STD-883 method 1019, condition D and as specified herein.

4.4.4.1.1 Accelerated annealing test. Accelerated annealing tests shall be performed on all devices requiring a RHA level greater than 5 krad(Si). The post-anneal end-point electrical parameter limits shall be as specified in table I herein and shall be the pre-irradiation end-point electrical parameter limit at $25^\circ\text{C} \pm 5^\circ\text{C}$. Testing shall be performed at initial qualification and after any design or process changes which may affect the RHA response of the device.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 13

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform DLA Land and Maritime when a system application requires configuration control and which SMD's are applicable to that system. DLA Land and Maritime will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DLA Land and Maritime-VA, telephone (614) 692-8108.

6.4 Comments. Comments on this drawing should be directed to DLA Land and Maritime-VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0540.

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in MIL-HDBK-103 and QML-38535. The vendors listed in MIL-HDBK-103 and QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DLA Land and Maritime-VA and have agreed to this drawing.


STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 14

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-95687

A.1 SCOPE

A.1.1 Scope. This appendix establishes minimum requirements for microcircuit die to be supplied under the Qualified Manufacturers List (QML) Program. QML microcircuit die meeting the requirements of MIL-PRF-38535 and the manufacturers approved QM plan for use in monolithic microcircuits, multi-chip modules (MCMs), hybrids, electronic modules, or devices using chip and wire designs in accordance with MIL-PRF-38534 are specified herein. Two product assurance classes consisting of military high reliability (device class Q) and space application (device class V) are reflected in the Part or Identification Number (PIN). When available, a choice of Radiation Hardiness Assurance (RHA) levels are reflected in the PIN.

A.1.2 PIN. The PIN is as shown in the following example:



A.1.2.1 RHA designator. Device classes Q and V RHA identified die meet the MIL-PRF-38535 specified RHA levels. A dash (-) indicates a non-RHA die.

A.1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	HS-3530ARH	Radiation hardened, DI low power, programmable operational amplifier
02	HS-3530AEH	Radiation hardened, DI low power, programmable operational amplifier

A.1.2.3 Device class designator.

<u>Device class</u>	<u>Device requirements documentation</u>
Q or V	Certification and qualification to the die requirements of MIL-PRF-38535

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 15

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-95687

A.1.2.4 Die details. The die details designation is a unique letter which designates the die's physical dimensions, bonding pad location(s) and related electrical function(s), interface materials, and other assembly related information, for each product and variant supplied to this appendix.

A.1.2.4.1 Die physical dimensions.

<u>Die type</u>	<u>Figure number</u>
01, 02	A-1

A.1.2.4.2 Die bonding pad locations and electrical functions.

<u>Die type</u>	<u>Figure number</u>
01, 02	A-1

A.1.2.4.3 Interface materials.

<u>Die type</u>	<u>Figure number</u>
01, 02	A-1

A.1.2.4.4 Assembly related information.

<u>Die type</u>	<u>Figure number</u>
01, 02	A-1

A.1.3 Absolute maximum ratings. See paragraph 1.3 herein for details.

A.1.4 Recommended operating conditions. See paragraph 1.4 herein for details.

**STANDARD
MICROCIRCUIT DRAWING**
DLA LAND AND MARITIME
COLUMBUS, OHIO 43218-3990

SIZE
A

REVISION LEVEL
E

5962-95687

SHEET
16

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-95687

A.2 APPLICABLE DOCUMENTS.

A.2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARD

MIL-STD-883 - Test Method Standard Microcircuits.

DEPARTMENT OF DEFENSE HANDBOOKS

MIL-HDBK-103 - List of Standard Microcircuit Drawings.

MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <http://quicksearch.dla.mil/> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

A.2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

A.3 REQUIREMENTS

A.3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

A.3.2 Design, construction and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein and the manufacturer's QM plan for device classes Q and V.

A.3.2.1 Die physical dimensions. The die physical dimensions shall be as specified in A.1.2.4.1 and on figure A-1.

A.3.2.2 Die bonding pad locations and electrical functions. The die bonding pad locations and electrical functions shall be as specified in A.1.2.4.2 and on figure A-1.

A.3.2.3 Interface materials. The interface materials for the die shall be as specified in A.1.2.4.3 and on figure A-1.

A.3.2.4 Assembly related information. The assembly related information shall be as specified in A.1.2.4.4 and on figure A-1.

A.3.2.5 Radiation exposure circuit. The radiation exposure circuit shall be as defined in paragraph 3.2.3 herein.

A.3.3 Electrical performance characteristics and post-irradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and post-irradiation parameter limits are as specified in table I of the body of this document.

A.3.4 Electrical test requirements. The wafer probe test requirements shall include functional and parametric testing sufficient to make the packaged die capable of meeting the electrical performance requirements in table I.

A.3.5 Marking. As a minimum, each unique lot of die, loaded in single or multiple stack of carriers, for shipment to a customer, shall be identified with the wafer lot number, the certification mark, the manufacturer's identification and the PIN listed in A.1.2 herein. The certification mark shall be a "QML" or "Q" as required by MIL-PRF-38535.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 17

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-95687

A.3.6 Certification of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see A.6.4 herein). The certificate of compliance submitted to DLA Land and Maritime -VA prior to listing as an approved source of supply for this appendix shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and the requirements herein.

A.3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 shall be provided with each lot of microcircuit die delivered to this drawing.

A.4 VERIFICATION

A.4.1 Sampling and inspection. For device classes Q and V, die sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modifications in the QM plan shall not affect the form, fit, or function as described herein.

A.4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and as defined in the manufacturer's QM plan. As a minimum, it shall consist of:

- a. Wafer lot acceptance for class V product using the criteria defined in MIL-STD-883, method 5007.
- b. 100% wafer probe (see paragraph A.3.4 herein).
- c. 100% internal visual inspection to the applicable class Q or V criteria defined in MIL-STD-883, method 2010 or the alternate procedures allowed in MIL-STD-883, method 5004.

A.4.3 Conformance inspection.

A.4.3.1 Group E inspection. Group E inspection is required only for parts intended to be identified as radiation assured (see A.3.5 herein). RHA levels for device classes Q and V shall be as specified in MIL-PRF-38535. End point electrical testing of packaged die shall be as specified in table IIA herein. Group E tests and conditions are as specified in paragraphs 4.4.4, 4.4.4.1, and 4.4.4.1.1 herein.

A.5 DIE CARRIER

A.5.1 Die carrier requirements. The requirements for the die carrier shall be accordance with the manufacturer's QM plan or as specified in the purchase order by the acquiring activity. The die carrier shall provide adequate physical, mechanical and electrostatic protection.

A.6 NOTES

A.6.1 Intended use. Microcircuit die conforming to this drawing are intended for use in microcircuits built in accordance with MIL-PRF-38535 or MIL-PRF-38534 for government microcircuit applications (original equipment), design applications, and logistics purposes.


A.6.2 Comments. Comments on this appendix should be directed to DLA Land and Maritime -VA, Columbus, Ohio, 43218-3990 or telephone (614)-692-0540.

A.6.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535 and MIL-HDBK-1331.

A.6.4 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed within QML-38535 have submitted a certificate of compliance (see A.3.6 herein) to DLA Land and Maritime -VA and have agreed to this drawing.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 18

APPENDIX A
APPENDIX A FORMS A PART OF SMD 5962-95687



Die physical dimensions:

Die size: 1720 microns x 1390 microns
Die thickness: 19 $\pm$ 1 mils

Interface materials.

Top metallization: Al Si Cu 16.0 kÅ $\pm$ 2 kÅ
Backside metallization: None

Glassivation.

Type: PSG
Thickness: 8.0 kÅ $\pm$ 1.0 kÅ

Substrate: Dielectric Isolation (DI)

Assembly related information.

Substrate potential: Insulator
Special assembly instructions: None

FIGURE A-1. Die bonding pad locations and electrical functions.

STANDARD MICROCIRCUIT DRAWING DLA LAND AND MARITIME COLUMBUS, OHIO 43218-3990	SIZE A		5962-95687
		REVISION LEVEL E	SHEET 19

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 13-06-11

Approved sources of supply for SMD 5962-95687 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DLA Land and Maritime-VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DLA Land and Maritime maintains an online database of all current sources of supply at <http://www.landandmaritime.dla.mil/Programs/Smcr/>.

Standard microcircuit drawing PIN <u>1</u> /	Vendor CAGE number	Vendor similar PIN <u>2</u> /
5962F9568701QGA	34371	HS2-3530ARH-8
5962F9568701VGA	34371	HS2-3530ARH-Q
5962F9568701VXC	34371	HS9-3530ARH-Q
5962F9568701V9A	34371	HS0-3530ARH-Q
5962F9568702VGA	34371	HS2-3530AEH-Q
5962F9568702VXC	34371	HS9-3530AEH-Q
5962F9568702V9A	34371	HS0-3530AEH-Q

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

34371

Vendor name
and address

Intersil Corporation
1001 Murphy Ranch Road
Milpitas, CA 95035-6803

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.