

Dual Conductor, High Current Power Inductors

Flat-Pac™ FPT705 Series



Description

- Halogen free, lead free, RoHS compliant
- 125°C maximum total operating temperature
- 8.0 x 7.1 x 5.35mm maximum surface mount package
- Ferrite core material
- Dual conductor, two-turn construction
- Inductance range from 170nH to 300nH

Applications

- Designed specifically for use with Picor® Cool-Power® ZVS-Buck Regulator Family (Picor part number Series PI33xx and PI34xx)

Environmental Data

- Storage temperature range (component): -40°C to +125°C
- Operating temperature range: -40°C to +125°C (ambient + self-temperature rise)
- Solder reflow temperature: J-STD-020D compliant

Packaging

- Supplied in tape-and reel packaging, 1000 parts per 13" diameter reel

Product Specifications				
Part Number ⁵	OCL ¹ (nH)	I _{rms} ² (Amps)	I _{sat} ³ (Amps)	DCR ⁴ (mΩ) @ 20°C
FPT705-170-R	170 (±12%)	13	31	0.65 ± 0.15
FPT705-190-R	190		28	
FPT705-200-R	200		25	
FPT705-230-R	230		23	
FPT705-270-R	270		19	
FPT705-300-R	300		17	

1. Open Circuit Inductance (OCL) test parameters: 1.0MHz, 0.1V_{rms}, 0.0Adc @ 25°C ± 10% (Pins 1-3, short 2-4).
2. I_{rms}: DC current for an approximate temperature rise of 40°C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat-generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed 125°C under worst case operating conditions verified in the end application.

3. I_{sat}: Peak current for < 2% rolloff at +25°C.

4. DCR Tested from Pins (1-2) and (3-4).


5. Part Number Definition: FPT705-xxx-R

FPT705 = Product code and size


xxx= Inductance value in nH

"-R" Suffix = RoHS compliant

Dimensions - mm




Packaging Information - mm




Supplied in tape and reel packaging, 1000 parts on a 13" diameter reel.

Inductance Characteristics

FPT705-170-R




FPT705-190-R




Inductance Characteristics

FPT705-200-R & -230-R



FPT705-270-R & -300-R



Solder Reflow Profile




Table 1 - Standard SnPb Solder (T_c)

Package	Volume mm ³	Volume mm ³
Thickness	<350	≥350
<2.5mm	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_c)

Package	Volume mm ³	Volume mm ³	Volume mm ³
Thickness	<350	350 - 2000	>2000
<1.6mm	260°C	260°C	260°C
1.6 - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak	100°C	150°C
• Temperature min. (T_{smin})	100°C	150°C
• Temperature max. (T_{smax})	150°C	200°C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T_{smax} to T_p	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T_L)	183°C	217°C
Time at liquidous (t_L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T_p)*	Table 1	Table 2
Time (t_p)** within 5 °C of the specified classification temperature (T_c)	20 Seconds**	30 Seconds**
Average ramp-down rate (T_p to T_{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

North America

Cooper Electronic Technologies
1225 Broken Sound Parkway NW
Boca Raton, FL 33487-3533
Tel: 1-561-998-4100
Fax: 1-561-241-6640
Toll Free: 1-888-414-2645

Cooper Bussmann
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-636-527-1607

Europe

Cooper Electronic Technologies
Cooper (UK) Limited
Burton-on-the-Wolds
Leicestershire • LE12 5TH UK
Tel: +44 (0) 1509 882 737
Fax: +44 (0) 1509 882 786

Cooper Electronic Technologies
Avda. Santa Eulalia, 290
08223
Terrassa, (Barcelona), Spain
Tel: +34 937 362 812
+34 937 362 813
Fax: +34 937 362 719

Asia Pacific

Cooper Electronic Technologies
1 Jalan Kilang Timor
#06-01 Pacific Tech Centre
Singapore 159303
Tel: +65 278 6151
Fax: +65 270 4160

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cooper Bussmann:](#)

[FPT705-170-R](#) [FPT705-190-R](#) [FPT705-270-R](#) [FPT705-300-R](#)