




FCP20N60 / FCPF20N60 600V N-Channel MOSFET

Features

- 650V @ $T_J = 150^\circ\text{C}$
- Typ. $R_{DS(on)} = 0.15\Omega$
- Ultra low gate charge (typ. $Q_g = 75\text{nC}$)
- Low effective output capacitance (typ. $C_{oss,eff} = 165\text{pF}$)
- 100% avalanche tested
- RoHS Compliant



Description

SuperFET™ is, Fairchild's proprietary, new generation of high voltage MOSFET family that is utilizing an advanced charge balance mechanism for outstanding low on-resistance and lower gate charge performance.

This advanced technology has been tailored to minimize conduction loss, provide superior switching performance, and withstand extreme dv/dt rate and higher avalanche energy. Consequently, SuperFET is very suitable for various AC/DC power conversion in switching mode operation for system miniaturization and higher efficiency.

Absolute Maximum Ratings

| Symbol | Parameter | FCP20N60 | FCPF20N60 | Unit |
|----------------|--|-------------|--------------|--------------------------|
| V_{DSS} | Drain-Source Voltage | 600 | | V |
| I_D | Drain Current - Continuous ($T_C = 25^\circ\text{C}$) - Continuous ($T_C = 100^\circ\text{C}$) | 20 12.5 | 20* 12.5* | A A |
| I_{DM} | Drain Current - Pulsed | (Note 1) | 60 | 60* |
| V_{GSS} | Gate-Source voltage | | ± 30 | V |
| E_{AS} | Single Pulsed Avalanche Energy | (Note 2) | 690 | mJ |
| I_{AR} | Avalanche Current | (Note 1) | 20 | A |
| E_{AR} | Repetitive Avalanche Energy | (Note 1) | 20.8 | mJ |
| dv/dt | Peak Diode Recovery dv/dt | (Note 3) | 4.5 | V/ns |
| P_D | Power Dissipation ($T_C = 25^\circ\text{C}$) - Derate above 25°C | 208 1.67 | 39 0.3 | W W/ $^\circ\text{C}$ |
| T_J, T_{STG} | Operating and Storage Temperature Range | | -55 to +150 | $^\circ\text{C}$ |
| T_L | Maximum Lead Temperature for Soldering Purpose, 1/8" from Case for 5 Seconds | | 300 | $^\circ\text{C}$ |

*Drain current limited by maximum junction temperature

Thermal Characteristics

| Symbol | Parameter | FCP20N60 | FCPF20N60 | Unit |
|-----------------|---|----------|-----------|---------------------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction-to-Case | 0.6 | 3.2 | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | 62.5 | 62.5 | $^\circ\text{C}/\text{W}$ |

Package Marking and Ordering Information

| Device Marking | Device | Package | Reel Size | Tape Width | Quantity |
|----------------|-----------|---------|-----------|------------|----------|
| FCP20N60 | FCP20N60 | TO-220 | - | - | 50 |
| FCPF20N60 | FCPF20N60 | TO-220F | - | - | 50 |

Electrical Characteristics

$T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|---|---|---|----------|----------|------|------------------|
| Off Characteristics | | | | | | |
| BV _{DSS} | Drain-Source Breakdown Voltage | $V_{GS} = 0\text{V}$, $I_D = 250\mu\text{A}$, $T_J = 25^\circ\text{C}$ | 600 | -- | -- | V |
| | | $V_{GS} = 0\text{V}$, $I_D = 250\mu\text{A}$, $T_J = 150^\circ\text{C}$ | -- | 650 | -- | V |
| ΔBV_{DSS} / ΔT_J | Breakdown Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$, Referenced to 25°C | -- | 0.6 | -- | $^\circ\text{C}$ |
| BV _{DS} | Drain-Source Avalanche Breakdown Voltage | $V_{GS} = 0\text{V}$, $I_D = 20\text{A}$ | -- | 700 | -- | V |
| I _{DSS} | Zero Gate Voltage Drain Current | $V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$ $V_{DS} = 480\text{V}$, $T_C = 125^\circ\text{C}$ | -- -- | -- 10 | 1 | μA |
| I _{GSSF} | Gate-Body Leakage Current, Forward | $V_{GS} = 30\text{V}$, $V_{DS} = 0\text{V}$ | -- | -- | 100 | nA |
| I _{GSSR} | Gate-Body Leakage Current, Reverse | $V_{GS} = -30\text{V}$, $V_{DS} = 0\text{V}$ | -- | -- | -100 | nA |
| On Characteristics | | | | | | |
| V _{GS(th)} | Gate Threshold Voltage | $V_{DS} = V_{GS}$, $I_D = 250\mu\text{A}$ | 3.0 | -- | 5.0 | V |
| R _{DS(on)} | Static Drain-Source On-Resistance | $V_{GS} = 10\text{V}$, $I_D = 10\text{A}$ | -- | 0.15 | 0.19 | Ω |
| g _{FS} | Forward Transconductance | $V_{DS} = 40\text{V}$, $I_D = 10\text{A}$ | (Note 4) | -- | 17 | -- |
| | | | | -- | -- | S |
| Dynamic Characteristics | | | | | | |
| C _{iss} | Input Capacitance | $V_{DS} = 25\text{V}$, $V_{GS} = 0\text{V}$, $f = 1.0\text{MHz}$ | -- | 2370 | 3080 | pF |
| C _{oss} | Output Capacitance | | -- | 1280 | 1665 | pF |
| C _{rss} | Reverse Transfer Capacitance | | -- | 95 | -- | pF |
| C _{oss} | Output Capacitance | $V_{DS} = 480\text{V}$, $V_{GS} = 0\text{V}$, $f = 1.0\text{MHz}$ | -- | 65 | 85 | pF |
| C _{oss} eff. | Effective Output Capacitance | $V_{DS} = 0\text{V}$ to 400V , $V_{GS} = 0\text{V}$ | -- | 165 | -- | pF |
| Switching Characteristics | | | | | | |
| t _{d(on)} | Turn-On Delay Time | $V_{DD} = 300\text{V}$, $I_D = 20\text{A}$ $R_G = 25\Omega$ | -- | 62 | 135 | ns |
| t _r | Turn-On Rise Time | | -- | 140 | 290 | ns |
| t _{d(off)} | Turn-Off Delay Time | | -- | 230 | 470 | ns |
| t _f | Turn-Off Fall Time | | -- | 65 | 140 | ns |
| Q _g | Total Gate Charge | $V_{DS} = 480\text{V}$, $I_D = 20\text{A}$ $V_{GS} = 10\text{V}$ | -- | 75 | 98 | nC |
| Q _{gs} | Gate-Source Charge | | -- | 13.5 | 18 | nC |
| Q _{gd} | Gate-Drain Charge | | -- | 36 | -- | nC |
| Drain-Source Diode Characteristics and Maximum Ratings | | | | | | |
| I _S | Maximum Continuous Drain-Source Diode Forward Current | -- | -- | 20 | -- | A |
| I _{SM} | Maximum Pulsed Drain-Source Diode Forward Current | -- | -- | 60 | -- | A |
| V _{SD} | Drain-Source Diode Forward Voltage | $V_{GS} = 0\text{V}$, $I_S = 20\text{A}$ | -- | -- | 1.4 | V |
| t _{rr} | Reverse Recovery Time | $V_{GS} = 0\text{V}$, $I_S = 20\text{A}$ $dI/dt = 100\text{A}/\mu\text{s}$ | -- | 530 | -- | ns |
| Q _{rr} | Reverse Recovery Charge | | -- | 10.5 | -- | μC |

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. I_{AS} = 10A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C
3. I_{SD} ≤ 20A, di/dt ≤ 200A/μs, V_{DD} ≤ BV_{DSS}, Starting T_J = 25°C
4. Pulse Test: Pulse width ≤ 300μs, Duty Cycle ≤ 2%
5. Essentially Independent of Operating Temperature Typical Characteristics

Typical Performance Characteristics

Figure 1. On-Region Characteristics




Figure 3. On-Resistance Variation vs. Drain Current and Gate Voltage




Figure 2. Transfer Characteristics




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature




Figure 5. Capacitance Characteristics





Figure 6. Gate Charge Characteristics



Typical Performance Characteristics (Continued)

Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On-Resistance Variation vs. Temperature




Figure 9-1. Maximum Safe Operating Area for FCP20N60




Figure 9-2. Maximum Safe Operating Area for FCPF20N60





Figure 10. Maximum Drain Current vs. Case Temperature



Typical Performance Characteristics (Continued)

Figure 11-1. Transient Thermal Response Curve for FCP20N60







Figure 11-2. Transient Thermal Response Curve for FCPF20N60




Gate Charge Test Circuit & Waveform





Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching Test Circuit & Waveforms




Peak Diode Recovery dv/dt Test Circuit & Waveforms




Mechanical Dimensions

TO - 220



Mechanical Dimensions (Continued)

TO-220F





TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
EcoSPARK®
EfficientMax™
EZSWITCH™ *



Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FlashWriter®
FPS™
F-PFST™

FRFET®
Global Power Resource™
Green FPST™
Green FPST™ e-Series™
GTO™
IntelliMAX™
ISOPLANAR™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MillerDrive™
MotionMax™
Motion-SPM™
OPTOLOGIC®
OPTOPLANAR®
PDP SPM™
Power-SPM™
PowerTrench®
PowerXST™

Programmable Active Droop™
QFET®
QST™
Quiet Series™
RapidConfigure™
Saving our world, 1mW /W /kW at a time™
SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET™
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS™
SyncFET™
SYSTEM ®
GENERAL
The Power Franchise®

the power franchise
TinyBoost™
TinyBuck™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
μUserDes™
μSerDes™
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
XSTM

* EZSWITCH™ and FlashWriter® are trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|-----------------------|---|
| Advance Information | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design. |
| Obsolete | Not In Production | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only. |

Rev. I37

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Fairchild Semiconductor](#):

[FCP20N60FS](#) [FCPF20N60FS](#) [FCP20N60_F080](#)