

2SK3013
(FP16W60VX2)

600V 16A


FEATURES

- Input capacitance (Ciss) is small.
Especially, input capacitance at 0 bias is small.
- The static Rds(on) is small.
- The switching time is fast.
- Avalanche resistance guaranteed.

APPLICATION

- Switching power supply of
AC 100-200V input
- Inverter
- Power Factor Control Circuit

OUTLINE DIMENSIONS



RATINGS

●Absolute Maximum Ratings (Tc = 25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T _{stg}		-55~150	°C
Channel Temperature	T _{ch}		150	
Drain-Source Voltage	V _{DSS}		600	V
Gate-Source Voltage	V _{GSS}		±30	
Continuous Drain Current (DC)	I _D		16	
Continuous Drain Current (Peak)	I _{DP}		48	A
Continuous Source Current (DC)	I _S		16	
Total Power Dissipation	P _T		70	W
Single Pulse Avalanche Current	I _{AS}	T _{ch} = 25°C	16	A
Dielectric Strength	V _{dis}	Terminals to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque : 0.5N·m)	0.8	N·m

●Electrical Characteristics $T_c = 25^{\circ}\text{C}$


Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 1\text{mA}$, $V_{GS} = 0\text{V}$	600			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$			250	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS} = \pm 30\text{V}$, $V_{DS} = 0\text{V}$			± 0.1	
Forward Transconductance	g_{fs}	$I_D = 8\text{A}$, $V_{DS} = 10\text{V}$	6.2	10.0		S
Static Drain-Source On-state Resistance	$R_{DS(ON)}$	$I_D = 8\text{A}$, $V_{GS} = 10\text{V}$		0.45	0.6	Ω
Gate Threshold Voltage	V_{TH}	$I_D = 1\text{mA}$, $V_{DS} = 10\text{V}$	2.5	3	3.5	V
Source-Drain Diode Forward Voltage	V_{SD}	$I_S = 8\text{A}$, $V_{GS} = 0\text{V}$			1.5	
Thermal Resistance	θ_{jc}	junction to case			1.78	$^{\circ}\text{C/W}$
Total Gate Charge	Q_g	$V_{GS} = 10\text{V}$, $I_D = 16\text{A}$, $V_{DD} = 400\text{V}$		85		nC
Input Capacitance	C_{iss}	$V_{DS} = 10\text{V}$, $V_{GS} = 0\text{V}$, $f = 1\text{MHz}$		2300		pF
Reverse Transfer Capacitance	C_{rss}			180		
Output Capacitance	C_{oss}			480		
Turn-On Time	t_{on}	$I_D = 8\text{A}$, $V_{GS} = 10\text{V}$, $R_L = 19\Omega$		130	280	ns
Turn-Off Time	t_{off}			260	500	

2SK3013


Transfer Characteristics



2SK3013 Static Drain-Source On-state Resistance




2SK3013 Gate Threshold Voltage




2SK3013


Safe Operating Area




2SK3013 Transient Thermal Impedance



2SK3013 Single Avalanche Energy Derating




2SK3013 Capacitance




2SK3013

Single Avalanche Current - Inductive Load



2SK3013

Power Derating



2SK3013 Gate Charge Characteristics

