

FL Series

- Long life for $\phi 4 \times 5L$ to $\phi 8 \times 5L$ mm range
- Endurance with ripple current : 3,000 hours at 105°C
- Suitable for long life products
- Solvent resistant type (see PRECAUTIONS AND GUIDELINES)
- RoHS2 Compliant




SPECIFICATIONS

Items	Characteristics							
Category	-40 to +105℃							
Temperature Range								
Rated Voltage Range	6.3 to 50V _{dc}							
Capacitance Tolerance	± 20% (M) (at 20℃, 120Hz)							
Leakage Current	I=0.03CV or 3μA, whichever is greater. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20℃ after 2 minutes)							
Dissipation Factor (tan δ)	Rated voltage (V _{dc})	6.3V	10V	16V	25V	35V	50V	
	tan δ (Max.)	0.50	0.40	0.35	0.30	0.25	0.25	(at 20℃, 120Hz)
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20℃ after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for 3,000 hours at 105℃.							
	Capacitance change	≤ ±30% of the initial value						
	D.F. (tan δ)	≤300% of the initial specified value						
	Leakage current	≤The initial specified value						
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 1,000 hours at 105℃ without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4.							
	Capacitance change	≤ ±20% of the initial value						
	D.F. (tan δ)	≤200% of the initial specified value						
	Leakage current	≤The initial specified value						

DIMENSIONS [mm]


Terminal Code : E



* $\phi 8 \times 5L$: Coating case

ϕD	4	5	6.3	8
ϕd	0.45	0.45	0.45	0.45
F	1.5	2.0	2.5	2.5
$\phi D'$	$\phi D + 0.5 \text{ max.}$			
L'	L + 1.0 max.			

PART NUMBERING SYSTEM



Please refer to "Product code guide (radial lead type)"

STANDARD RATINGS

WV (V _{ac})	Cap (μ F)	Case size ϕ D $\times$ L (mm)	$\tan \delta$	Impedance (Ω max./20°C, 100kHz)	Rated ripple current (mA _{rms} /105°C, 100kHz)	Part No.
6.3	33	4 $\times$ 5	0.50	5.4	37	EFL-6R3E□□330MD05D
	47	4 $\times$ 7	0.50	4.5	44	EFL-6R3E□□470MD07D
	56	5 $\times$ 5	0.50	3.1	57	EFL-6R3E□□560ME05D
	82	5 $\times$ 7	0.50	2.5	70	EFL-6R3E□□820ME07D
	100	6.3 $\times$ 5	0.50	1.7	82	EFL-6R3E□□101MF05D
	150	6.3 $\times$ 7	0.50	1.3	116	EFL-6R3E□□151MF07D
10	220	8 $\times$ 5	0.50	1.5	110	EFL-6R3E□□221MH05G
	22	4 $\times$ 5	0.40	5.4	37	EFL-100E□□220MD05D
	33	4 $\times$ 7	0.40	4.5	44	EFL-100E□□330MD07D
	33	5 $\times$ 5	0.40	3.1	57	EFL-100E□□330ME05D
	47	5 $\times$ 7	0.40	2.5	70	EFL-100E□□470ME07D
	68	6.3 $\times$ 5	0.40	1.7	82	EFL-100E□□680MF05D
16	100	6.3 $\times$ 7	0.40	1.3	116	EFL-100E□□101MF07D
	150	8 $\times$ 5	0.40	1.5	110	EFL-100E□□151MH05G
	15	4 $\times$ 5	0.35	5.4	37	EFL-160E□□150MD05D
	22	4 $\times$ 7	0.35	4.5	44	EFL-160E□□220MD07D
	22	5 $\times$ 5	0.35	3.1	57	EFL-160E□□220ME05D
	33	5 $\times$ 7	0.35	2.5	70	EFL-160E□□330ME07D
25	47	6.3 $\times$ 5	0.35	1.7	82	EFL-160E□□470MF05D
	68	6.3 $\times$ 7	0.35	1.3	116	EFL-160E□□680MF07D
	100	8 $\times$ 5	0.35	1.5	110	EFL-160E□□101MH05G
	10	4 $\times$ 5	0.30	5.4	37	EFL-250E□□100MD05D
	15	4 $\times$ 7	0.30	4.5	44	EFL-250E□□150MD07D
	15	5 $\times$ 5	0.30	3.1	57	EFL-250E□□150ME05D
35	22	5 $\times$ 7	0.30	2.5	70	EFL-250E□□220ME07D
	33	6.3 $\times$ 5	0.30	1.7	82	EFL-250E□□330MF05D
	56	6.3 $\times$ 7	0.30	1.3	116	EFL-250E□□560MF07D
	68	8 $\times$ 5	0.30	1.5	110	EFL-250E□□680MH05G
	4.7	4 $\times$ 5	0.25	5.4	37	EFL-350E□□4R7MD05D
	6.8	4 $\times$ 7	0.25	4.5	44	EFL-350E□□6R8MD07D
50	10	5 $\times$ 5	0.25	3.1	57	EFL-350E□□100ME05D
	10	5 $\times$ 7	0.25	2.5	70	EFL-350E□□100ME07D
	22	6.3 $\times$ 5	0.25	1.7	82	EFL-350E□□220MF05D
	22	6.3 $\times$ 7	0.25	1.3	116	EFL-350E□□220MF07D
	33	8 $\times$ 5	0.25	1.5	110	EFL-350E□□330MH05G
	1.0	4 $\times$ 5	0.25	19	18	EFL-500E□□1R0MD05D
50	2.2	4 $\times$ 5	0.25	14	22	EFL-500E□□2R2MD05D
	3.3	4 $\times$ 5	0.25	11	26	EFL-500E□□3R3MD05D
	4.7	4 $\times$ 7	0.25	9.0	30	EFL-500E□□4R7MD07D
	4.7	5 $\times$ 5	0.25	6.0	40	EFL-500E□□4R7ME05D
	6.8	5 $\times$ 7	0.25	4.8	50	EFL-500E□□6R8ME07D
	10	6.3 $\times$ 5	0.25	2.9	63	EFL-500E□□100MF05D
	15	6.3 $\times$ 7	0.25	2.2	90	EFL-500E□□150MF07D
	22	8 $\times$ 5	0.25	2.6	84	EFL-500E□□220MH05G

□□ : Enter the appropriate lead forming or taping code.

RATED RIPPLE CURRENT MULTIPLIERS

Frequency Multipliers

Capacitance(μ F)	Frequency(Hz)	120	1k	10k	100k
to 3.3		0.20	0.66	0.90	1.00
4.7 to 6.8		0.35	0.70	0.90	1.00
10 to 150		0.40	0.75	0.90	1.00
220		0.50	0.85	0.94	1.00

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.