

WT11i Bluetooth Class 1 Module™



Description

WT11i is a fully integrated *Bluetooth* 2.1 + EDR, class 1 module combining antenna, *Bluetooth* radio and an on-board *Bluetooth* stack. The WT11i module utilizes Bluegiga's latest generation RF technology and provides better performance than Bluegiga's previous class 1 *Bluetooth* module WT11. For OEMs WT11i offers trouble free *Bluetooth* integration for applications where the best performance is needed and it is a drop-in performance upgrade for designs where WT11 is already used. WT11i comes with Bluegiga's iWRAP firmware offering the users simple software integration without the need of *Bluetooth* protocol or profile development.

Benefits

- ▶ Fully integrated solution
 - Lower cost
 - Faster time to market
- ▶ Good radio performance
 - Long range and robust connections
 - Programmable TX power
- ▶ *Bluetooth* qualified
 - Proven interoperability
 - No qualification costs
- ▶ WT11 compatible
 - Drop-in upgrade for WT11 based designs

Key Features

- ▶ *Bluetooth* v.2.1 + EDR, class 1
- ▶ Radio performance
 - Transmit power : +17 dBm
 - Receiver sensitivity: -86 dBm
- ▶ Integrated iWRAP *Bluetooth* stack
 - 14 integrated *Bluetooth* profiles
 - Simple ASCII based host protocol
- ▶ Standard HCI over UART or USB
- ▶ Industrial temperature range: -40C to +85C
- ▶ *Bluetooth* end product, CE, FCC and IC qualified
- ▶ WT11i with integrated chip antenna and HCI USB 2.0 + EDR WT11i-A-HCI

Target Markets

- ▶ M2M
- ▶ Industrial
- ▶ Healthcare and medical
- ▶ Point-of-sale
- ▶ Automotive

Target Applications

- ▶ RFID and bar code scanners
- ▶ Point-of-sale terminals
- ▶ Industrial PCs and PDAs
- ▶ Medical device gateways
- ▶ Industrial sensors and collectors



TECHNICAL DATA

Hardware

- Interfaces
 - 1 x UART, flow control, 3Mbps (host interface)
 - 1 x USB 2.0 device (host interface)
 - 1 x SPI (Programming/debugging interface)
 - 1 x 8-bit AIO
 - 6 x GPIO
 - 1 x PCM (audio interface)
- Power supply: 3.3V
- Internal antenna or 50 OHM RF pin
- Dimensions: 35.8 x 14.5 x 2.3mm
- Surface mount
- Processor core: 16-bit XAP2

Firmware

- iWRAP™ firmware includes all relevant *Bluetooth* profiles and simple control interface to access the *Bluetooth* functionality
- Standard HCI over UART/USB available
- Possibility to develop custom firmware

Product Codes

- | | |
|---|------------------|
| • WT11i with integrated chip antenna and iWRAP4 | WT11i-A-AI4 |
| • WT11i with USB and HCI 2.1 + EDR | WT11i-A-HCI21 |
| • WT11i with integrated chip antenna and iWRAP HDP | WT11i-A-eHealth |
| • WT11i with integrated chip antenna and IEEE manager | WT11i-A-mgr 2738 |

Evaluation Tools

- | | |
|--------------------------|---------|
| • WT11i Evaluation Board | EBWT11i |
|--------------------------|---------|

Certifications

- *Bluetooth* 2.1 + EDR
- CE (EN300328, EN300489)
- FCC
- Industry Canada

For more information about Bluegiga Technologies, please contact:

Bluegiga Technologies Oy
 Sinikalliontie 5 A
 02630 Espoo, Finland
 Phone: +358 9 435 50 60
 Fax: +358 9 435 50 660
www.bluegiga.com
sales@bluegiga.com

© Bluegiga Technologies 2000-2011.

Bluegiga Technologies takes no responsibility for any mistakes that might appear in this document. It reserves the right to change devices, software or specifications detailed here at any time without notice, and does not make any commitment to update the information contained here. Bluegiga products are not authorised for any use as critical components in life support devices or systems. Bluegiga Access Server, Access Point, AX4, BSM, iWRAP and WRAP THOR are trademarks of Bluegiga Technologies. The *Bluetooth* trademark and logo are registered trademarks and are owned by the Bluetooth SIG, Inc.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Bluegiga Technologies:](#)

[EBWT11i-A](#) [WT11i-E-AI5](#) [WT11i-A-AI5](#)