




# AMPMODU Interconnection System



## Table of Contents

### Disclaimer

While Tyco Electronics Corporation and its affiliates referenced herein ("Tyco Electronics") have made every reasonable effort to confirm the accuracy of the information in this catalog, Tyco Electronics does not guarantee that it is error-free, nor does Tyco Electronics make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current.

Tyco Electronics reserves the right to make any adjustments to the information contained herein at any time without notice. Tyco Electronics expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. Tyco Electronics' only obligations are those in the Tyco Electronics Standard Terms and Conditions of Sale, and in no case will Tyco Electronics be responsible for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of its products. Users should independently evaluate the suitability of, and test each product for, their application.

The dimensions, specifications, designs, construction, materials and processes in this catalog are for reference purposes only and are subject to change without notice. Please consult Tyco Electronics for the most current product information.

The export of certain Tyco Electronics products is restricted by the Arms Export Control Act (Title 22, U.S.C. Sec 2751, et seq.) or the Export Administration Act of 1979, as amended (Title 50, U.S.C., App. 2401 et seq.). Orders may be subject to export approval by the U.S. Government. Buyer must comply with all applicable export laws of all applicable jurisdictions.

© 2008 and 2004 Tyco Electronics Corporation. All Rights Reserved.

AMP, ACTION PIN, AMP-LATCH, AMP-O-ELECTRIC, AMP-O-MATIC, AMPLIMITE, AMPMODU, AMPOMATOR, CERTI-CRIMP, CHAMPOMATOR, PRO-CRIMPER, R-CAM, TE LOGO and TYCO ELECTRONICS are trademarks of Tyco Electronics Corporation.

Teflon® is a trademark of E.I. du Pont de Nemours and Company.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners.

**See inside back cover for Global Contacts and phone numbers.**

### 1 PC/104 and PC/104-Plus Connectors

|                        |      |
|------------------------|------|
| Introduction           | 5    |
| PC/104, Press Fit      | 6, 7 |
| PC/104-Plus, Press Fit | 8, 9 |
| PC/104, Solder         | 10   |
| PC/104-Plus, Solder    | 11   |
| Accessories, Kits      | 12   |

### 2 0.050 [1.27] x 0.050 [1.27] CENTERLINE AMPMODU 50/50 Grid

#### Board-to-Board Vertical Receptacles and Headers:

|                                  |        |
|----------------------------------|--------|
| Introduction                     | 13, 14 |
| Vertical Receptacles, Double Row | 15     |
| Vertical Headers, Double Row     | 16     |
| Recommended PC Board Layouts     | 17     |

#### Board-to-Board Right-Angle Headers:

|                                                            |    |
|------------------------------------------------------------|----|
| Introduction                                               | 18 |
| Right-Angle Headers, Double Row, Latching and Non-Latching | 19 |

#### Cable-to-Board Connectors:

|                                                           |    |
|-----------------------------------------------------------|----|
| Introduction                                              | 20 |
| Receptacle Connectors, Double Row, With and Without Latch | 21 |
| Cable Connector Terminating Cover, Double Row             | 22 |
| IDC (Insulation Displacement Crimp) Tooling               | 23 |

#### Performance Specifications

#### Technical Documents

### 3 .050 [1.27] x 0.100 [2.54] CENTERLINE AMPMODU System 50

#### Board-to-Board Connectors, Thru-Hole:

|                                  |        |
|----------------------------------|--------|
| Introduction                     | 26     |
| Headers, Shrouded and Unshrouded | 27-35  |
| Introduction                     | 36     |
| Receptacles                      | 37-40  |
| PC Board Hole Layouts            | 41, 42 |

#### Board-to-Board Connectors, Surface-Mount:

|              |    |
|--------------|----|
| Introduction | 43 |
| Headers      | 44 |
| Receptacles  | 45 |

#### Cable-to-Board Connectors, FFC Cable:

|                               |        |
|-------------------------------|--------|
| Introduction                  | 46     |
| Flexible Flat Conductor Cable | 47     |
| FFC Contacts                  | 48     |
| Receptacle Housings           | 49-52  |
| ZIF-Line Connectors           | 53, 54 |

#### Cable-to-Board Connectors, Ribbon Cable:

|                                            |        |
|--------------------------------------------|--------|
| Introduction                               | 55     |
| Ribbon Cable Receptacles                   | 56     |
| Paddleboard Receptacles                    | 57     |
| Flat Ribbon Cable                          | 58, 59 |
| Application Tooling for Flex Film Contacts | 60     |

#### Application Tooling

#### Performance Specifications

#### Technical Documents

PC/104 and PC/104-Plus Connectors

1

.050 x .050 [1.27 x 1.27] Centerline

2

.050 x .100 [1.27 x 2.54] Centerline

3

AMPMODU 2mm Connectors

4

.100 x .100 [2.54 x 2.54] Centerline

5

.125 x .125 [3.18 x 3.18] Centerline

6

.156 [3.96] Centerline

7

Shunts

8

## Table of Contents (Continued)

|          |                                                                   |          |
|----------|-------------------------------------------------------------------|----------|
| <b>4</b> | <b>AMPMODU 2mm Connectors</b>                                     |          |
|          | AMPMODU 2mm Connectors (Board to Board)                           | 65       |
|          | Headers, Unshrouded, Double Row, Thru-Hole Mount                  | 66, 67   |
|          | Breakaway Headers, Unshrouded, Double Row, Thru-Hole Mount        | 68-70    |
|          | Breakaway Headers, Unshrouded, Double Row, Surface Mount          | 71, 72   |
|          | Stacking Header, Unshrouded, Double Row, Thru-Hole Mount          | 73       |
|          | Headers, Shrouded, Double Row, Thru-Hole, Right-Angle Mount       | 74, 75   |
|          | Headers, Shrouded, Double Row, Surface Mount                      | 76, 77   |
|          | Headers, Shrouded, Double Row, Thru-Hole Mount with Cable Shrouds | 78, 79   |
|          | Receptacles, Double Row, Thru-Hole, Vertical Mount                | 80, 81   |
|          | Receptacles, Double Row, Surface Mount, Right-Angle Mount         | 82       |
|          | Receptacles, Double Row, Thru-Hole, Right-Angle Mount             | 83       |
|          | Receptacles, Double Row, Surface Mount, Vertical Mount            | 84       |
| <b>5</b> | <b>.100 [2.54] x .100 [2.54] CENTERLINE</b>                       |          |
|          | Introduction                                                      | 85-87    |
|          | Terms Explained                                                   | 87       |
|          | Wire Sizes                                                        | 88       |
|          | Contact Platings                                                  | 88       |
|          | Mating Post Lengths                                               | 88       |
|          | Application Tooling                                               | 88       |
|          | Board-to-Board Solutions Guides, .100[2.54] Centerline Products   | 89       |
|          | Wire-to-Board Solutions Guide, .100[2.54] Centerline Products     | 89       |
|          | Mating Post Selection Guide                                       | 90       |
|          | Parallel Stacking Guide for Board-to-Board Applications           | 91       |
|          | <b>Board-to-Board Products:</b>                                   |          |
|          | Unshrouded Headers                                                | 92-100   |
|          | Breakaway and Retention Headers-Unshrouded                        | 101-105  |
|          | Reeled Breakaway Headers                                          | 106, 107 |
|          | Surface Mount Breakaway Headers                                   | 108-110  |
|          | Unshrouded Stacking Headers- Breakaway                            | 111-113  |
|          | Shrouded Headers                                                  | 114-140  |
|          | Standard Profile                                                  | 114-133  |
|          | Low Profile                                                       | 134-140  |
|          | Shrouded Stacking Headers                                         | 141-144  |
|          | ACTION PIN Headers                                                | 145-149  |
|          | ACTION PIN Press-Fit Posts                                        | 150, 151 |
|          | Application Tooling for ACTION PIN Posts                          | 152, 153 |
|          | ACTION PIN Stacking Connectors                                    | 154-161  |
|          | Application Tooling for AMP ACTION PIN Stacking Connectors        | 162      |
|          | 0.025 [0.64] Square Posts                                         | 163      |
|          | 0.025 [0.64] Square Continuous Posts                              | 164, 165 |
|          | 0.045 [1.14] Square Continuous Posts                              | 166, 167 |
|          | Horizontal Mount Receptacle Assemblies, Mod II                    | 168-173  |
|          | Vertical Mount Receptacle Assemblies, Mod II & Mod IV             | 174-184  |
|          | Surface Mount Vertical Receptacles, Mod IV                        | 185-192  |
|          | Two-Piece Printed Circuit Board Connectors                        | 193-202  |
|          | Accessories                                                       | 203-205  |
|          | <b>Wire-to-Board Products:</b>                                    |          |
|          | Locking Clip Contacts and Housings                                | 206-209  |
|          | Mod IV Contacts and Housings                                      | 210-220  |
|          | Short Point Contacts and Housings                                 | 221-224  |
|          | MTE Interconnection System                                        | 225-250  |
|          | Surface Mount MTE Headers (Right-Angle & Vertical)                | 251, 252 |
|          | Interchangeable Contacts, Wire Crimp (Snap-In)                    | 253, 254 |
|          | MT and Shielded MT Connectors                                     | 255-265  |
|          | Mini-Tandem Spring Receptacle Contacts                            | 266-269  |
|          | <b>Application Tooling</b>                                        | 270-275  |
|          | <b>Technical Documents</b>                                        | 276-278  |

**1**  
PC/104 and PC/104-Plus Connectors

**2**  
.050 x .050 [1.27 x 1.27] Centerline

**3**  
.050 x .100 [1.27 x 2.54] Centerline

**4**  
AMPMODU 2mm Connectors

**5**  
.100 x .100 [2.54 x 2.54] Centerline

**6**  
.125 x .125 [3.18 x 3.18] Centerline

**7**  
.156 [3.96] Centerline

**8**  
Shunts

## Table of Contents (Continued)

|                                                        |                                                                                |          |
|--------------------------------------------------------|--------------------------------------------------------------------------------|----------|
| <b>1</b><br>PC/104 and PC/104-<br>Plus Connectors      | <b>6</b> .125 [3.18] x .125 [3.18] CENTERLINE<br>Wire-to-Board Product:        |          |
|                                                        | Level V IDC Connectors .....                                                   | 279-282  |
| <b>2</b><br>.050 x .050<br>[1.27 x 1.27]<br>Centerline | <b>7</b> .156 [3.96] CENTERLINE<br>Mod I 0.031 x 0.062 Interconnection System  |          |
|                                                        | Introduction .....                                                             | 283, 284 |
| <b>3</b><br>.050 x .100<br>[1.27 x 2.54]<br>Centerline | Receptacles, Vertical and Horizontal Board Mount .....                         | 285, 286 |
|                                                        | Receptacle Assemblies, Vertical and Horizontal Board Mount .....               | 287-289  |
| <b>4</b><br>AMPMODU<br>2mm Connectors                  | Receptacles, Crimp Snap-In (Wire Applied) .....                                | 290      |
|                                                        | Receptacle Housings, Standard Profile-Unkeyed (With/Without Strain Relief) ... | 291, 292 |
| <b>5</b><br>.100 x .100<br>[2.54 x 2.54]<br>Centerline | Receptacle Housings, Low Profile-Keyed .....                                   | 293      |
|                                                        | Posts, Machined Applied .....                                                  | 294      |
| <b>6</b><br>.125 x .125<br>[3.18 x 3.18]<br>Centerline | Headers:                                                                       |          |
|                                                        | Straight Post, Keyed .....                                                     | 295, 296 |
| <b>7</b><br>.156 [3.96]<br>Centerline                  | Right-Angle, Keyed .....                                                       | 297      |
|                                                        | Locking Clip Contacts, Crimp Snap-In (Wire Applied) .....                      | 298      |
| <b>8</b><br>Shunts                                     | Locking Clip Connector Housings, Single Row, Crimp Snap-In .....               | 299      |
|                                                        | Application Tooling .....                                                      | 300-304  |
|                                                        | Performance Specifications .....                                               | 305      |
|                                                        | Technical Documents .....                                                      | 305      |
|                                                        | Dual In-Line Package DIP Shunts .....                                          | 306, 307 |
|                                                        | Post Shunts .....                                                              | 308-310  |
|                                                        | Performance Specifications .....                                               | 311      |
|                                                        | Technical Documents .....                                                      | 311      |
|                                                        | Part Number Index .....                                                        | 313-316  |

### Restriction on the use of Hazardous Substances (RoHS)

At Tyco Electronics, we're ready to support your RoHS requirements. We've assessed more than 1.5 million end items/components for RoHS compliance, and issued new part numbers where any change was required to eliminate the restricted materials. Part numbers in this catalog are identified as:

**RoHS Compliant** — Part numbers in this catalog are RoHS Compliant, unless marked otherwise. These products comply with European Union Directive 2002/95/EC as amended 1 January 2006 that restricts the use of lead, mercury, cadmium, hexavalent chromium, PBB, and PBDE in certain electrical and electronic products sold into the EU as of 1 July 2006.

**NOTE:** For purposes of this Catalog, included within the definition of RoHS Compliant are products that are clearly "Out of Scope" of the RoHS Directive such as hand tools and other non-electrical accessories.

**NOTE:** Information regarding RoHS compliance is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information provided by our suppliers. This information is subject to change. For latest compliance status, refer to our website referenced at right.

### Getting the Information You Need

Our comprehensive on-line RoHS Customer Support Center provides a forum to answer your questions and support your RoHS needs. A RoHS FAQ (Frequently Asked Questions) is available with links to more detailed information. You can also submit RoHS questions and receive a response within 24 hours during a normal work week. The Support Center also provides:



- Cross-Reference from Non-compliant to Compliant Products
- Ability to browse RoHS Compliant Products in our on-line catalog
- Downloadable Technical Data Customer Information Presentation
- More detailed information regarding the definitions used above
- So whatever your questions when it comes to RoHS, we have the answers at [www.tycoelectronics.com/leadfree](http://www.tycoelectronics.com/leadfree)

**RoHS**  
Customer  
Support  
Center

## PC/104 and PC/104-Plus Connectors

### Product Facts

- Press fit design — eliminates hand soldering
- Unitized PC/104 connector assembly — eliminates two piece (64 pin & 40 pin) configuration
- Integral board spacers with captive hardware — eases & improves assembly efficiency while minimizing stocked hardware
- “Flat-rock” insertable — no need for complex insertion tooling
- Recognized by Underwriters' Laboratories to US and Canadian standards  file No. E28476
- Fully compliant with PC104 & PC104-Plus standards
- Solutions available for lead free processes (ie. ENIG and silver immersion plated PCB's)



The PC/104 and PC/104-Plus connectors are industry standard product offerings which comply with the interconnection requirements defined by the PC/104 organization (<http://www.pc104.org>)

Both products are designed specifically for “flat-rock” press-fit installation for ease of application. Solder version is also available.

Optional integral standoffs minimize the customer's system assembly time.

The Tyco Electronics offering of the standard PC/104 product is a unitized connector rather than the two piece, 40 and 64 position connectors currently on the market. Customer needs to stock and apply only one part number rather than two.

### Performance Specifications

#### Electrical Characteristics

Meets requirements of PC/104 and PC/104-Plus standards

**Nominal Resistance** — 10 milliohms maximum,  $\Delta R$

**Insulation Resistance** — 1000 megohms minimum

**Dielectric Withstanding Voltage** — 500 VAC for 1 min. at sea level

#### Mechanical Characteristics

Meets requirements of PC/104 and PC/104-Plus standards

**Current** — Signal application only

**Temperature** — -55° to 105°C

#### Material and Finish

**Housing** — Black Thermoplastic, UL 94V-0

**Contact** — Phosphor Bronze, Full Gold all over Nickel (stackthrough), Gold on mating end, Tin or Tin-lead on PCB tail all over Nickel (non-stackthrough)

### Need more information?

Call Technical Support 1-800-522-6752:

Technical Support is staffed with specialists well versed in all Tyco Electronics products. The Center can provide you with:

- Technical Support
- Catalogs
- Technical Documents
- Tyco Electronics Authorized Distributor Locations

### Technical Documents

#### Product Specifications

108-1956

#### Application Specifications

114-13021

| Connector   | Centerline   | Position |
|-------------|--------------|----------|
| PC/104      | .100<br>2.54 | 104*     |
| PC/104-Plus | .079<br>2.0  | 120**    |

\*Two circuits plugged per PC/104 specification. Other options available.

\*\*One circuit plugged per PC/104-Plus specification. Other options available.

## PC/104, Press-Fit

### Material and Finish


**Housing** — Glass filled thermoplastic, Black, 94V-0 rated

### Contacts

**Stackthrough** — Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000005 [0.000130] min. Gold on remainder, all over .000050 [0.00127] Nickel  
or  
Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000100-.000200 [0.00254-.00508] matte tin on compliant section, .000005 [0.000130] min. Gold on remainder of post, all over .000050 [0.00127] Nickel

**Non-Stackthrough** — Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000100 [0.00254] matte tin or tin-lead on remainder, all over .000050 [0.00127] Nickel

**Screwlocks** — Steel, Clear Chromate over Zinc




### Stackthrough, No Standoffs

Gold plated contacts\*

**Part No. 1375795-1** (keyed), **Part No. 1375795-2** (unkeyed)

Gold plated contacts with Tin plated compliant pin section\*\*

**Part No. 1375795-3** (keyed), **Part No. 1375795-4** (unkeyed)



Keyed


### Non-Stackthrough, No Standoffs

Tin-lead plated tails\*

**Part No. 1375796-1** (keyed), **Part No. 1375796-2** (unkeyed)

Matte tin plated tails\*\*

**Part No. 1375796-3** (keyed), **Part No. 1375796-4** (unkeyed)



Unkeyed

**Recommended PC Board Layout**  
See Customer Drawing for  
Hole Geometry and Recommended Plating.

**Note:** All part numbers are RoHS compliant.

\* For RoHS exempt Tin-lead processes (including ENIG Plated PCB's)

\*\* for Silver Immersion processes or where a total lead free solution is desired

## PC/104, Press-Fit (Continued)


### Stackthrough, 2 Standoffs

Gold plated contacts\*

Part No. 1375793-1 (keyed), Part No. 1375793-2 (unkeyed)

Gold plated contacts with Tin plated compliant pin section\*\*

Part No. 1375793-3 (keyed), Part No. 1375793-4 (unkeyed)




### Non-Stackthrough, 2 Standoffs

Tin-lead plated tails\*

Part No. 1375794-1 (keyed), Part No. 1375794-2 (unkeyed)

Matte tin plated tails\*\*

Part No. 1375794-3 (keyed), Part No. 1375794-4 (unkeyed)




### Stackthrough, 4 Standoffs

Gold plated contacts\*


Part No. 1375791-1 (keyed), Part No. 1375791-2 (unkeyed)

Gold plated contacts with Tin plated compliant pin section\*\*

Part No. 1375791-3 (keyed), Part No. 1375791-4 (unkeyed)



Keyed



Unkeyed

Recommended PC Board Layout  
See Customer Drawing for  
Hole Geometry and Recommended Plating.

**Note:** All part numbers are RoHS compliant.

\* For RoHS exempt Tin-lead processes (including ENIG Plated PCB's)

\*\* for Silver Immersion processes or where a total lead free solution is desired

## PC/104-Plus, Press-Fit

### Material and Finish


**Housing** — Glass filled thermoplastic, Black, 94V-0 rated

### Contacts

**Stackthrough** — Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000005 [0.000130] min. Gold on remainder, all over .000050 [0.00127] Nickel  
or  
Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000100-.000200 [0.000254-.00508] matte tin on compliant section, .000005 [0.000130] min. Gold on remainder of post, all over .000050 [0.00127] Nickel

**Non-Stackthrough** — Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000100 [0.00254] matte tin or tin-lead on remainder, all over .000050 [0.00127] Nickel

**Screwlocks** — Steel, Clear Chromate over Zinc



### Stackthrough, No Standoffs

Gold plated contacts\*

**Part No. 1375799-1** (unkeyed)

**Part No. 1375799-2** (keyed-A1) per PC/104-Plus specification

**Part No. 1375799-3** (keyed-D30) per PC/104-Plus specification

Gold plated contacts with Tin plated compliant pin section\*\*

**Part No. 1375799-4** (unkeyed)

**Part No. 1375799-5** (keyed-A1) per PC/104-Plus specification

**Part No. 1375799-6** (keyed-D30) per PC/104-Plus specification

### Non-Stackthrough, No Standoffs

Tin-lead plated tails\*

**Part No. 1375800-1** (unkeyed)

**Part No. 1375800-2** (keyed-A1) per PC/104-Plus specification


**Part No. 1375800-3** (keyed-D30) per PC/104-Plus specification

Matte tin plated tails\*\*


**Part No. 1375800-4** (unkeyed)

**Part No. 1375800-5** (keyed-A1) per PC/104-Plus specification


**Part No. 1375800-6** (keyed-D30) per PC/104-Plus specification



**Recommended PC Board Layout**  
for 1375799-1, 1375799-4,  
1375800-1, 1375800-4



**Recommended PC Board Layout**  
for 1375799-2, 1375799-5,  
1375800-2, 1375800-5



**Recommended PC Board Layout**  
for 1375799-3, 1375799-6,  
1375800-3, 1375800-6

See Customer Drawing for Hole Geometry and Recommended Plating.  
(Including ENIG plated PCB's)

**Note:** All part numbers are RoHS compliant.

\* For RoHS exempt Tin-lead processes (including ENIG Plated PCB's)


\*\* for Silver Immersion processes or where a total lead free solution is desired

## PC/104-Plus, Press-Fit (Continued)

### Non-Stackthrough, 2 Standoffs


Tin-lead plated tails\*

- Part No. 1375798-1** (unkeyed)  
**Part No. 1375798-2** (keyed-A1)  
per PC/104-Plus specification  
**Part No. 1375798-3** (keyed-D30)  
per PC/104-Plus specification



Matte tin plated tails\*\*


- Part No. 1375798-4** (unkeyed),  
**Part No. 1375798-5** (keyed-A1)  
per PC/104-Plus specification  
**Part No. 1375798-6** (keyed-D30)  
per PC/104-Plus specification



### Stackthrough, 2 Standoffs



Gold plated contacts\*

- Part No. 1375797-1** (unkeyed)  
**Part No. 1375797-2** (keyed-A1)  
per PC/104-Plus specification  
**Part No. 1375797-3** (keyed-D30)  
per PC/104-Plus specification




Gold plated contacts with Tin plated compliant pin section\*\*


- Part No. 1375797-4** (unkeyed)  
**Part No. 1375797-5** (keyed-A1)  
per PC/104-Plus specification  
**Part No. 1375797-6** (keyed-D30)  
per PC/104-Plus specification



**Recommended PC Board Layout**  
for 1375797-1, 1375797-4,  
1375798-1, 1375798-4



**Recommended PC Board Layout**  
for 1375797-2, 1375797-5,  
1375798-2, 1375798-5



**Recommended PC Board Layout**  
for 1375797-3, 1375797-6,  
1375798-3, 1375798-6

See Customer Drawing for  
Hole Geometry and Recommended Plating.

**Note:** All part numbers are RoHS compliant.

\* For RoHS exempt Tin-lead processes (including ENIG Plated PCB's)

\*\* for Silver Immersion processes or where a total lead free solution is desired

## PC/104, Solder

### Material and Finish

**Housing** — Glass filled thermoplastic, Black, 94V-0 rated

### Contacts


**Non-Stackthrough** — Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000100 [0.00254] matte tin on remainder, all over .000050 [0.00127] Nickel

**Screwlocks** — Steel, Clear Chromate over Zinc

### Non-Stackthrough, No Standoffs

**Part No. 1375963-3** (keyed)

**Part No. 1375963-4** (unkeyed)




### Recommended PC Board Layout

### Non-Stackthrough, 2 Standoffs

**Part No. 1375961-3** (keyed)


**Part No. 1375961-4** (unkeyed)



### Non-Stackthrough, 4 Standoffs

**Part No. 1375959-3** (keyed)

**Part No. 1375959-4** (unkeyed)



### Recommended PC Board Layout

**Note:** All part numbers are RoHS compliant.

## PC/104-Plus, Solder

### Material and Finish

**Housing** — Glass filled thermoplastic, Black, 94V-0 rated

### Contacts

**Non-Stackthrough** — Phosphor Bronze; plated .000015 [0.00038] min. Gold on mating receptacle end, .000100 [0.00254] matte tin on remainder, all over .000050 [0.00127] Nickel

**Screwlocks** — Steel, Clear Chromate over Zinc

### Non-Stackthrough, No Standoffs


**Part No. 1375967-4** (unkeyed)

**Part No. 1375967-5** (keyed-A1)

per PC/104-Plus specification

**Part No. 1375967-6** (keyed-D30)

per PC/104-Plus specification



### Non-Stackthrough, 2 Standoffs


**Part No. 1375965-4** (unkeyed)

**Part No. 1375965-5** (keyed-A1)

per PC/104-Plus specification

**Part No. 1375965-6** (keyed-D30)

per PC/104-Plus specification




**Note:** All part numbers are RoHS compliant.

## Accessories


### Shroud, PC/104-Plus Part No. 1375801-1

**Material** — PBT, Black




### Organizer, PC/104 Part Number 1445251-1

**Material** — Polyester, PBT, Black




### Kit Packaging Part Numbers


| Part Number | Component Part Number |           | Style   |
|-------------|-----------------------|-----------|---------|
|             | Connector Assembly    | Organizer |         |
| 1445441-3   | 1375795-3             | 1445251-1 | Keyed   |
| 1445441-4   | 1375795-4             | 1445251-1 | Unkeyed |
| 1445440-3   | 1375793-3             | 1445251-1 | Keyed   |
| 1445440-4   | 1375793-4             | 1445251-1 | Unkeyed |
| 1445439-3   | 1375791-3             | 1445251-1 | Keyed   |
| 1445439-4   | 1375791-4             | 1445251-1 | Unkeyed |



Part No. 1445441-3




Part No. 1445440-3



Part No. 1445439-3

**Note:** All part numbers are RoHS compliant.

## AMPMODU 50/50 Grid Connector System



**Produced under a Quality Management System certified to ISO 9001**


A copy of the certificate is available upon request.



## Board-to-Board Vertical Receptacles and Headers

### Product Facts

- Surface-mount products for parallel board-to-board applications, as well as right-angle board-to-board and cable-to-board applications
- High density .050 x .050 [1.27x1.27] centerline grid
- Three board-to-board stack heights: .250 [6.35], .320 [8.13] and .390 [9.91]
- Non-protrusive metallic holddowns
- Reliable dual beam receptacle contacts for redundant contact
- Duplex plated receptacle and post contacts; gold plated on mating areas, tin plated on tails
- Compatible with standard surface-mount processing (VPR and IR)
- Receptacle and header allow for drainage of processing fluids
- Tape and reel packaging available. Contact Tyco Electronics for details
- Polarized header and receptacle assemblies
- Sizes of 10, 20, 30, 40, 50, 60, 70, 80 and 100 positions
- Recognized under the Component Program of Underwriters Laboratories Inc., File No. E28476 
- Certified by Canadian Standards Association File No. LR7189 



AMPMODU 50/50 Grid Vertical Headers and Receptacles are designed for parallel board-to-board stacking in high density applications.

Right-angle board-to-board and cable-to-board applications are also possible, since the vertical receptacles also mate with non-latching right-angle headers (page 19) and the vertical headers also mate with non-latching cable connectors.

Available are double row, vertical shrouded headers and receptacles in sizes ranging from 10 through 100 positions (in 10 position increments).

Parallel board-to-board stack heights of .250 [6.35], .320 [8.13] and .390 [9.91] are achievable by selection of the appropriate header. The receptacle is the same for all three stack height headers.

Non-protrusive metallic holddowns are designed for use in .062 [1.57] or thicker




PC boards and allow surface mounting to both sides of the board. In addition to providing retention during processing, the holddowns are soldered during reflow and therefore provide long-term strain relief for the solder joints.

AMPMODU 50/50 Grid Vertical Headers and Receptacles are designed to be compatible with standard surface-mount processes; IR (infrared) and VPR (vapor phase reflow). The surface-mount connectors have been designed so that dimensioning, tolerances, referenced datums, holddown characteristics


and packaging methods result in a system that is compatible with robotic assembly.

The headers and receptacles feature polarization to prevent misalignment.


### Three Board Stack Heights



### Non-Protrusive Metallic Holddowns



## Board-to-Board Vertical Receptacles, Double Row, .050 x .050 [1.27 x 1.27] Centerline




### Material and Finish

**Housing**—Glass-filled thermoplastic, black, 94V-0 rated

**Contacts**—Copper alloy; duplex plated .000030 [0.00076] gold in mating area, .000150 [0.00381] tin on solder tail, with entire contact underplated .000050 [0.00127] nickel

**Holddown**—Copper alloy; plated .000150 [0.00381] tin over .000050 [0.00127] nickel



### Related Product Data

**Mating Headers** — pages 16, 19

**PC Board Layouts** — page 17

**Performance Specifications** — page 24

**Technical Documents** — page 24

**Product Specification** 108-1332

**Application Specification** 114-7010

**Packaging:** Tube or Tape and Reel

| No. of Pos. | Dimension A   | Receptacle Part Numbers |                |                             |
|-------------|---------------|-------------------------|----------------|-----------------------------|
|             |               | Tube                    | Tape and Reel* | No Hold Down w/Vacuum Cover |
| 10          | .266 [6.75]   | 5-104652-1              | 5-147384-1     | 5-147413-1                  |
| 20          | .516 [13.11]  | 5-104652-2              | 5-147384-2     | 5-147413-3                  |
| 30          | .766 [19.46]  | 5-104652-3              | 5-147384-3     | 5-147413-4                  |
| 40          | 1.016 [25.81] | 5-104652-4              | 5-147384-4     | —                           |
| 50          | 1.266 [32.16] | 5-104652-5              | 5-147384-5     | 5-147413-2                  |
| 60          | 1.516 [38.51] | 5-104652-6              | 5-147384-6     | —                           |
| 70          | 1.766 [44.86] | 5-104652-7              | 5-147384-7     | —                           |
| 80          | 2.016 [51.21] | 5-104652-8              | 5-147384-8     | —                           |
| 100         | 2.516 [63.91] | 6-104652-0              | 5-147384-9     | —                           |

\* Parts packaged in tape and reel have vacuum pick and place cover.  
See PC Board Layout on page 17.

**Note:** All part numbers are RoHS compliant.

## Board-to-Board Vertical Headers, Double Row, .050 x .050 [1.27 x 1.27] Centerline










For .250 [6.35] Mated Height



For .320 [8.13] Mated Height



For .390 [9.91] Mated Height



### Material and Finish

**Housing**—Glass-filled thermoplastic, black, 94V-0 rated

**Contacts**—Copper alloy; duplex plated .000030 [0.00076] gold in mating area, .000150 [0.00381] tin on solder tail, with entire contact underplated .000050 [0.00127] nickel

**Holddown**—Copper alloy; plated .000150 [0.00381] tin over .000050 [0.00127] nickel

### Related Product Data

**Mating Receptacles** — page 15, 21 (without latch only)

**PC Board Layouts** — page 17

**Performance Specifications** — page 24

### Technical Documents — page 24

**Product Specification** 108-1332

**Application Specification** 114-7010

**Packaging:** Tube or Tape and Reel

| No. of Pos. | Dimension A   | Header Part Numbers      |              |              |                          |              |                          |              |              |  |
|-------------|---------------|--------------------------|--------------|--------------|--------------------------|--------------|--------------------------|--------------|--------------|--|
|             |               | .250 [6.35] Mated Height |              |              | .320 [8.13] Mated Height |              | .390 [9.91] Mated Height |              |              |  |
|             |               | Tubes                    | Tape & Reel* |              | Tubes                    | Tape & Reel* | Tubes                    |              | Tape & Reel* |  |
|             |               |                          | Hold Down    | No Hold Down |                          |              | Hold Down                | No Hold Down |              |  |
| 10          | .372 [9.44]   | 5-104655-1               | 5-147381-1   | 5-147121-1   | 5-104656-1               | 5-147382-1   | 5-104693-1               | —            | 5-147383-1   |  |
| 20          | .622 [15.79]  | 5-104655-3               | 5-147381-2   | 5-147121-2   | 5-104656-2               | 5-147382-2   | 5-104693-2               | —            | 5-147383-2   |  |
| 30          | .872 [22.14]  | 5-104655-4               | 5-147381-3   | —            | 5-104656-3               | 5-147382-3   | 5-104693-3               | —            | 5-147383-3   |  |
| 40          | 1.122 [28.49] | 5-104655-5               | 5-147381-4   | —            | 5-104656-4               | 5-147382-4   | 5-104693-4               | —            | 5-147383-4   |  |
| 50          | 1.372 [34.84] | 5-104655-6               | 5-147381-5   | —            | 5-104656-5               | 5-147382-5   | 5-104693-5               | —            | 5-147383-5   |  |
| 60          | 1.622 [41.19] | 5-104655-7               | 5-147381-6   | —            | 5-104656-6               | 5-147382-6   | 5-104693-6               | —            | 5-147383-6   |  |
| 70          | 1.872 [47.54] | 5-104655-8               | 5-147381-7   | —            | 5-104656-7               | 5-147382-7   | 5-104693-7               | —            | 5-147383-7   |  |
| 80          | 2.122 [53.89] | 5-104655-9               | 5-147381-8   | —            | 5-104656-8               | 5-147382-8   | 5-104693-8               | —            | 5-147383-8   |  |
| 90          | 2.372 [60.24] | —                        | —            | —            | 5-104656-9               | —            | 5-104693-9               | —            | —            |  |
| 100         | 2.622 [66.59] | 6-104655-1               | 5-147381-9   | —            | 6-104656-0               | 5-147382-9   | 6-104693-0               | 5-147503-1   | 5-147383-9   |  |

\*Parts packaged in tape and reel have vacuum pick and place cover. See PC Board Layout on page 17.

**Note:** All part numbers are RoHS compliant.

## Recommended PC Board Layouts

## 2

Figure 1: Pattern layout for a 10-hole punch. The diagram shows a rectangular pattern with 10 vertical slots, each containing a crosshair. Dimensions are given in inches and millimeters. Key dimensions include: .029 [0.74] for the top slot width, .050 [1.27] for the slot spacing (B Spaces), .162 [4.11] for the total width, .182 [4.62] for the total height, .091 [2.31] for the bottom slot width, .061 [1.54] for the bottom slot spacing, and .047 [1.19] for the hole diameter (2 Plc.). A detail view of the hole shows a crosshair and a .010 [0.25] 4 Plc. dimension. The center of the pattern is marked with a circle and crosshair.


**Note:** Refer to Tyco Electronics Customer Drawings for additional PC board layout information and dimensional tolerances.

**Note:** All part numbers are RoHS compliant.

## Board-to-Board Right-Angle Headers

### Product Facts

- Surface-mount products for right-angle board-to-board and cable-to-board applications
- Double-row, right-angle shrouded headers
- High density .050 x .050 [1.27 x 1.27] centerline grid
- Latching and non-latching versions available
- Non-protrusive metallic holddowns
- Metallic tabs, when soldered to PC board pad, provide added mechanical support
- Duplex plated post contacts; gold plated on mating area, tin plated on tails
- Compatible with standard surface-mount processing (VPR and IR)
- Standoffs on header housings allow for drainage of processing fluids
- All headers are polarized
- Sizes of 10, 20, 30, 40, 50, 60, 70, 80 and 100 positions
- Recognized under the Component Program of Underwriters Laboratories Inc.,  File No. E28476
- Certified by Canadian Standards Association  File No. LR7189



AMPMODU 50/50 Grid Right-Angle Headers will accommodate a variety of high density packaging applications; right-angle board-to-board applications when mated with vertical receptacles (page 15) and right-angle cable-to-board applications when mated with cable connectors (page 21). The small .050 x .050 [1.27 x 1.27] centerline contact spacing allows efficient use of the PC board area.


Mechanical support of the headers to the PC board is provided by non-protrusive metallic holddowns designed for .062 [1.57] or thicker PC boards. These holddowns are of the same

design as those used in the vertical headers (page 16) and receptacles (page 15). There are also metallic tabs that are soldered to the surfaces of the PC board pads for added support.



AMPMODU 50/50 Grid Right-Angle Headers are available in double-row, in either latching or non-latching versions, and in sizes ranging from 10 through 100 positions (in 10 position increments). The latching version provides positive retention when mated with the latching cable connector (page 21). All headers feature polarization to help prevent misalignment during mating.

## Board-to-Board Right-Angle Headers, Double Row, .050 x .050 [1.27 x 1.27] Centerline

### Non-Latching Header



### Latching Header



### Material and Finish

**Housing** — Liquid crystal polymer, black, 94V-0 rated

**Contacts** — Copper alloy; duplex plated .000030 [0.00076] gold in mating area, .000150 [0.000381] tin on solder tail, with entire contact under-plated .000050 [0.00127] nickel

**Holddown** — Copper alloy; plated .0000150 [0.000381] tin over .000050 [0.00127] nickel

### Related Product Data

**Mating Receptacles** — page 15, 21


**Performance Specifications** — page 24

**Technical Documents** — page 24

**Product Specification** 108-1443

**Application Specification** 114-7010

**Packaging:** Tube



Recommended PC Board Layout

**Note:** Refer to Tyco Electronics Customer Drawings for additional PC board layout information and dimensional tolerances.


| No. of Pos. | Dimensions    |    |               |               | Header Part Numbers |              |
|-------------|---------------|----|---------------|---------------|---------------------|--------------|
|             | A             | B  | C             | D             | Latching            | Non-Latching |
| 10          | .630 [16.00]  | 9  | .225 [5.72]   | .550 [13.97]  | 5-104895-1          | 5-104894-1   |
| 20          | .880 [22.35]  | 19 | .475 [12.07]  | .800 [20.32]  | 5-104895-2          | 5-104894-2   |
| 30          | 1.130 [28.70] | 29 | .725 [18.42]  | 1.050 [26.67] | 5-104895-3          | 5-104894-3   |
| 40          | 1.380 [35.05] | 39 | .975 [24.77]  | 1.300 [33.02] | 5-104895-4          | 5-104894-4   |
| 50          | 1.630 [41.40] | 49 | 1.225 [31.12] | 1.550 [39.37] | 5-104895-5          | 5-104894-5   |
| 60          | 1.880 [47.75] | 59 | 1.475 [37.47] | 1.800 [45.72] | 5-104895-6          | 5-104894-6   |
| 70          | 2.130 [54.10] | 69 | 1.725 [43.82] | 2.050 [52.07] | 5-104895-7          | 5-104894-7   |
| 80          | 2.380 [60.45] | 79 | 1.975 [50.17] | 2.300 [58.42] | 5-104895-8          | 5-104894-8   |
| 100         | 2.880 [73.15] | 99 | 2.475 [62.87] | 2.800 [71.12] | 6-104895-0          | 6-104894-0   |

**Note:** All part numbers are RoHS compliant.

## Cable-to-Board Connectors

### Product Facts

- Double-row receptacle connectors provide cable-to-board connection capabilities for vertical headers (non-latching) and right-angle headers (latching and non-latching)
- IDC (Insulation Displacement Crimp) mass termination of solid or stranded round conductor .050 [1.27] centerline ribbon cable with PVC or polyethylene insulation
- Accommodates ribbon cable conductor sizes of 28 AWG [0.08-0.09 mm<sup>2</sup>] and 30 AWG [0.05 mm<sup>2</sup>] and insulation diameters up to .036 [0.91] maximum
- Reliable single beam receptacle contact design
- Duplex plated receptacle contacts; gold plated in mating area, tin in termination area
- Terminating covers (sold separately) provide both strain relief and protection to the termination area
- Sizes of 10, 20, 30, 40, 50, 60, 70, 80 and 100 positions
- Connectors available with or without metal latch
- Connectors without latches are polarized to help prevent mismatching
- Recognized under the Component Program of Underwriters Laboratories Inc.,  File No. E28476
- Certified by Canadian Standards Association  File No. LR7189



These double-row cable connectors, with a .050 x .050 [1.27 x 1.27] centerline contact spacing, provide cable-to-board connection capabilities for the AMPMODU 50/50 Grid Connector System. Cable connectors without a latch will mate with the vertical headers (page 16), while cable connectors with or without a latch can be used to mate with the right-angle headers (page 19).


The cable connectors feature reliable single-beam IDC (insulation displacement crimp) contacts which are duplex plated with .00030 [0.00076] gold. These contacts can be mass terminated to either solid or

stranded round conductor ribbon cable with conductor sizes of 28 AWG [0.08-0.09 mm<sup>2</sup>] and 30 AWG [0.05 mm<sup>2</sup>] and a maximum insulation diameter of .036 [0.91]. During termination, the terminating covers, which must be purchased separately, assist in guiding the wire into the IDC contacts, then provide strain relief when fully seated. Actual termination is accomplished with the Tyco Electronics manual tooling shown on page 23.

The latching version of the cable connector is equipped with a metal latch which provides positive retention of the receptacle cable connector when mated with a surface-

mounted right-angle header. The cable connector without a metal latch features polarization to help prevent mismatching. All connectors are available in sizes ranging from 10 through 100 positions (in 10 position increments).

## Cable-to-Board Receptacle Connectors, Double Row, .050 x .050 [1.27 x 1.27] Centerline



### Material and Finish

**Housing** — Thermoplastic, black, 94V-0 rated

**Latch** — Stainless steel

**Contacts** — Phosphor bronze; duplex plated .000030 [0.00076] minimum gold in mating area, .000150 [0.00381] minimum tin on solder tail, with entire contact underplated .000050 [0.00127] minimum nickel

### Related Product Data

**Mating Headers** — page 16, 19 (latching)

**Terminating Covers (Must be Purchased Separately, 2 Required per Connector)** — page 22

**Termination Tooling** — page 23





**Performance Specifications** — page 24

### Technical Documents — page 24

**Product Specification** 108-1443

**Application Specification**  
408-9817, 408-9909

**Packaging:** Tube



| No. of Pos. | Dimensions    |    |               |               | Receptacle Part Numbers |               |
|-------------|---------------|----|---------------|---------------|-------------------------|---------------|
|             | A             | B  | C             | D             | With Latch              | Without Latch |
| 10          | .578 [14.68]  | 4  | .200 [5.08]   | .266 [6.76]   | 5-104892-1              | 5-104893-1    |
| 20          | .828 [21.03]  | 9  | .450 [11.43]  | .516 [13.11]  | 5-104892-2              | 5-104893-2    |
| 30          | 1.078 [27.38] | 14 | .700 [17.78]  | .766 [19.46]  | 5-104892-3              | 5-104893-3    |
| 40          | 1.328 [33.73] | 19 | .950 [24.13]  | 1.016 [25.81] | 5-104892-4              | 5-104893-4    |
| 50          | 1.578 [40.08] | 24 | 1.200 [30.48] | 1.266 [32.16] | 5-104892-5              | 5-104893-5    |
| 60          | 1.828 [46.43] | 29 | 1.450 [36.83] | 1.516 [38.51] | 5-104892-6              | 5-104893-6    |
| 70          | 2.078 [52.78] | 34 | 1.700 [43.18] | 1.766 [44.86] | 5-104892-7              | 5-104893-7    |
| 80          | 2.328 [59.13] | 39 | 1.950 [49.53] | 2.016 [51.21] | 5-104892-8              | 5-104893-8    |
| 100         | 2.828 [71.83] | 49 | 2.450 [62.23] | 2.516 [63.91] | 6-104892-0              | 6-104893-0    |

**Note:** All part numbers are RoHS compliant.

## Terminating Covers for Cable Connectors



### Material

Glass-filled thermoplastic,  
black, 94V-0 rated

### Related Product Data

**Connectors used with Covers** —  
page 21




**Termination Tooling** — page 23

**Technical Documents** — page 24

**Product Specification** 108-1443

**Application Specification**  
408-9817, 408-9909

**Packaging:** Plastic bag



| No. of Pos. | Dimension A   | Terminator Cover Part Numbers |
|-------------|---------------|-------------------------------|
| 10          | .565 [14.35]  | 104891-1                      |
| 20          | .815 [20.70]  | 104891-2                      |
| 30          | 1.065 [27.05] | 104891-3                      |
| 40          | 1.315 [33.82] | 104891-4                      |
| 50          | 1.565 [39.75] | 104891-5                      |
| 60          | 1.815 [46.10] | 104891-6                      |
| 70          | 2.065 [52.45] | 104891-7                      |
| 80          | 2.315 [58.80] | 104891-8                      |
| 100         | 2.815 [71.50] | 1-104891-0                    |

**Note:** Terminating covers must be purchased separately, two are required for each cable connector.

**Note:** All part numbers are RoHS compliant.

## Application Tooling for Cable Connectors

The Manual Miniature Application Frame Assembly 91295-1, equipped with a Cover Closing Kit 543518-1, is used for the IDC termination of ribbon cable to the cable connectors shown on page 21.


Prior to termination, the covers must be partially assembled onto a connector housing, the cable inserted between the covers and contacts and the covers preclosed by hand, clamping the cable in place.

In the Manual Miniature Application Frame Assembly, the covers are fully seated to complete the mass termination and provide strain relief for the completed connection.

For tooling information, call Technical Support Center **1-800-522-6752**.



**Manual Miniature Application Frame Assembly 91295-1  
with Cover Closing Kit 543518-1**



**Note:** Refer to Tyco Electronics Instruction Sheets 408-9817 (Frame Assembly 91295-1) and 408-9909 (Cover Closing Kit 543518-1) for complete termination/tooling information.

**Note:** All part numbers are RoHS compliant.

## Performance Specifications

### Board-to-Board Connectors, Vertical and Right-Angle

**Mating Force:** 6.4 oz (1.78 N) max. per contact

**Unmating Force:** 1.0 oz [0.28 N] min. per contact

**Durability:** Tested to 200 cycles min.

**Current Rating:** (30°C T rise): .5 ampere per contact

**Operating Temperature Range:** -65°C to +105°C

**Termination Resistance:** 16 milliohms max. (initial)

**Insulation Resistance:** 5000 megohms min. (initial)

**Dielectric Withstanding Voltage:** 300 VAC

### Cable-to-Board Connectors

**Mating Force:** 6.4 oz (1.78 N) max. per contact

**Unmating Force Without Latch:** .5 oz [0.14 N] min. per contact

**Durability:** Tested to 200 cycles min.

**Current Rating:** (10°C T rise): .5 ampere per contact

**Operating Temperature Range:** -65°C to +105°C

**Termination Resistance:** 25 milliohms max. (initial and final)

**Insulation Resistance:** 5000 megohms min. (initial)

**Dielectric Withstanding Voltage:** 300 VAC

## Technical Documents

Various technical documents are available for your use:

**Product Specifications** describe technical performance characteristics and verification tests. They are intended for the Design, Component and Quality Engineer.

108-1332 AMPMODU 50/50 Grid Vertical Board-to-Board Connectors

108-1443 AMPMODU 50/50 Grid Right-Angle Board-to-Board and Cable Connectors

**Application Specifications** describe requirements for using the product in its intended application and/or crimping information. They are intended for the Packaging and Design Engineer and the Machine Setup Person.

114-7010 AMPMODU 50/50 Grid Connector System

**Instruction Sheets** provide instructions for assembling or applying the product. They are intended for the Manufacturing Assembler or Operator.

408-9817 Manual Miniature Application Frame Assembly 91295-1

408-9909 Cover Closing Kit 543518-1

**Note:** All part numbers are RoHS compliant.