

	1	2	3	4	5	6	7													
A	RoHS compliant							A												
B								B												
C								C												
D								D												
E								E												
F								F												
							Notes Material : AL 6063 Finished : Black Anodized <table><tr><th>Option</th><th>L</th><th>Thermal resistance(K/W)</th></tr><tr><td>V2000W</td><td>25</td><td>6.5</td></tr><tr><td>V2000X</td><td>38</td><td>5</td></tr><tr><td>V2000Y</td><td>50</td><td>4</td></tr></table>	Option	L	Thermal resistance(K/W)	V2000W	25	6.5	V2000X	38	5	V2000Y	50	4	
Option	L	Thermal resistance(K/W)																		
V2000W	25	6.5																		
V2000X	38	5																		
V2000Y	50	4																		
G	Scale		FREE			Date	Name	Customer-No.	G											
	TOLERANCE					Drawn	11.08.2009	Dean												
						Approved	10.03.2010	Andy												
	UNIT		±0.2						ASSMANN WSW-No. V2000x											
H	DIM		TOL	②	Modify drawing layout	10.03.2010	Dean	Drawing-No.	H											
	X.°		±X°	①	Drawn	11.08.2009	Dean	ASS 0869 HS												
	X.X°		±X°					rev02												
	Angle		TOL	Id.	Modification	Date	Name	Replace												
									Sheet											
	1	2	3	4	5	6	7													