

PRODUCT DATASHEET Lisa2 series

last update 23/11/2011



18 degrees

Available

89 %



Ordering number FP11086_LISA2-RS-CLIP

Family Lisa2 Type Lens LED **LUXEON Rebel** Color Black Diameter 9.9 mm Height 6.6 mm Style Round **PMMA** Optic Material

Fastening Glue, clips Status Ready

Holder Material



Ordering number FP11072_LISA2-M-CLIP

PC

Family Lisa2 FWHM 25 degrees
Type Lens Efficiency 90 %
LED LUXEON Rebel cd/lm Color Black Gerber File Available

FWHM

cd/lm

Efficiency

Gerber File

Diameter 9.9 mm
Height 6.6 mm
Style Round
Optic Material PMMA
Holder Material PC
Fastening Glue, clips
Status Ready



Ordering number FP11073_LISA2-W-CLIP

Family Lisa2 FWHM 34 degrees
Type Lens Efficiency 89 %
LED LUXEON Rebel cd/lm Color Black Gerber File Available

Diameter 9.9 mm
Height 6.6 mm
Style Round
Optic Material PMMA
Holder Material PC
Fastening Glue, clips
Status Ready



Ordering number FP11122_LISA2-O-CLIP

Family Lisa2 FWHM 48+20 degrees
Type Lens Efficiency 85 %
LED LUXEON Rebel cd/lm -

Gerber File

Available

Color Black
Diameter 9.9 mm
Height 6.6 mm
Style Round
Optic Material PMMA
Holder Material PC

Fastening Glue, clips Status Ready



PRODUCT DATASHEET Lisa2 series

last update 23/11/2011

2 series





Ordering number FP11858_LISA2-O-90-CLIP

Family Lisa2 Type Lens LED **LUXEON Rebel** Color Black Diameter 9.9 mm Height 6.6 mm Style Round **PMMA** Optic Material PC Holder Material Glue, clips Fastening Status Ready

FWHM 48+20 degrees Efficiency 81 % cd/lm -

Gerber File Available



Ordering number FP11952_LISA2-WWW-CLIP

Family Lisa2 Type Lens LED **LUXEON Rebel** Color Black Diameter 9.9 mm Height 6.6 mm Round Style **PMMA** Optic Material PC Holder Material Fastening Glue, clips Status Ready

FWHM 73.5 degrees
Efficiency 76 %
cd/lm Gerber File Available

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.



PRODUCT DATASHEET Lisa2 series



last update 23/11/2011

GENERAL INFORMATION

- Product series especially designed & optimized for LUXEON Rebel series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance (105 degrees of Celcius / 220 degrees of Fahrenheit). Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf

- Optic holder molded by high quality PC material (120 dergees of Celcius / 248 degrees of Fahrenheit).
- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

