

Cable kit , Riser Cards & I/O modules

PCM-10586-9562E


Installation Wiring Kit for PCM-9562

Part No.	Cable Description	Quantity	PCM-9562 Connector	Terminating Connector
1700160160	Audio cable	1	CN4	Cable 16-Pin (2.0 mm) Audio 16 cm
1700002142	Ethernet cable	2	CN10, CN12	Ethernet Cable IDC10P 2.0 mm/RJ45 15cm
1700260250	LPT port cable	1	CN15	Cable 25 cm 25P to 26P ASS'Y LPT Port 2.0 mm
1700019109	COM 4/5 cable	1	CN42	A Cable 2 x 5P-2.0/D-SUB(M) 9P+D-SUB(M) 9P 25 cm
1703100260	USB Port cable	4	CN20, CN21, CN28, CN29	Wire 10P 26 cm 2.0 mm For USB 2 PORT
1703060191	PS2 KB/MS Cable	1	CN25	Cable 6P-2.0 mm Housing/6P (PS/2)/6P (K/B) 19 cm
1700008941	SATA Cable	3	CN32, CN33, CN34	Cable 7P/7P SATA L=30cm Lock
1700001296	VGA cable	1	CN8	VGA Cable D-SUB 3 x 5P(F)/2x 8P-2.0 15 cm
1700100250	COM1/2/3	3	CN39, CN40, CN41	F Cable IDE#2 10P-2.0/D-SUB 9P(M) 25 cm
1703150102	SATA Power Cable	3	None	SATA Power cable L= 10 cm
170304015K	AT power cable	1	CN5	A Cable 2 x 2P-4.2/B4P-5.08 x 2 15 cm

Ordering Information

PCM-10586-9562E	PCM-9562 cable kit
-----------------	--------------------

PCI Riser Card



PCM-110


1-Slot PCI Riser Card for 5.25" Biscuit SBCs

CE FCC

Fits in PCM-95XX series
Provides bracket to secure Biscuit SBCs
Size: 103.7 x 56 mm (4.08" x 2.2")

Ordering Information

P/N	Description
PCM-110-00A3E	1-slot PCI riser Card for Biscuit SBCs



PCM-261

LVDS/TTL to DVI Module

Supports 18 and 24-bit LVDS to DVI
Supports 18 or 24-bit TTL LCD to DVI (optional)

Specifications

General	
Chipset	Silicon Image Sil 164; NS DS90CF364
LCD Connector	Hirose Output Connector; DVI
Mechanical and Environmental	
Dimensions (L x W)	72 x 62 mm
Weight	0.029 kg (0.064 lb)
Operating Temperature	0 ~ 60° C (32 ~ 140° F)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
Power	
Power Supply Voltage	+5 V, ±5%

Ordering Information

Standard	
PCM-261L-A0A1E	24-bit LVDS to DVI Module
PCM-261L-B0A1E	18-bit LVDS to DVI Module
PCM-261T-A0A1E	24-bit TTL to DVI Module

Packing List

1 x User manual
1 x PCM-261 board