PX130&PX140

DESCRIPTION
- Industrial protective glove.
- Synthetic coating on a synthetic textile liner.
- Available in grey (PX130) or in white (PX140).
- 5 available sizes : 6, 7, 8, 9 and 10.
- Single pair packed, trade unit 12 pairs, 240 pairs in a transit case.

CHARACTERISTICS
- Nylon textile liner made with a seamless non-stop process.
- Fine and stretchable stitches.
- Lightweight ergonomic design.
- Flat dipped polyurethane palm fit coating.
- Latex knit wrist to ensure snug fit.

PERFORMANCES
- Excellent adaptability owing to its extensibility.
- Excellent comfort and dexterity.
- Ventilated back ensures that the hand can breathe naturally.
- Good abrasion resistance.
- In compliance with the standards EN420 (General Requirements) and EN388 (Mechanical Hazards) by the notified body CTC.

APPLICATIONS
- For general handlings where comfort is required.
- Ideal for use in automotive industry, painting, print shops, general maintenance,small parts handling.

LIMITATIONS
- Do not use for handling liquids and pointed objects.
- Do not use with a rotating machine in which glove may get caught.
- Limited protection at the wrist.

This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.

CE

EN 420

EN 420
- **5** Dexterity

4131

EN 388
Mechanical hazards

EN 388
- **4** Abrasion
- **1** Cut
- **3** Tear
- **1** Puncture

Order codes

Sizes	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)
PX130	M10254	M10255	M10256	M10257	M10258
PX140	M10249	M10250	M10251	M10252	M10253

www.marigold-industrial.com • www.marigold-industrial.com • www.marigold-industrial.com • www.marigold-industrial.com • www.marigold-industrial.com

N° MI/TDS/PX130&140EN/FT/5 - 20/08

Marigold Industrial

AFAQ ISO 9001 VERSION 2000

IQNet CERTIFIED QUALITY SYSTEM