

TECHNICAL DATA SHEET

K-Type™ markers

MATERIAL DESCRIPTION: Extruded plasticized polyvinyl chloride (PPVC) profiles and carriers.

USE: Identification of wire bundles, cables, pipes and conduits using individual characters. The characters slide on to a plastic carrier which is then attached using cable ties. K-Type™ markers are ideal for identification after cable, pipe etc installation or where identification retrofit is anticipated.

CARRIER SIZES: Two carrier sizes available with 7 and 18 character capacity.

COLORS/MARKING: Yellow markers with black characters (A - Z, 0 - 9 and symbols).

Color coded 0 - 9 characters available.

SERVICE TEMPERATURE: -45°C to +70°C (-50°F to +158°F).

CHEMICAL RESISTANCE of MARK and MATERIAL: 24 hours immersion, 25 rubs with a cloth

FLUID	TEST RESULT
Aircraft fuel	Excellent
Propan-2-ol	Excellent
Gasoline	Excellent
50% NaCl	Excellent
Diesel fuel	Excellent
Diala oil B	Excellent
Diethyl ether	Excellent
NH ₄ OH	Excellent
White spirit	Excellent
Tap water	Excellent
Sea water	Excellent

FLUID	TEST RESULT
10% detergent solution	Excellent
Kilfrost™	Excellent
Silicone hydraulic fluid	Excellent
Aeroshell™ 41 hydraulic Fluid	Good
Sullage fluid	Good
Gas turbine oil 98	Good
20% NaOH	Good
HCl	Poor
Acetone	Poor
Skydrol™ 500 B4	Poor

www.idento.com

Document number: TTDS-025 Date: September 2001

Issue: 1 Pages: 1

Business locations:

N America: + 1 650 361 3860 (West Coast)
 Germany: + 49 (0) 6074 89080
 UK: + 44 (0) 1495 244000 (Labels)
 Japan: + 81 (0) 44 900 5102

N America: + 1 401 751 6505 (East Coast)
 France: + 33 (0) 476 099696
 UK: + 44 (0) 1793 528171 (Other products)
 Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.