




NOTES:

- MATERIAL:
 - HOUSING: HIGH TEMP THERMO PLASTIC
 - CONTACT: COPPER ALLOY
 - FITTING NAIL: COPPER ALLOY
 - ACTUATOR: HIGH TEMP THERMO PLASTIC
- FINISH:

UNDER PLATING: 50u" MIN. NICKEL OVERALL

CONTACT AREA AND SOLDER TAIL: GOLD FLASH OVERALL

FITTING NAIL:

UNDER PLATING: 50u" MIN. NICKEL OVERALL

GOLD FLASH OVERALL
- REFLOW SOLDER CAPABLE TO 260°C PEAK TEMP. FOR 10 SECONDS MAX.
- THE PACKING DRAWING PLS REFER TO GS-14-1332.
- THE SPEC. PLS REFER TO GS-12-580.

6. PART NUMBER DESCRIPTION:

10089711-XXX 0 1 0 LF

NO OF CONTACTS(CKT)	LEAD FREE	COLOR	
		X: HOUSING	ACTUATOR
PACKING	0: TAPE & REEL	PLATING	
		1: GOLD FLASH OVERALL	

CKT	DIM.A	DIM.B	DIM.C	DIM. D
010	4.5	10.25	11.5	5.65
012	5.5	11.25	12.5	6.65
014	6.5	12.25	13.5	7.65
050	24.5	30.25	31.5	25.65

mat'l. code				tolerances unless otherwise specified				CUSTOMER COPY		 www.fciconnect.com		
ltr	ecn no	dr	date	linear	.X ± 0.25			projection 	title 0.5mm ZIF FPC CONN. SMT R/A B/C TYPE			
A	T08-1182	WL	11/06/08		.XX ± 0.15							
B	T08-1196	WL	12/10/08		.XXX ± 0.10							
C	T09-1005	WL	01/20/09	angles	0° ± 2°				product family FPC size dwg no A4 10089711			
D	T09-1054	WL	04/21/09	dr	LEIF SHEN	08-06-18						
E	T09-1065	WL	05/05/09	enrg	DENNIS GOH	08-08-08						
				chr	DENNIS GOH	08-08-08	scale					
				appd	JOEY NG	08-08-08						
sheet index	revision sheet	E 1										