

TLSD-12-D-02.00-01-L-RN1

## TLSD SERIES

# COST EFFECTIVE IDC SOCKET CABLES

| TYPE                                                                                                                                                                                       | NO. PINS PER ROW                                                                  | END OPTION                    | LENGTH                                                                                                                          | 01                                                  | PLATING OPTION                                                                                                | OTHER OPTION                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                            | <b>-05, -08, -10, -12, -13, -15, -17, -20, -22, -25</b><br>(Call for other sizes) |                               | <b>-"XX.XX"</b><br>= Assembled Length<br>                                                                                       |                                                     | <b>-L</b><br>= 10µ" (0,25 µm)<br>Gold on contact area                                                         |                                                                                                               |
|                                                                                                                                                                                            | <b>-S</b><br>= Single End<br>                                                     | <b>-D</b><br>= Double End<br> |                                                                                                                                 | <b>-N</b><br>= Notch Polarization<br>               | <b>-RW</b><br>= Reverse Wiring<br><br>Black wire opposite position #1.                                        |                                                                                                               |
|                                                                                                                                                                                            | <b>TLSD</b><br>= Socket Strip<br>                                                 |                               | <br><b>RUGGEDIZED</b><br>by SAMTEC<br>• Strain relief<br>• Optional polarization and polarizing key                             |                                                     | <b>-SR</b><br>= Strain Relief<br>                                                                             | <b>-RN1</b><br>= Reverse Notch End 1<br><br>Reverse notch option on end 1 only. Not Available with -R option. |
|                                                                                                                                                                                            |                                                                                   |                               | <b>-P "XX"</b><br>= Position Polarization<br><br>Specify "XX" as position number. Same position will be polarized on both ends. |                                                     | <b>-RN2</b><br>= Reverse Notch End 2<br><br>Reverse notch option on end 2 only. Not Available with -R option. |                                                                                                               |
| <b>-B "XX"</b><br>= Breakout<br>Specify "XX" as number of conductors to be broken out.<br><br>Breakout starts with Number 1 lead indicated by brown wire or red stripe. Shown on top side. | <b>-D "XX"</b><br>= Daisy Chain<br>                                               | <b>-R</b><br>= Reversed<br>   | <b>-M</b><br>= Middle Reverse<br><br>Requires -DXX                                                                              | <b>-O</b><br>= Outside Reverse<br><br>Requires -DXX |                                                                                                               |                                                                                                               |

*Due to technical progress, all designs, specifications and components are subject to change without notice*

**WWW.SAMTEC.COM**

**SAMTEC USA** • Tel: 1-800-SAMTEC-9 or 812-944-6733    **SAMTEC NORTHERN CALIFORNIA** • Tel: 408-395-5900    **SAMTEC SOUTHERN CALIFORNIA** • Tel: 1-800-726-8329  
**SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA** • Tel: (+55 31) 3786 3227    **SAMTEC UNITED KINGDOM** • Tel: 44 1236 739292    **SAMTEC GERMANY** • Tel: 49 (0) 89 / 89460-0  
**SAMTEC FRANCE** • Tel: 33 01 60 95 06 60    **SAMTEC ITALY** • Tel: 39 039 6890337    **SAMTEC NORDIC/BALTIC** • Tel: +46-84477280    **SAMTEC BENELUX** • Tel: 44 1236 739292  
**SAMTEC ISRAEL** • Tel: 972-3-7526060    **SAMTEC INDIA** • Tel: +91-80-3272 1612    **SAMTEC ASIA PACIFIC** • Tel: 65 6745-5955    **SAMTEC JAPAN** • Tel: 045-475-1385    **SAMTEC CHINA** • Tel: 86-21-6083 3766  
**SAMTEC TAIWAN** • Tel: 886-2-2735-6109    **SAMTEC HONG KONG** • Tel: 852-26904858    **SAMTEC KOREA** • Tel: 82-31-717-5685    **SAMTEC ANZ** • Tel: 613 9580 0683