



Last Update: 6-9-10 **Ref.** #: MS-100917

Dimensions: mm (in.)










P.C. Mounting



POS.1	POS.2
7	#
ON	ON
2-3	2-1
2 Comm.	2 Comm.

Switch Function

Electrical Specifications:

- Contact resistance: 10mΩ max. initial @ 2-4VDC 100mA
- Insulation resistance: 1,000M Ω min.
- Dieletric strength: 1,000 V RMS@sea level
- Rating: 2A / 250VAC; 5A / 120VAC or 28VDC

Mechanical Specifications:

- Mechanical life: 30,000 make-and-break cycles
- Operating temperature: -30°C to 85°C

Soldering Process:

- Manual Soldering: Use soldering iron of 30 watts, controlled at 350°C approximately 5 sec. while applying solder.
- Wave Soldering: Recommended Soldering Temperature: 260±5°C Duration of Solder Immersion: 5±1sec. (PCB is 1.6mm in thickness)

Noto:

• RoHS Compliant by Exemption

Sealed Miniature Toggle Switch 108-1AS1T2219-EVX



Available from Mouser Electronics

www.mouser.com

1-800-346-6873

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mountain Switch: 108-1AS1T2219-EVX