

# GSM | GPRS

## GL865-QUAD Embedded



- Ultra Compact
- Telit Unified AT Command Set
- eCall
- RUN AT Commands Remotely
- SMD Component
- LCC Package
- Quad Band GPRS
- GPRS Class 10
- RoHS Compliant
- SIM Access Profile
- PYTHON\* Script Interpreter
- Embedded FTP and SMTP Client
- Extended Temperature Range -40° to +85° C
- Extended RF Sensitivity
- Serial Port Multiplexer (3GPP 27.010)
- Embedded TCP/IP Stack

The new GL865-QUAD product is the new representative of Telit's GSM/GPRS LCC surface mounted family. It features the same performances of its companion module GL865-DUAL but in all GSM bands. GL865-QUAD is a quad band GSM/GPRS device in LCC castellation packaging with extremely low power consumption, extended temperature range and compact profile.

The GL865-QUAD modules with LCC castellation package technology are surface mount package devices, which use metalized pads on the sides of the package. This kind of packaging is ideally suited for uncomplicated and low-cost applications based on Four-Layer PCB (printed circuit board). Moreover, with the option for manual soldering and removal, it can also serve niche applications with a low volume production. Since connectors are eliminated, the solution cost is significantly reduced compared to conventional mounting. Additional features such as integrated TCP/IP protocol stack, serial multiplexer and Remote AT commands extend the functionality of the application at no additional cost.

The GL865-QUAD makes it possible to run the customer's application inside the module by means its embedded Python Script Interpreter, thus making it the smallest, complete SMT platform for m2m solutions.

The GL865-QUAD is also compliant with eCall EU Directive.

The eCall project is sponsored by the European Commission and it's based on the EU directive E112. It is intended to adopt a black box device installed inside vehicles, wirelessly connected to Emergency Centers. In case of an emergency such as an accident or by user intervention, the black box and its sensors will send information about the event to such centers, with the chance to establish a voice call for safety measures.

All Telit modules, support Over-the-Air firmware update by means Premium FOTA Management. By embedding Red Bend Software vRapid Mobile® agent, a proven and battle-tested technology powering hundreds of millions of cellular handsets world-wide Telit is able to update its products by transmitting only a delta file, which represents the difference between one firmware version and another.

As a part of Telit's corporate policy of environmental protection, all products comply to the RoHS (Restriction of Hazardous Substances) directive of the European Union (EU Directive 2002/95/EG).

### Product features

- LCC Castellation form factor
- Quad-band GSM/GPRS 850/900/1800/1900 MHz
- GSM/GPRS protocol stack 3GPP Release 4 compliant
- Control via AT commands according to 3GPP TS 27.005, 27.007 and Telit custom AT commands
- Serial port multiplexer 3GPP TS 27.010
- SIM access profile
- TCP/IP stack access via AT commands



**Making machines talk.®**

# GL 865-QUAD

Embedded



actual size

## Product features

- SIM application toolkit 3GPP TS 51.014
- Dimensions: 24.4 x 24.4 x 2.7 mm
- Weight: 2.8 grams
- DARP/SAIC support
- Output power
  - Class 4 (2W) @ 850/900 MHz
  - Class 1 (1W) @ 1800/1900 MHz
- Supply voltage range: 3.22 - 4.5 VDC (3.8 V DC recommended)
- Power consumption (typical values)
  - Power off: < 5 uA
  - Idle (registered, power saving): 1.5 mA @ DRX=9
  - Dedicated mode: 230 mA @ max power level
  - GPRS cl.10: 360 mA @ max power level
- Sensitivity:
  - 108 dBm (typ.) @ 850/900 MHz
  - 107 dBm (typ.) @ 1800/1900 MHz
- Extended temperature range
  - 40°C to +85°C (operational)
  - 40°C to +85°C (storage temperature)

## Interfaces

- Interfaces
- 8 I/O ports maximum
- Analog audio (balanced), digital audio
- 2 A/D plus 1 D/A converter
- Buzzer output
- ITU-T V.24 serial link through CMOS UART:
  - Baud rate from 300 to 115,200 bps
  - Autobauding up to 115,200 bps

## Audio

- Telephony, emergency call
- Half rate, full rate, enhanced full rate and adaptive multi rate voice codecs (HR, FR, EFR, AMR)
- Superior echo cancellation & noise reduction
- Multiple audio profiles pre-programmed and fully configurable by mean AT commands
- DTMF

## Approvals

- Fully type approved conforming R&TTE directive
- CE, GCF

## SMS

- Point-to-point mobile originated and mobile terminated SMS
- Concatenated SMS supported
- SMS cell broadcast
- Text and PDU mode
- SMS over GPRS

## Circuit switched data transmission

- Asynchronous non-transparent CSD up to 9.6 kbps
- V.110

## GPRS data

- GPRS class 10
- Mobile station class B
- Coding scheme 1 to 4
- PBCCH support
- GERAN Feature Package 1 support (NACC, Extended TBF)

## GSM supplementary

- Call forwarding
- Call barring
- Call waiting & call hold
- Advice of charge
- Calling line identification presentation (CLIP)
- Calling line identification restriction (CLIR)
- Unstructured supplementary services mobile originated data (USSD)
- Closed user group

## Additional features

- SIM phonebook
- Fixed dialing number (FDN)
- Real-time clock
- Alarm management
- Network LED support
- IRA, GSM, 8859-1 and UCS2 character set
- Jamming detection
- Embedded TCP/IP stack, including TCP, IP, UDP, SMTP, ICMP and FTP protocols
- PFM (Premium FOTA Management) Over-The-Air Update service
- Remote AT commands
- Event monitor

## Python\* application resources

- Python\* script interpreter (module takes the application code directly in the Python\* language)
- Memory: 1.9 MB of NV memory for the user scripts and 1 MB RAM for the Python\* engine usage



## Telit's EASY features

- EASY SCAN® automatic scan over GSM frequencies (also without SIM card)

## Order No.

Please contact your Telit representative for order codes and all further information



Telit Communications S.p.A.  
Via Stazione di Prosecco, 5/B  
I-34010 Sgonico (Trieste), Italy  
Tel +39 040 4192 200  
Fax +39 040 4192 289  
E-Mail: EMEA@telit.com

Telit Wireless Solutions Inc.  
3131 RDU Center Drive, Suite 135  
Morrisville, NC 27560, USA  
Tel +1 888 846 9773 or +1 919 439 7977  
Fax +1 888 846 9774 or +1 919 840 0337  
E-Mail: NORTHAMERICA@telit.com

Telit Wireless Solutions Inc.  
Rua Cunha Gago, 700 - cj 81, Pinheiros  
São Paulo - SP, 05421001, Brazil  
Tel +55 11 3031 5051  
Fax +55 11 3031 5051  
E-Mail: LATINAMERICA@telit.com

Telit Wireless Solutions Co., Ltd.  
12th Fl., Shinyoung Securities Bld.  
34-12, Yeouido-dong, Yeongdeungpo-gu  
Seoul, 150-884, Korea  
Tel. +82 2 368 4600  
Fax +82 2 368 4606  
E-Mail: APAC@telit.com

[www.telit.com](http://www.telit.com)

[www.telit.com/ebook](http://www.telit.com/ebook)

[www.telit.com/techforum](http://www.telit.com/techforum)

[www.telit.com/facebook](http://www.telit.com/facebook)

[www.telit.com/twitter](http://www.telit.com/twitter)

Distributed by:

Copyright © 2012, Telit - Subject to changes in technology, design and availability

\* Copyright © 1991-1995 by Stichting Mathematisch Centrum, Amsterdam, The Netherlands; All Rights Reserved.  
Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved.  
Copyright © 2001-2010 Python Software Foundation; All Rights Reserved.  
All Rights Reserved are retained in Python.