Product Details for 6605711 -1

6605711 -1

Active

Integrated Magnetic, Stacked (Mag45™) and Power over Ethernet (PoE)

RoHS Compliant (Statement of Compliance)

Product Highlights:

- 10/100BASE -T Ethernet Application
- Component Type = Single Port
- Magnetic Circuit = 714ET
- Turns Ratio = 1:1
- 1 x 1 Jack Configuration

View all Features

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- 1X1 MAG45(TM) MODULAR JACK, 7N2ET INDUSTRIAL TEMP SC... (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- Mag45* Modular Jacks With Integrated Magnetics (PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

List all Documents

Additional Information:

- Product Line Information

Related Products:

- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Signal Routing Type = NIC
- PCB Mount Style = Thru Hole
- Shielded = Yes
- Shield Material = Brass

Mechanical Attachment:

- Jack Configuration = 1 x 1
- Impedance (?) = 100

Electrical Characteristics:

- Component Type = Single Port
- Turns Ratio = 1:1

Termination Related Features:

- Bottom Panel Ground Tab = Without

Body Related Features:

- LED = With
- Shield Panel Ground Tabs = With
- Latch Orientation = Inverted - Latch Up
- Bottom Shield = Without
- Shield Plating = Semi -Bright Nickel (Pre -plated)

Housing Related Features:

- Housing Flammability Rating = UL 94V -0
- Housing Material = Thermoplastic

Configuration Related Features:

- Magnetic Circuit = 714ET
- Decoupling Capacitor = Without
- Rear PCB Ground Tab = Without
- Signal Lead Quantity = 8

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:

- Left LED Color (Position #1) = Green - 250 ohm resistor
- Right LED Color (Position #2) = Yellow - 250 ohm resistor

Conditions for Usage:

- Temperature Rating = Industrial / Commercial (-40 ºC to + 85 ºC)

Operation/Application:

- Application = 10/100BASE -T Ethernet

Other:

- Insulator = Without
- Brand = Transpower

© 2006 Tyco Electronics Corporation All Rights Reserved