

Technical Data

ROCOL®

Performance you can trust



FOODLUBE® Extreme

Food grade multipurpose EP grease.
Non-toxic lubricant designed for the effective lubrication and protection of ball, roller and plain bearings operating in food/clean environments.

Features

- Temperature range –30°C to 160°C
- Excellent EP performance (355kg weld load)
- Highly resistant to water wash off
- Excellent corrosion protection
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients.
- FDA Group 21 CFR 178.3570
- NSF H1 registered – 132235
- DIN V 10517

Directions for Use

- Apply manually or with a suitable applicator e.g. ROCOL grease gun.
- The previous lubricant should be removed prior to application.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.

Technical Data

ROCOL®

Performance you can trust

FOODLUBE® Extreme

Appearance	Beige, tenacious grease
NLGI No. (IP 50)(ASTM D217)	NLGI No. 2
Base type	Synthetic
Thickener	Organo Clay
Solids	High Load White Solids
Temperature range	-30°C to 160°C
Drop point	None
Base fluid viscosity at 40°C	200 cSt
Shell 4 ball (IP 239)(ASTM D2596)	
Weld load	355 kg
EMCOR Corrosion Test (IP220)	0 Rating
Copper corrosion test (IP 112)(ASTM D130)	Pass
Water washout test (IP 215)(ASTM D 1264)	<2.0%
Storage	Storage temperature should be controlled to between 1 and 40°C.
Pack Sizes – Part Codes	380g – p/c 15241 4kg – p/c 15246 18kg – p/c 15244

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers.
There are many factors outside our control or knowledge which affect the use and performance
of our products, for which reason it is given without responsibility.