

# MAX3222/MAX3232/ MAX3237/MAX3241\*

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1µF External Capacitors

### General Description

The MAX3222/MAX3232/MAX3237/MAX3241 transceivers have a proprietary low-dropout transmitter output stage enabling true RS-232 performance from a 3.0V to 5.5V supply with a dual charge pump. The devices require only four small 0.1µF external charge-pump capacitors. The MAX3222, MAX3232, and MAX3241 are guaranteed to run at data rates of 120kbps while maintaining RS-232 output levels. The MAX3237 is guaranteed to run at data rates of 250kbps in the normal operating mode and 1Mbps in the MegaBaud™ operating mode, while maintaining RS-232 output levels.

The MAX3222/MAX3232 have 2 receivers and 2 drivers. The MAX3222 features a 1µA shutdown mode that reduces power consumption and extends battery life in portable systems. Its receivers remain active in shutdown mode, allowing external devices such as modems to be monitored using only 1µA supply current. The MAX3222 and MAX3232 are pin, package, and functionally compatible with the industry-standard MAX242 and MAX232, respectively.

The MAX3241 is a complete serial port (3 drivers/5 receivers) designed for notebook and subnotebook computers. The MAX3237 (5 drivers/3 receivers) is ideal for fast modem applications. Both these devices feature a shutdown mode in which all receivers can remain active while using only 1µA supply current. Receivers R1 (MAX3237/MAX3241) and R2 (MAX3241) have extra outputs in addition to their standard outputs. These extra outputs are always active, allowing external devices such as a modem to be monitored without forward biasing the protection diodes in circuitry that may have V<sub>CC</sub> completely removed.

The MAX3222, MAX3232, and MAX3241 are available in space-saving TSSOP and SSOP packages.

### Applications

Notebook, Subnotebook, and Palmtop Computers  
High-Speed Modems  
Battery-Powered Equipment  
Hand-Held Equipment  
Peripherals  
Printers

**Typical Operating Circuits appear at end of data sheet.**

MegaBaud and UCSP are trademarks of Maxim Integrated Products, Inc.

\*Covered by U.S. Patent numbers 4,636,930; 4,679,134; 4,777,577; 4,797,899; 4,809,152; 4,897,774; 4,999,761; and other patents pending.

### Next Generation Device Features

- ♦ **For Smaller Packaging:**  
MAX3228E/MAX3229E: +2.5V to +5.5V RS-232 Transceivers in UCSP™
- ♦ **For Integrated ESD Protection:**  
MAX3222E/MAX3232E/MAX3237E/MAX3241E\*/MAX3246E: ±15kV ESD-Protected, Down to 10nA, 3.0V to 5.5V, Up to 1Mbps, True RS-232 Transceivers
- ♦ **For Low-Voltage or Data Cable Applications:**  
MAX3380E/MAX3381E: +2.35V to +5.5V, 1µA, 2Tx/2Rx RS-232 Transceivers with ±15kV ESD-Protected I/O and Logic Pins


### Ordering Information

| PART        | TEMP RANGE   | PIN-PACKAGE    | PKG CODE |
|-------------|--------------|----------------|----------|
| MAX3222CUP+ | 0°C to +70°C | 20 TSSOP       | U20+2    |
| MAX3222CAP+ | 0°C to +70°C | 20 SSOP        | A20+1    |
| MAX3222CWN+ | 0°C to +70°C | 18 SO          | W18+1    |
| MAX3222CPN+ | 0°C to +70°C | 18 Plastic Dip | P18+5    |

+ Denotes lead-free package.

Ordering Information continued at end of data sheet.

### Pin Configurations



**For pricing, delivery, and ordering information, please contact Maxim Direct at 1-888-629-4642, or visit Maxim Integrated's website at [www.maximintegrated.com](http://www.maximintegrated.com).**

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1µF External Capacitors

### ABSOLUTE MAXIMUM RATINGS

|                                                                           |                                   |
|---------------------------------------------------------------------------|-----------------------------------|
| V <sub>CC</sub> .....                                                     | -0.3V to +6V                      |
| V <sub>+</sub> (Note 1) .....                                             | -0.3V to +7V                      |
| V <sub>-</sub> (Note 1) .....                                             | +0.3V to -7V                      |
| V <sub>+</sub> + V <sub>-</sub> (Note 1) .....                            | +13V                              |
| Input Voltages                                                            |                                   |
| T <sub>IN</sub> , $\overline{\text{SHDN}}$ , $\overline{\text{EN}}$ ..... | -0.3V to +6V                      |
| MBAUD .....                                                               | -0.3V to (V <sub>CC</sub> + 0.3V) |
| R <sub>IN</sub> .....                                                     | ±25V                              |
| Output Voltages                                                           |                                   |
| T <sub>OUT</sub> .....                                                    | ±13.2V                            |
| R <sub>OUT</sub> .....                                                    | -0.3V to (V <sub>CC</sub> + 0.3V) |
| Short-Circuit Duration                                                    |                                   |
| T <sub>OUT</sub> .....                                                    | Continuous                        |

|                                                          |                |
|----------------------------------------------------------|----------------|
| Continuous Power Dissipation (T <sub>A</sub> = +70°C)    |                |
| 16-Pin TSSOP (derate 6.7mW/°C above +70°C) .....         | 533mW          |
| 16-Pin Narrow SO (derate 8.70mW/°C above +70°C) .....    | 696mW          |
| 16-Pin Wide SO (derate 9.52mW/°C above +70°C) .....      | 762mW          |
| 16-Pin Plastic DIP (derate 10.53mW/°C above +70°C) ..... | 842mW          |
| 18-Pin SO (derate 9.52mW/°C above +70°C) .....           | 762mW          |
| 18-Pin Plastic DIP (derate 11.11mW/°C above +70°C) ..... | 889mW          |
| 20-Pin SSOP (derate 7.00mW/°C above +70°C) .....         | 559mW          |
| 20-Pin TSSOP (derate 8.0mW/°C above +70°C) .....         | 640mW          |
| 28-Pin TSSOP (derate 8.7mW/°C above +70°C) .....         | 696mW          |
| 28-Pin SSOP (derate 9.52mW/°C above +70°C) .....         | 762mW          |
| 28-Pin SO (derate 12.50mW/°C above +70°C) .....          | 1W             |
| Operating Temperature Ranges                             |                |
| MAX32__C_ .....                                          | 0°C to +70°C   |
| MAX32__E_ .....                                          | -40°C to +85°C |
| Storage Temperature Range .....                          |                |
| Lead Temperature (soldering, 10s) .....                  |                |
| +300°C                                                   |                |

**Note 1:** V<sub>+</sub> and V<sub>-</sub> can have a maximum magnitude of 7V, but their absolute difference cannot exceed 13V.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

### ELECTRICAL CHARACTERISTICS

(V<sub>CC</sub> = +3.0V to +5.5V, C1–C4 = 0.1µF (Note 2), T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.)

| PARAMETER                            | CONDITIONS                                                                  |                             | MIN                   | TYP                   | MAX | UNITS |
|--------------------------------------|-----------------------------------------------------------------------------|-----------------------------|-----------------------|-----------------------|-----|-------|
| DC CHARACTERISTICS                   |                                                                             |                             |                       |                       |     |       |
| V <sub>CC</sub> Power-Supply Current | No load, V <sub>CC</sub> = 3.3V or 5.0V, T <sub>A</sub> = +25°C             | MAX3222/MAX3232/<br>MAX3241 | 0.3                   | 1.0                   | mA  |       |
|                                      |                                                                             | MAX3237                     | 0.5                   | 2.0                   |     |       |
| Shutdown Supply Current              | $\overline{\text{SHDN}}$ = GND, T <sub>A</sub> = +25°C                      |                             | 1.0                   | 10                    | μA  |       |
| LOGIC INPUTS AND RECEIVER OUTPUTS    |                                                                             |                             |                       |                       |     |       |
| Input Logic Threshold Low (Note 3)   | T <sub>IN</sub> , $\overline{\text{EN}}$ , $\overline{\text{SHDN}}$ , MBAUD |                             | 0.8                   |                       | V   |       |
| Input Logic Threshold High (Note 3)  | V <sub>CC</sub> = 3.3V                                                      |                             | 2.0                   |                       | V   |       |
|                                      | V <sub>CC</sub> = 5.0V                                                      |                             | 2.4                   |                       |     |       |
| Input Leakage Current                | T <sub>IN</sub> , $\overline{\text{EN}}$ , $\overline{\text{SHDN}}$ , MBAUD |                             | ±0.01                 | ±1.0                  | μA  |       |
| Output Leakage Current               | Receivers disabled                                                          |                             | ±0.05                 | ±10                   | μA  |       |
| Output Voltage Low                   | I <sub>OUT</sub> = 1.6mA                                                    |                             | 0.4                   |                       | V   |       |
| Output Voltage High                  | I <sub>OUT</sub> = -1.0mA                                                   |                             | V <sub>CC</sub> - 0.6 | V <sub>CC</sub> - 0.1 | V   |       |
| RECEIVER INPUTS                      |                                                                             |                             |                       |                       |     |       |
| Input Voltage Range                  |                                                                             |                             | -25                   | 25                    | V   |       |
| Input Threshold Low                  | T <sub>A</sub> = +25°C                                                      | V <sub>CC</sub> = 3.3V      | 0.6                   | 1.2                   | V   |       |
|                                      |                                                                             | V <sub>CC</sub> = 5.0V      | 0.8                   | 1.5                   |     |       |
| Input Threshold High                 | T <sub>A</sub> = +25°C                                                      | V <sub>CC</sub> = 3.3V      | 1.5                   | 2.4                   | V   |       |
|                                      |                                                                             | V <sub>CC</sub> = 5.0V      | 1.8                   | 2.4                   |     |       |

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1µF External Capacitors

### ELECTRICAL CHARACTERISTICS (continued)

(V<sub>CC</sub> = +3.0V to +5.5V, C1–C4 = 0.1µF (Note 2), T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.)

| PARAMETER                           | CONDITIONS                                                                                                       | MIN  | TYP  | MAX | UNITS |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------|------|------|-----|-------|
| Input Hysteresis                    |                                                                                                                  |      | 0.3  |     | V     |
| Input Resistance                    | T <sub>A</sub> = +25°C                                                                                           | 3    | 5    | 7   | kΩ    |
| <b>TRANSMITTER OUTPUTS</b>          |                                                                                                                  |      |      |     |       |
| Output Voltage Swing                | All transmitter outputs loaded with 3kΩ to ground                                                                | ±5.0 | ±5.4 |     | V     |
| Output Resistance                   | V <sub>CC</sub> = V <sub>+</sub> = V <sub>-</sub> = 0V, V <sub>OUT</sub> = ±2V                                   | 300  | 10M  |     | Ω     |
| Output Short-Circuit Current        |                                                                                                                  |      | ±35  | ±60 | mA    |
| Output Leakage Current              | V <sub>OUT</sub> = ±12V, V <sub>CC</sub> = 0V or 3V to 5.5V, transmitters disabled                               |      |      | ±25 | µA    |
| <b>MOUSE DRIVEABILITY (MAX3241)</b> |                                                                                                                  |      |      |     |       |
| Transmitter Output Voltage          | T1IN = T2IN = GND, T3IN = V <sub>CC</sub> , T3OUT loaded with 3kΩ to GND, T1OUT and T2OUT loaded with 2.5mA each | ±5.0 |      |     | V     |

### TIMING CHARACTERISTICS—MAX3222/MAX3232/MAX3241

(V<sub>CC</sub> = +3.0V to +5.5V, C1–C4 = 0.1µF (Note 2), T<sub>A</sub> = T<sub>MIN</sub> to T<sub>MAX</sub>, unless otherwise noted. Typical values are at T<sub>A</sub> = +25°C.)

| PARAMETER                    | CONDITIONS                                                                                                                       | MIN                              | TYP | MAX | UNITS |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-----|-----|-------|
| Maximum Data Rate            | R <sub>L</sub> = 3kΩ, C <sub>L</sub> = 1000pF, one transmitter switching                                                         | 120                              | 235 |     | kbps  |
| Receiver Propagation Delay   | R <sub>IN</sub> to R <sub>OUT</sub> , C <sub>L</sub> = 150pF                                                                     | t <sub>PHL</sub>                 |     | 0.3 | µs    |
|                              |                                                                                                                                  | t <sub>PLH</sub>                 |     | 0.3 |       |
| Receiver Output Enable Time  | Normal operation                                                                                                                 |                                  | 200 |     | ns    |
| Receiver Output Disable Time | Normal operation                                                                                                                 |                                  | 200 |     | ns    |
| Transmitter Skew             | t <sub>PHL</sub> - t <sub>PLH</sub>                                                                                              |                                  | 300 |     | ns    |
| Receiver Skew                | t <sub>PHL</sub> - t <sub>PLH</sub>                                                                                              |                                  | 300 |     | ns    |
| Transition-Region Slew Rate  | V <sub>CC</sub> = 3.3V, R <sub>L</sub> = 3kΩ to 7kΩ, +3V to -3V or -3V to +3V, T <sub>A</sub> = +25°C, one transmitter switching | C <sub>L</sub> = 150pF to 1000pF |     | 6   | V/µs  |
|                              |                                                                                                                                  | C <sub>L</sub> = 150pF to 2500pF |     | 4   |       |

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors

### TIMING CHARACTERISTICS—MAX3237

( $V_{CC} = +3.0V$  to  $+5.5V$ ,  $C_1$ – $C_4 = 0.1\mu F$  (Note 2),  $T_A = T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted. Typical values are at  $T_A = +25^\circ C$ .)




| PARAMETER                    | CONDITIONS                                                                                                                        |                                               |                         | MIN  | TYP | MAX  | UNITS |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------|------|-----|------|-------|
| Maximum Data Rate            | R <sub>L</sub> = 3kΩ, C <sub>L</sub> = 1000pF, one transmitter switching, MBAUD = GND                                             |                                               |                         | 250  |     | kbps |       |
|                              | V <sub>CC</sub> = 3.0V to 4.5V, R <sub>L</sub> = 3kΩ, C <sub>L</sub> = 250pF, one transmitter switching, MBAUD = V <sub>CC</sub>  |                                               |                         | 1000 |     |      |       |
|                              | V <sub>CC</sub> = 4.5V to 5.5V, R <sub>L</sub> = 3kΩ, C <sub>L</sub> = 1000pF, one transmitter switching, MBAUD = V <sub>CC</sub> |                                               |                         | 1000 |     |      |       |
| Receiver Propagation Delay   | R_IN to R_OUT, C <sub>L</sub> = 150pF                                                                                             |                                               | t <sub>PHL</sub>        | 0.15 |     | μs   |       |
|                              |                                                                                                                                   |                                               | t <sub>PLH</sub>        | 0.15 |     |      |       |
| Receiver Output Enable Time  | Normal operation                                                                                                                  |                                               |                         | 200  |     | ns   |       |
| Receiver Output Disable Time | Normal operation                                                                                                                  |                                               |                         | 200  |     | ns   |       |
| Transmitter Skew             | t <sub>PHL</sub> - t <sub>PLH</sub>  , MBAUD = GND                                                                                |                                               |                         | 100  |     | ns   |       |
|                              | t <sub>PHL</sub> - t <sub>PLH</sub>  , MBAUD = V <sub>CC</sub>                                                                    |                                               |                         | 25   |     | ns   |       |
| Receiver Skew                | t <sub>PHL</sub> - t <sub>PLH</sub>                                                                                               |                                               |                         | 50   |     | ns   |       |
| Transition-Region Slew Rate  | V <sub>CC</sub> = 3.3V, R <sub>L</sub> = 3Ω to 7kΩ, +3V to -3V or -3V to +3V, T <sub>A</sub> = +25°C                              | C <sub>L</sub> = 150pF to 1000pF              | MBAUD = GND             | 6    | 30  | V/μs |       |
|                              |                                                                                                                                   |                                               | MBAUD = V <sub>CC</sub> | 24   | 150 |      |       |
|                              |                                                                                                                                   | C <sub>L</sub> = 150pF to 2500pF, MBAUD = GND |                         | 4    | 30  |      |       |

**Note 2:** MAX3222/MAX3232/MAX3241:  $C_1$ – $C_4 = 0.1\mu F$  tested at  $3.3V \pm 10\%$ ;  $C_1 = 0.047\mu F$ ,  $C_2$ – $C_4 = 0.33\mu F$  tested at  $5.0V \pm 10\%$ . MAX3237:  $C_1$ – $C_4 = 0.1\mu F$  tested at  $3.3V \pm 5\%$ ;  $C_1$ – $C_4 = 0.22\mu F$  tested at  $3.3V \pm 10\%$ ;  $C_1 = 0.047\mu F$ ,  $C_2$ – $C_4 = 0.33\mu F$  tested at  $5.0V \pm 10\%$ .

**Note 3:** Transmitter input hysteresis is typically 250mV.

### Typical Operating Characteristics

( $V_{CC} = +3.3V$ , 235kbps data rate,  $0.1\mu F$  capacitors, all transmitters loaded with  $3k\Omega$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)












# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1 $\mu$ F External Capacitors

### Typical Operating Characteristics (continued)

( $V_{CC} = +3.3V$ , 235kbps data rate, 0.1 $\mu$ F capacitors, all transmitters loaded with 3k $\Omega$ ,  $T_A = +25^\circ C$ , unless otherwise noted.)



# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors

### Pin Description

| PIN     |        |         |                    |            | NAME                     | FUNCTION                                                                                                              |
|---------|--------|---------|--------------------|------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------|
| MAX3222 |        | MAX3232 | MAX3237            | MAX3241    |                          |                                                                                                                       |
| DIP/SO  | SSOP   |         |                    |            |                          |                                                                                                                       |
| 1       | 1      | —       | 13                 | 23         | $\overline{\text{EN}}$   | Receiver Enable. Active low.                                                                                          |
| 2       | 2      | 1       | 28                 | 28         | C1+                      | Positive Terminal of Voltage-Doubler Charge-Pump Capacitor                                                            |
| 3       | 3      | 2       | 27                 | 27         | V+                       | +5.5V Generated by the Charge Pump                                                                                    |
| 4       | 4      | 3       | 25                 | 24         | C1-                      | Negative Terminal of Voltage-Doubler Charge-Pump Capacitor                                                            |
| 5       | 5      | 4       | 1                  | 1          | C2+                      | Positive Terminal of Inverting Charge-Pump Capacitor                                                                  |
| 6       | 6      | 5       | 3                  | 2          | C2-                      | Negative Terminal of Inverting Charge-Pump Capacitor                                                                  |
| 7       | 7      | 6       | 4                  | 3          | V-                       | -5.5V Generated by the Charge Pump                                                                                    |
| 8, 15   | 8, 17  | 7, 14   | 5, 6, 7, 10, 12    | 9, 10, 11  | T_OUT                    | RS-232 Transmitter Outputs                                                                                            |
| 9, 14   | 9, 16  | 8, 13   | 8, 9, 11           | 4–8        | R_IN                     | RS-232 Receiver Inputs                                                                                                |
| 10, 13  | 10, 15 | 9, 12   | 18, 20, 21         | 15–19      | R_OUT                    | TTL/CMOS Receiver Outputs                                                                                             |
| 11, 12  | 12, 13 | 10, 11  | 17, 19, 22, 23, 24 | 12, 13, 14 | T_IN                     | TTL/CMOS Transmitter Inputs                                                                                           |
| 16      | 18     | 15      | 2                  | 25         | GND                      | Ground                                                                                                                |
| 17      | 19     | 16      | 26                 | 26         | V <sub>CC</sub>          | +3.0V to +5.5V Supply Voltage                                                                                         |
| 18      | 20     | —       | 14                 | 22         | $\overline{\text{SHDN}}$ | Shutdown Control. Active low.                                                                                         |
| —       | 11, 14 | —       | —                  | —          | N.C.                     | No Connection                                                                                                         |
| —       | —      | —       | 15                 | —          | MBAUD                    | MegaBaud Control Input. Connect to GND for normal operation; connect to V <sub>CC</sub> for 1Mbps transmission rates. |
| —       | —      | —       | 16                 | 20, 21     | R_OUTB                   | Noninverting Complementary Receiver Outputs. Always active.                                                           |

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors

### Detailed Description

#### Dual Charge-Pump Voltage Converter

The MAX3222/MAX3232/MAX3237/MAX3241's internal power supply consists of a regulated dual charge pump that provides output voltages of +5.5V (doubling charge pump) and -5.5V (inverting charge pump), regardless of the input voltage ( $V_{CC}$ ) over the 3.0V to 5.5V range. The charge pumps operate in a discontinuous mode; if the output voltages are less than 5.5V, the charge pumps are enabled, and if the output voltages exceed 5.5V, the charge pumps are disabled. Each charge pump requires a flying capacitor (C1, C2) and a reservoir capacitor (C3, C4) to generate the  $V+$  and  $V-$  supplies.

#### RS-232 Transmitters

The transmitters are inverting level translators that convert CMOS-logic levels to 5.0V EIA/TIA-232 levels.

The MAX3222/MAX3232/MAX3241 transmitters guarantee a 120kbps data rate with worst-case loads of  $3k\Omega$  in parallel with 1000pF, providing compatibility with PC-to-PC communication software (such as LapLink™). Typically, these three devices can operate at data rates of 235kbps. Transmitters can be paralleled to drive multiple receivers or mice.

The MAX3222/MAX3237/MAX3241's output stage is turned off (high impedance) when the device is in shut-down mode. When the power is off, the MAX3222/MAX3232/MAX3237/MAX3241 permit the outputs to be driven up to  $\pm 12V$ .

The transmitter inputs do not have pullup resistors. Connect unused inputs to GND or  $V_{CC}$ .

#### MAX3237 MegaBaud Operation

In normal operating mode (MBAUD = GND), the MAX3237 transmitters guarantee a 250kbps data rate with worst-case loads of  $3k\Omega$  in parallel with 1000pF. This provides compatibility with PC-to-PC communication software, such as LapLink.

For higher speed serial communications, the MAX3237 features MegaBaud operation. In MegaBaud operating mode (MBAUD =  $V_{CC}$ ), the MAX3237 transmitters guarantee a 1Mbps data rate with worst-case loads of  $3k\Omega$  in parallel with 250pF for  $3.0V < V_{CC} < 4.5V$ . For  $5V \pm 10\%$  operation, the MAX3237 transmitters guarantee a 1Mbps data rate into worst-case loads of  $3k\Omega$  in parallel with 1000pF.

LapLink is a trademark of Traveling Software, Inc.




Figure 1. Slew-Rate Test Circuits



# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors

## RS-232 Receivers

The receivers convert RS-232 signals to CMOS-logic output levels. The MAX3222/MAX3237/MAX3241 receivers have inverting three-state outputs. In shutdown, the receivers can be active or inactive (Table 1).

The complementary outputs on the MAX3237 (R1OUTB) and the MAX3241 (R1OUTB, R2OUTB) are always active, regardless of the state of  $\overline{\text{EN}}$  or SHDN. This allows for Ring Indicator applications without forward biasing other devices connected to the receiver outputs. This is ideal for systems where  $V_{CC}$  is set to 0V in shutdown to accommodate peripherals, such as UARTs (Figure 2).

## MAX3222/MAX3237/MAX3241 Shutdown Mode

Supply current falls to less than 1  $\mu$ A in shutdown mode ( $\overline{\text{SHDN}} = \text{low}$ ). When shut down, the device's charge pumps are turned off,  $V_+$  is pulled down to  $V_{CC}$ ,  $V_-$  is pulled to ground, and the transmitter outputs are disabled (high impedance). The time required to exit shutdown is typically 100  $\mu$ s, as shown in Figure 3. Connect  $\overline{\text{SHDN}}$  to  $V_{CC}$  if the shutdown mode is not used.  $\overline{\text{SHDN}}$  has no effect on  $R_{OUT}$  or  $R_{OUTB}$ .

### **MAX3222/MAX3237/MAX3241** **Enable Control**

The inverting receiver outputs (R\_OUT) are put into a high-impedance state when EN is high. The complementary outputs R1OUTB and R2OUTB are always active, regardless of the state of EN and SHDN (Table 1). EN has no effect on T\_OUT.

## Applications Information

## Capacitor Selection

The capacitor type used for C1–C4 is not critical for proper operation; polarized or nonpolarized capacitors can be used. The charge pump requires 0.1  $\mu$ F capacitors for 3.3V operation. For other supply voltages, refer to Table 2 for required capacitor values. Do not use values lower than those listed in Table 2. Increasing the capacitor values (e.g., by a factor of 2) reduces ripple on the transmitter outputs and slightly reduces power consumption. C2, C3, and C4 can be increased without changing C1's value. However, do not increase C1 without also increasing the values of C2, C3, and C4, to maintain the proper ratios (C1 to the other capacitors).

When using the minimum required capacitor values, make sure the capacitor value does not degrade excessively with temperature. If in doubt, use capacitors with a higher nominal value. The capacitor's equivalent series resistance (ESR), which usually rises at low temperatures, influences the amount of ripple on V+ and V-.




Figure 2. Detection of RS-232 Activity when the UART and Interface are Shut Down; Comparison of MAX3237/MAX3241 (b) with Previous Transceivers (a).



# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors

**Table 1. MAX3222/MAX3237/MAX3241 Shutdown and Enable Control Truth Table**

| SHDN | EN | T_OUT  | R_OUT  | R_OUTB<br>(MAX3237/<br>MAX3241) |
|------|----|--------|--------|---------------------------------|
| 0    | 0  | High-Z | Active | Active                          |
| 0    | 1  | High-Z | High-Z | Active                          |
| 1    | 0  | Active | Active | Active                          |
| 1    | 1  | Active | High-Z | Active                          |

**Table 2. Required Minimum Capacitor Values**

| V <sub>CC</sub><br>(V)         | C1<br>(μF) | C2, C3, C4<br>(μF) |
|--------------------------------|------------|--------------------|
| <b>MAX3222/MAX3232/MAX3241</b> |            |                    |
| 3.0 to 3.6                     | 0.1        | 0.1                |
| 4.5 to 5.5                     | 0.047      | 0.33               |
| 3.0 to 5.5                     | 0.1        | 0.47               |
| <b>MAX3237</b>                 |            |                    |
| 3.0 to 3.6                     | 0.22       | 0.22               |
| 3.15 to 3.6                    | 0.1        | 0.1                |
| 4.5 to 5.5                     | 0.047      | 0.33               |
| 3.0 to 5.5                     | 0.22       | 1.0                |

### Power-Supply Decoupling

In most circumstances, a 0.1μF bypass capacitor is adequate. In applications that are sensitive to power-supply noise, decouple V<sub>CC</sub> to ground with a capacitor of the same value as charge-pump capacitor C1. Connect bypass capacitors as close to the IC as possible.

### Operation Down to 2.7V

Transmitter outputs will meet EIA/TIA-562 levels of ±3.7V with supply voltages as low as 2.7V.

### Transmitter Outputs when Exiting Shutdown

Figure 3 shows two transmitter outputs when exiting shutdown mode. As they become active, the two transmitter outputs are shown going to opposite RS-232 levels (one transmitter input is high, the other is low). Each transmitter is loaded with 3kΩ in parallel with 2500pF. The transmitter outputs display no ringing or undesirable transients as they come out of shutdown. Note that the transmitters are enabled only when the magnitude of V<sub>-</sub> exceeds approximately 3V.

### Mouse Driveability

The MAX3241 has been specifically designed to power serial mice while operating from low-voltage power supplies. It has been tested with leading mouse brands from manufacturers such as Microsoft and Logitech. The MAX3241 successfully drove all serial mice tested and met their respective current and voltage requirements. Figure 4a shows the transmitter output voltages under increasing load current at 3.0V. Figure 4b shows a typical mouse connection using the MAX3241.




Figure 3. Transmitter Outputs when Exiting Shutdown or Powering Up

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1 $\mu$ F External Capacitors




Figure 4a. MAX3241 Transmitter Output Voltage vs. Load Current per Transmitter






Figure 4b. Mouse Driver Test Circuit

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1 $\mu$ F External Capacitors



The MAX3222/MAX3232/MAX3241 maintain the RS-232  $\pm 5.0\text{V}$  minimum transmitter output voltage even at high data rates. Figure 5 shows a transmitter loopback test circuit. Figure 6 shows a loopback test result at 120kbps, and Figure 7 shows the same test at 235kbps. For Figure 6, all transmitters were driven simultaneously at 120kbps into RS-232 loads in parallel with 1000pF. For Figure 7, a single transmitter was driven at 235kbps, and all transmitters were loaded with an RS-232 receiver in parallel with 1000pF.

Figure 6. MAX3241 Loopback Test Result at 120kbps



# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors


### Interconnection with 3V and 5V Logic

The MAX3222/MAX3232/MAX3237/MAX3241 can directly interface with various 5V logic families, including ACT and HCT CMOS. See Table 3 for more information on possible combinations of interconnections.

Table 3. Logic-Family Compatibility with Various Supply Voltages

| SYSTEM POWER-SUPPLY VOLTAGE (V) | MAX32_ _ V <sub>CC</sub> SUPPLY VOLTAGE (V) | COMPATIBILITY                                                                              |
|---------------------------------|---------------------------------------------|--------------------------------------------------------------------------------------------|
| 3.3                             | 3.3                                         | Compatible with all CMOS families.                                                         |
| 5                               | 5                                           | Compatible with all TTL and CMOS-logic families.                                           |
| 5                               | 3.3                                         | Compatible with ACT and HCT CMOS, and with TTL. Incompatible with AC, HC, and CD4000 CMOS. |


### Typical Operating Circuits




# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1µF External Capacitors

### Typical Operating Circuits (continued)



\* C3 CAN BE RETURNED TO EITHER V<sub>CC</sub> OR GROUND.







\* C3 CAN BE RETURNED TO EITHER V<sub>CC</sub> OR GROUND.

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors

### Pin Configurations (continued)

TOP VIEW



# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1µF External Capacitors

### Ordering Information (continued)

| PART                | TEMP RANGE     | PIN-PACKAGE    | PKG CODE |
|---------------------|----------------|----------------|----------|
| MAX3222EUP+         | -40°C to +85°C | 20 TSSOP       | U20+2    |
| MAX3222EAP+         | -40°C to +85°C | 20 SSOP        | A20+1    |
| MAX3222EWN+         | -40°C to +85°C | 18 SO          | W18+1    |
| MAX3222EPN+         | -40°C to +85°C | 18 Plastic Dip | P18+5    |
| MAX3222C/D          | 0°C to +70°C   | Dice*          | —        |
| <b>MAX3232</b> CUE+ | 0°C to +70°C   | 16 TSSOP       | U16+1    |
| MAX3232CSE+         | 0°C to +70°C   | 16 Narrow SO   | S16+1    |
| MAX3232CWE+         | 0°C to +70°C   | 16 Wide SO     | W16+1    |
| MAX3232CPE+         | 0°C to +70°C   | 16 Plastic DIP | P16+1    |
| MAX3232EUE+         | -40°C to +85°C | 16 TSSOP       | U16+1    |
| MAX3232ESE+         | -40°C to +85°C | 16 Narrow SO   | S16+5    |

| PART                | TEMP RANGE     | PIN-PACKAGE    | PKG CODE |
|---------------------|----------------|----------------|----------|
| MAX3232EWE+         | -40°C to +85°C | 16 Wide SO     | W16+1    |
| MAX3232EPE+         | -40°C to +85°C | 16 Plastic DIP | P16+1    |
| <b>MAX3237</b> CAI+ | 0°C to +70°C   | 16 SSOP        | A28+2    |
| MAX3237EAI+         | 0°C to +70°C   | 28 SSOP        | A28+1    |
| <b>MAX3241</b> CUI+ | 0°C to +70°C   | 28 TSSOP       | U28+2    |
| MAX3241CAI+         | 0°C to +70°C   | 28 SSOP        | A28+1    |
| MAX3241CWI+         | 0°C to +70°C   | 28 SO          | W28+6    |
| MAX3241EUI+         | -40°C to +85°C | 28 TSSOP       | U28+2    |
| MAX3241EAI+         | -40°C to +85°C | 28 SSOP        | A28+1    |
| MAX3241EWI+         | -40°C to +85°C | 28 SO          | W28+6    |

\*Dice are tested at  $T_A = +25^\circ\text{C}$ , DC parameters only.

+Denotes lead-free package.

### 3V-Powered EIA/TIA-232 and EIA/TIA-562 Transceivers from Maxim


| PART    | POWER-SUPPLY VOLTAGE (V) | No. OF TRANSMITTERS/RECEIVERS | No. OF RECEIVERS ACTIVE IN SHUTDOWN | GUAR-ANTEED DATA RATE (kbps) | EIA/TIA-232 OR 562 | FEATURES                                                               |
|---------|--------------------------|-------------------------------|-------------------------------------|------------------------------|--------------------|------------------------------------------------------------------------|
| MAX212  | 3.0 to 3.6               | 3/5                           | 5                                   | 120                          | 232                | Drives mice                                                            |
| MAX218  | 1.8 to 4.25              | 2/2                           | 2                                   | 120                          | 232                | Operates directly from batteries without a voltage regulator           |
| MAX562  | 2.7 to 5.25              | 3/5                           | 5                                   | 230                          | 562                | Wide supply range                                                      |
| MAX563  | 3.0 to 3.6               | 2/2                           | 2                                   | 230                          | 562                | 0.1µF capacitors                                                       |
| MAX3212 | 2.7 to 3.6               | 3/5                           | 5                                   | 235                          | 232                | AutoShutdown, complementary receiver, drives mice, transient detection |
| MAX3222 | 3.0 to 5.5               | 2/2                           | 2                                   | 120                          | 232                | 0.1µF capacitors                                                       |
| MAX3223 | 3.0 to 5.5               | 2/2                           | 2                                   | 120                          | 232                | 0.1µF capacitors, AutoShutdown                                         |
| MAX3232 | 3.0 to 5.5               | 2/2                           | N/A                                 | 120                          | 232                | 0.1µF capacitors                                                       |
| MAX3237 | 3.0 to 5.5               | 5/3                           | 3                                   | 250/1000                     | 232                | 0.1µF capacitors, 1 complementary receiver, MegaBaud operation         |
| MAX3241 | 3.0 to 5.5               | 3/5                           | 5                                   | 120                          | 232                | 0.1µF capacitors, 2 complementary receivers, drives mice               |
| MAX3243 | 3.0 to 5.5               | 3/5                           | 1                                   | 120                          | 232                | 0.1µF capacitors, AutoShutdown, complementary receiver, drives mice    |



# MAX3222/MAX3232/MAX3237/MAX3241

**3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1μF External Capacitors**

## Chip Topography



## Chip Information

| PART    | TRANSISTOR COUNT |
|---------|------------------|
| MAX3222 | 339              |
| MAX3232 | 339              |
| MAX3237 | 1212             |
| MAX3241 | 894              |


TRANSISTOR COUNT: 339  
SUBSTRATE CONNECTED TO GND

# MAX3222/MAX3232/MAX3237/MAX3241

## 3.0V to 5.5V, Low-Power, up to 1Mbps, True RS-232 Transceivers Using Four 0.1µF External Capacitors

### Package Information

For the latest package outline information and land patterns (footprints), go to [www.maximintegrated.com/packages](http://www.maximintegrated.com/packages). Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.



### Revision History

Pages changed at Rev 7: 1, 15, 16, 17



Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the Electrical Characteristics table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

Maxim Integrated 160 Rio Robles, San Jose, CA 95134 USA 1-408-601-1000

17