



# TC1167

## Highly integrated 32-bit TriCore™-based Microcontroller for Industrial Applications

The TC1167 is the value optimized member of the Audo Future product family designed for high demanding real-time applications. Its award-winning TriCore™ CPU provides high-end microcontroller performance combined with sophisticated DSP capabilities.

A dedicated peripheral control processor (PCP) manages on-chip peripherals and relieves the TriCore™ from standard processing tasks. On top of this, a fast interrupt response time assures low latencies and low performance overhead for interrupt driven systems. Equipped with 1MByte of embedded Flash and a total of 128KByte RAM the TC1167 is a high performance device offering best value for embedded real-time industrial applications. The device is positioned in the mid-range of the audo future product family that covers the complete range from the very high end to very low cost. The comprehensive tool support emphasizes the great scalability of the family products.

### Applications

- Multi-axis controller for up to two 3-phase complementary PWM
- Supporting multiple modulation strategies (SVPWM, DPWM, Soft-PWM, Direct Torque Control)
- Ready for 4Q-Inverters, Matrix-Inverters
- Field oriented control with less than 10% CPU load
- Multiprocessor support for reliability and safety

### Features


- High performance 32-bit super-scalar TriCore™ V1.3.1 CPU with 4 stage pipeline
  - 133MHz
  - Superior real-time performance
  - Strong bit handling
  - Fully integrated DSP capabilities
  - Single precision floating point unit (FPU)
- 32-bit Peripheral Control Processor with single cycle instruction (PCP2)
  - 24KByte on-chip SRAM

### Features

- Memories
  - 1MByte embedded program flash with ECC
  - 16KByte EEPROM (emulated by 64KByte data Flash)
  - 92KByte on-chip SRAM
  - 4KByte data cache
  - 8KByte instruction cache
- 8 DMA channels
- General Purpose Timer Array and local timer cells with digital signal filters and timer functionality to realize complex I/O signalling (GPTA)
- Micro Second bus interface (MSC)
- 2 asynchronous/synchronous serial interfaces (ASC)
  - 2 high speed synchronous serial interfaces (SSC)
- High-speed Micro Link Interface (MLI)
- MultiCAN module with three CAN nodes and 64 message objects
- 4 channel fast analog-to-digital converter
- 32 channel analog-to-digital converter @ 5V
- On-chip debug support (OCDS)
- Dedicated emulation device chip for multicore debugging, tracing and calibration
- Core supply voltage 1.5V
- I/O voltage 3.3V and 5V
- Industrial temperature range: -40°C to +85°C

# TC1167

Block Diagram



## Product Summary

Type	CPU Clock	Temperature	Program Flash	Package
SAF-TC1167-128F133HL	133MHz	-40°C to +85°C	1MByte	LQFP-176

## Application Examples



How to reach us:  
<http://www.infineon.com>

Published by  
 Infineon Technologies AG  
 81726 Munich, Germany

© 2009 Infineon Technologies AG  
 All Rights Reserved.

**Legal Disclaimer** The information given in this Product Brief shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

**Information** For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

**Warnings** Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Infineon:](#)

[SAF-TC1167-128F133HL AD](#)