

Catalog that includes only former Hitachi products among Renesas Technology products.



Switching Power Supply Control ICs Products

April, 2003
Multi Purpose Semiconductor Device Div.
Analog & Discrete Semiconductor BU
Renesas Technology Corp.

Cautions

Keep safety first in your circuit designs!

1. Renesas Technology Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage.
Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of nonflammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

1. These materials are intended as a reference to assist our customers in the selection of the Renesas Technology Corporation product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Renesas Technology Corporation or a third party.
2. Renesas Technology Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
3. All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Renesas Technology Corporation without notice due to product improvements or other reasons.
It is therefore recommended that customers contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor for the latest product information before purchasing a product listed herein.
The information described here may contain technical inaccuracies or typographical errors.
Renesas Technology Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.
Please also pay attention to information published by Renesas Technology Corporation by various means, including the Renesas Technology Corporation Semiconductor home page (<http://www.renesas.com>).
4. When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products.
Renesas Technology Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
5. Renesas Technology Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Renesas Technology Corporation or an authorized Renesas Technology Corporation product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or system for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
6. The prior written approval of Renesas Technology Corporation is necessary to reprint or reproduce in whole or in part these materials.
7. If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
Any diversion or reexport contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
8. Please contact Renesas Technology Corporation for further details on these materials or the products contained therein.

Contents

- **Classified of Switching Regulator**
- **AC/DC Power Supply ICs**
- **Shunt Regulator**
- **PFC + PWM ICs**
- **Redundant Power Supply ICs.**
- **DC/DC ICs**
- **Half Bridge Power Supply IC**
- **Full Bridge Power Supply IC**

Classified of Switching Regulator

Isolated

Used
transformer

AC/DC converter

48 V input (brick, d2d)

UPS

redundant

Non isolated

DC/DC converter for battery

Single phase

Multi phase


Other

Shunt regulator

AC/DC Power Supply ICs

AC/DC Power Supply ICs

Type	SW mode		f	Package	Main SW	Note
V	C					
HA17384	—	✓	500 kHz	DIP-8	Power MOS	C-Mode
HA17385	—	✓	500 kHz	SOP-8	Power MOS	UC3842
HA16107	✓	—	600 kHz	DIP-16	Power MOS	Timer latch
HA16108	✓	—	600 kHz	SOP-16	Power MOS	Timer latch



Notes)

#V: Voltage mode


#C: Current mode

Shunt Regulator

Shunt Regulator IC Road Map

 : Mass Production







 : In Planning



Shunt Regulator ICs

HA17LXXX: 1.24 V HA17XXX: 2.50 V

TO-92MOD	TO-92	UPAK	MPAK-5	MPAK	SOP-8
HA17431PA	HA17L431AP HA17431VP HA17431PNA HA17431AP HA17431HP	HA17L431UP HA17L432UP HA17431UA HA17431HUP HA17432UA HA17432HUP	HA17L431ALP HA17431VLP HA17431HLP	HA17L431ALTP HA17L432ALTP HA17431HLTP HA17431VLTP HA17432HLTP HA17432VLTP	HA17431FPA



SMD

Note: Top of View

Many kind of packages.

Shunt Regulator ICs

V _x max (V)	V _{ref} and Accuracy	I _k max (V)	Parts name	Package
16	1.24 V $\pm$ 1.0%	-30 to 50	HA17L431AP	TO-92
			HA17L431ALP	MPAK-5
			HA17L431ALTP/432ALTP	MPAK
	1.24 V $\pm$ 1.5%	-30 to 50	HA17L431UP/432UP	UPAK
	2.5 V $\pm$ 1.0%	-50 to 50	HA17431VP	TO-92
			HA17431VLP	MPAK-5
			HA17431VUP/432VUP	UPAK
			HA17431VLTP/432VLTP	MPAK
36	2.5 V $\pm$ 1.0%	-50 to 50	HA17431HP	TO-92
			HA17431HLP	MPAK-5
			HA17431HUP/432HUP	UPAK
			HA17431HLTP/432HLTP	MPAK
40	2.5 V $\pm$ 2.2%	-100 to 150	HA17431PA	TO-92MOD
			HA17431PNA	TO-92
			HA17431UA/UPA	UPAK
			HA17432UA/UPA	UPAK
			HA17431FPA	SOP-8

Shunt Regulator IC Cross Reference (1)

Package	Standard Type Maker/Vref/Accuracy						
	Renesas 2.500 V ±1%	Toshiba 2.495 V ±2.2%	NEC 2.495 V ±2.2%	TI 2.495 V ±2.2%, ±1%	NS 2.495 V ±2.2%, 1%	ST 2.495 V ±2.2%, ±1%	ON 2.495 V ±2.2%, ±1%
TO-92	HA17431HP	TA76431S*1	μPC1093J	TL431CLP TL431ACLP TL431ILP TL431AILP	LM431ACZ LM431BCZ LM431AIZ LM431BIZ	TL431CZ TL431ACZ	TL431CLP TL431ILP TL431ACLP TL431AILP
UPAK	HA17431HUP	TA76431FR		TL431CPK TL431IPK			
	HA17432HUP	TA76431F	μPC1093T				
MPAK	HA17431HLTP						
	HA17432HLTP				LM431ACM3 LM431BCM3 LM431AIM3 LM431BIM3	TS2431ILT*2 TS2431AILT*3	
MPAK-5	HA17431HLP		μPC1093TA	TL431CDBV*4 TL431IDBV*4			

This cross reference is especially about the Voltage Reference and package.

*1: TO-92MOD

*2: TS2431ILT: 2.500 V±2%

*3: TS2431AILT: 2.500 V±1%

*4: Pin arrangement is different.

Shunt Regulator IC Cross Reference (2)

Low Voltage Type.
Maker/Vref/Accuracy

Package	Renesas 1.24 V ±1%	Toshiba 1.26 V ±1.4%	NEC 1.26 V ±2.4%	TI 1.24 V ±1.5%, ±1%	NS 1.24 V ±1.5%, 1%	ST 1.24 V ±2%, ±1%	ON 1.24 V ±1%
TO-92	HA17L431AP	TA76432S ^{*1}	μPC1944J	TLV431CLP TLV431ACLP TLV431ILP TLV431AILP	LMV431CZ LMV431ACZ LMV431AIZ LMV431AIZ	TS431CZ TS431ACZ	TLV431ALP
UPAK	HA17L431UP ^{*2}	TA76432FR	μPC1943T				
	HA17L432UP ^{*2}	TA76432F	μPC1944T				
MPAK	HA17L431ALTP						
	HA17L432ALTP						
MPAK-5	HA17L431ALP	TA76432FC ^{*3}		TLV431CDBV ^{*3} TLV431IDBV ^{*3} TLV431ACDBV ^{*3} TLV431AIDBV ^{*3}	LMV431CM5 ^{*3} LMV431ACM5 ^{*3} LMV431IM5 ^{*3} LMV431AIM5 ^{*3}	TS431ILT ^{*3} TS431AILT ^{*3}	TLV431ASN ^{*3}

This cross reference is especially about the Voltage Reference and package.

*1: TO-92MOD


*2: HA17L431UP, HA17L432UP: 1.24 V±1.5%

*3: Pin arrangement is different.

PFC + PWM ICs

Power Factor (PFC) + SW Reg. (PWM) ICs


Type	SW mode		f	Package	Main SW	Note
	V	C				
HA16141	—	✓	PFC: 100 kHz	DIP-16	Power MOS	Primary IC of HA16341
HA16142			PWM: 200 kHz	SOP-16		
HA16158	—	✓	PFC: 65 kHz	DIP-16	Power MOS	f adj., f-down
			PWM: 130 kHz	SOP-16		



1-chip solution

note) Input ac current becomes fine Sin-curve by PFC.


Note) HA16158 WS: 2Q/2002



PFC+PWM IC, HA16158 (1)

- Features
 - Can adjust frequency
 - f-down at light load
 - Soft start function
 - OVP for PWM



PFC+PWM IC, HA16158 (2)



- High noise immunity by synchronized between PFC and PWM
- Smaller capacitor on PFC out by PWM turn on when PFC turn off.

PFC+PWM IC, HA16158 (3)

Power saving at light load





Low Power Consumption.

Redundant Power Supply ICs.



Current Share and Load Regulation




DC/DC ICs


DC/DC Switching Regulator ICs

Type	SW mode		f	Package	Main SW	Note
	V	C				
HA16114	✓	—	600 kHz	DIP-16 SOP-16	Bip. Trs	Step down
HA16120	✓	—	600 kHz	DIP-16 SOP-16	Bip. Trs	Boost
HA17451A	✓	—	500 kHz	DIP-16 SOP-16	Bip power	TL451 Step down
HA16116	✓	—	600 kHz	DIP-16 SOP-16	Power MOS	Step down
HA16121	✓	—	600 kHz	DIP-16 SOP-16	Power MOS	Step down and boost

< Single ch >
< Dual ch >



Distributed Power Supply System



Note)


BMP: Board mounted Power Supply (DC/DC power supply)

VRM: Voltage Regulated Module

Half Bridge Power Supply IC

48 V Input DC/DC Power Supply IC

Type	SW mode		f	Package	Main SW	Note
	V	C				
HA16150	—	✓	1 MHz	DIP-16 TSSOP-16	Power MOS	48 V DC/DC




48 V Input DC/DC HA16150 (1)

- Features

- PWM Current mode
- FET driver
- 1 MHz max.
- Can adjust dead time
- Small and thin package: TSSOP-16

48 V Input DC/DC HA16150 (2)

Dual high current outputs for FET drive



for Wide Applications


Full Bridge Power Supply IC

48 V Input DC/DC Power Supply IC

Type	SW mode		f	Package	Main SW	Note
	V	C				
HA16163	—	✓	2 MHz	TSSOP20	Power MOS	Bridge cont. Sync.rect.

Note) WS: Available

for full bridge



48 V Input DC/DC HA16163 (1)

Preliminary

- Features

- 2 MHz max.



Miniaturized

- Phase-shift switching





- Synchronous rectification
with adjustable delay



High
Efficiency

48 V Input DC/DC HA16163 (2)

Phase shift switching → ZVS → low loss



Switching Power Supply Control ICs Products

Publication Date: April, 2003

Published by: Sales Strategic Planning Div.

Sales Management Business Unit

Renesas Technology Corp

Edited by: Technical Documentation Group

Renesas Kodaira Semiconductor Co., Ltd.

Copyright ©Renesas Technology Corp. 2003. All rights reserved. Printed in Japan

ADE-A09-301V(Z)



RENEASAS