


# DATA SHEET



## **BCX70 series** NPN general purpose transistors

Product data sheet  
Supersedes data of 1999 Apr 15

2004 Jan 16

## NPN general purpose transistors

## BCX70 series

## FEATURES

- Low current (max. 100 mA)
- Low voltage (max. 45 V).

## APPLICATIONS

- General purpose switching and amplification.

## DESCRIPTION

NPN transistor in a SOT23 plastic package.  
PNP complements: BCX71 series.

## MARKING

TYPE NUMBER	MARKING CODE <sup>(1)</sup>
BCX70G	AG*
BCX70H	AH*
BCX70J	AJ*
BCX70K	AK*

## Note

1. \* = p : Made in Hong Kong.
- \* = t : Made in Malaysia.
- \* = W : Made in China.

## PINNING

PIN	DESCRIPTION
1	base
2	emitter
3	collector




Fig.1 Simplified outline (SOT23) and symbol.

## ORDERING INFORMATION

TYPE NUMBER	PACKAGE		
	NAME	DESCRIPTION	VERSION
BCX70G	–	plastic surface mounted package; 3 leads	SOT23
BCX70H			
BCX70J			
BCX70K			

## NPN general purpose transistors

## BCX70 series

**LIMITING VALUES**

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
$V_{CBO}$	collector-base voltage	open emitter	–	45	V
$V_{CEO}$	collector-emitter voltage	open base	–	45	V
$V_{EBO}$	emitter-base voltage	open collector	–	5	V
$I_C$	collector current (DC)		–	100	mA
$I_{CM}$	peak collector current		–	200	mA
$I_{BM}$	peak base current		–	200	mA
$P_{tot}$	total power dissipation	$T_{amb} \leq 25 \text{ }^{\circ}\text{C}$	–	250	mW
$T_{stg}$	storage temperature		–65	+150	$^{\circ}\text{C}$
$T_j$	junction temperature		–	150	$^{\circ}\text{C}$
$T_{amb}$	operating ambient temperature		–65	+150	$^{\circ}\text{C}$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th(j-a)}$	thermal resistance from junction to ambient	note 1	500	K/W

**Note**

1. Transistor mounted on an FR4 printed-circuit board.

## NPN general purpose transistors

## BCX70 series

## CHARACTERISTICS

 $T_{amb} = 25^\circ C$  unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
$I_{CBO}$	collector cut-off current	$I_E = 0; V_{CB} = 45 V$	—	—	20	nA
		$I_E = 0; V_{CB} = 45 V; T_{amb} = 150^\circ C$	—	—	20	$\mu A$
$I_{EBO}$	emitter cut-off current	$I_C = 0; V_{EB} = 4 V$	—	—	20	nA
$h_{FE}$	DC current gain BCX70G	$I_C = 10 \mu A; V_{CE} = 5 V$	—	—	—	
	BCX70H		40	—	—	
	BCX70J		30	—	—	
	BCX70K		100	—	—	
	DC current gain BCX70G	$I_C = 2 mA; V_{CE} = 5 V$	120	—	220	
	BCX70H		180	—	310	
	BCX70J		250	—	460	
	BCX70K		380	—	630	
	DC current gain BCX70G	$I_C = 50 mA; V_{CE} = 1 V$	50	—	—	
	BCX70H		70	—	—	
	BCX70J		90	—	—	
	BCX70K		100	—	—	
$V_{CEsat}$	collector-emitter saturation voltage	$I_C = 10 mA; I_B = 0.25 mA$	50	—	350	mV
		$I_C = 50 mA; I_B = 1.25 mA$	100	—	550	mV
$V_{BEsat}$	base-emitter saturation voltage	$I_C = 10 mA; I_B = 0.25 mA$	600	—	850	mV
		$I_C = 50 mA; I_B = 1.25 mA$	700	—	1050	mV
$V_{BE}$	base-emitter voltage	$I_C = 10 \mu A; V_{CE} = 5 V$	—	520	—	mV
		$I_C = 2 mA; V_{CE} = 5 V$	550	650	750	mV
		$I_C = 50 mA; V_{CE} = 1 V$	—	780	—	mV
$C_c$	collector capacitance	$I_E = i_e = 0; V_{CB} = 10 V; f = 1 MHz$	—	1.7	—	pF
$C_e$	emitter capacitance	$I_C = i_c = 0; V_{EB} = 0.5 V; f = 1 MHz$	—	11	—	pF
$f_T$	transition frequency	$I_C = 10 mA; V_{CE} = 5 V; f = 100 MHz; note 1$	100	250	—	MHz
$F$	noise figure	$I_C = 200 \mu A; V_{CE} = 5 V; R_S = 2 k\Omega; f = 1 kHz; B = 200 Hz$	—	2	6	dB

## Note

1. Pulse test:  $t_p \leq 300 \mu s; \delta \leq 0.02$ .


## NPN general purpose transistors

## BCX70 series

## PACKAGE OUTLINE

Plastic surface-mounted package; 3 leads

SOT23



## DIMENSIONS (mm are the original dimensions)

UNIT	A	A <sub>1</sub> max.	b <sub>p</sub>	c	D	E	e	e <sub>1</sub>	H <sub>E</sub>	l <sub>p</sub>	Q	v	w
mm	1.1 0.9	0.1	0.48 0.38	0.15 0.09	3.0 2.8	1.4 1.2	1.9	0.95	2.5 2.1	0.45 0.15	0.55 0.45	0.2	0.1

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT23		TO-236AB				-04-11-04- 06-03-16

## NPN general purpose transistors

## BCX70 series

## DATA SHEET STATUS

DOCUMENT STATUS <sup>(1)</sup>	PRODUCT STATUS <sup>(2)</sup>	DEFINITION
Objective data sheet	Development	This document contains data from the objective specification for product development.
Preliminary data sheet	Qualification	This document contains data from the preliminary specification.
Product data sheet	Production	This document contains the product specification.

## Notes

1. Please consult the most recently issued document before initiating or completing a design.
2. The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

## DISCLAIMERS

**General** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions

above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

# **NXP Semiconductors**

## **Customer notification**

This data sheet was changed to reflect the new company name NXP Semiconductors, including new legal definitions and disclaimers. No changes were made to the technical content, except for package outline drawings which were updated to the latest version.

## **Contact information**

For additional information please visit: <http://www.nxp.com>

For sales offices addresses send e-mail to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

© NXP B.V. 2009

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

R75/04/pp7

Date of release: 2004 Jan 16

Document order number: 9397 750 12408

Founded by

**PHILIPS**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NXP](#):

[BCX70G T/R](#) [BCX70H T/R](#) [BCX70J T/R](#) [BCX70K T/R](#)