Maintenance Bypass Panels

APC Service Bypass Panel- 200/208/240V; 100A; MBB; Hardwire input; (3) L6-30R (3) L6-20R output

SBP10KRMT4U

Email Technical Specifications

Printer Friendly

Product Category

- Computer and Peripheral (5)
- Home UPS (2)
- Network and Server (3)
- Data Center and Facility 3 Phase (14)
- UPS Management (7)

Return to Uninterruptible Power Supply (UPS)

More Images

APC Maintenance Bypass Panels , Input: 200V, 208V , Input Connections: Hard Wire 3-wire (2PH + G) , Output: 200V, 208V , Output Connections: NEMA L6-20R,NEMA L6-30R

Includes: Installation guide, Rack Mounting brackets, User Manual

Standard Lead Time: Usually in Stock

Be the first to write a review

Share this Product:

Technical Specifications | Product Overview | Documentation | Ratings and Reviews

Output	
Nominal Output Voltage	200V,208V
Maximum Total Current Draw per Phase	100A
Output Connections	(3) NEMA L6-20R (3) NEMA L6-30R
Overload Protection	Yes
Input	
Nominal Input Voltage	200V,208V
Input Frequency	50/60 Hz
Input Connections	Hard Wire 3-wire (2PH + G)
Acceptable Input Voltage	200-240 VAC
Maximum Line Current per phase	100A
Maximum Input Current per phase	100A
Load Capacity	20 kVA
Load Power Factor Range	0 to 1
Physical	
Net Weight	21.82 KG
Maximum Height	178.00 mm
Maximum Width	432.00 mm
Maximum Depth	673.00 mm
Shipping Weight	31.82 KG
Shipping Height	305.00 mm
Shipping Width	610.00 mm
Shipping Depth	991.00 mm
Color	Black
Units per Pallet	6.00
Environmental	
Operating Environment	-20 - 50 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-4500 meters
Storage Temperature	-40 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Conformance	
Regulatory Approvals	CSA,EN 60950,GOST,IEC 60950,IEC 60950,UL 1778
Standard Warranty	2 years (parts only)