
IEM-LX

AMD LX800 Highly Integrated ETX Module

ETX CPU Module with AMD LX800 CPU onboard, USB 2.0, LAN & Audio



AMD LX800 onboard CPU

Solder Side



200-pin DDR

Feature

- 1. ETX (Embedded Technology eXtended) form factor for flexible base board design
- 2. AMD LX800 low power fanless processor module
- 3. DDR 333/400MHz SO-DIMM SDRAM up to 1GB
- 4. USB 2.0, LAN, Audio ready for base board

Specification

- **♦** CPU
- AMD LX800 processor
- ◆ System Chipset AMD CS5536
- **♦ BIOS**
 - **AWARD**
- ◆ System Memory
 - 1 x 200-pin DDR 400/333MHz SO-DIMM SDRAM up to 1GB
- ◆ Ethernet
 - 10/100Base-T RTL8100C
- I/O
- 4 x USB 2.0
- 1 x LPT
- 1 x CFII
- 1 x IDE
- Multi COM ports supports by base board
- Audio
- AC'97 Codec Realtek ALC23A
- ◆ Super I/O W83627EHG









- ◆ Display CRT integrated in AMD LX800
- TTL/ LVDS
- 24-bit TTL integrated in AMD LX800 18-bit LVDS
- ◆ Watchdog Timer
 - Software programable supports 1-255 sec. system reset
- Power Supply
- AT/ATX support
- ◆ Power Consumption
 - +5V@0.92A
 - (AMD LX-800 CPU with DDR 333MHz 256MB RAM)
- ◆ Temperature
- Operation: 0 ~ 60° C (32 ~ 140° F)
- Humidity
 - Operation: 5% ~ 95%, non-condensing
- Dimension
- 95 mm x 114 mm
- ◆ Weight
- GW: 650g; NW: 250g


IEM-LX Advantages

ETX is an industry standard System-On-Module (SOM) technology. By choosing integrated CPU and memory module and customized baseboard with I/O functionality, embedded product solutions could be incredibly efficiently and economically.

Benefits

- Time Advantage!
- Complete PC functionality with x86 architecture
- · Cost saving in engineering and developing
- · Time to market in software designing and scheduling
- Design Advantage!
- · Customize designing in reliable connectors
- · Easy upgrading with no redesign needed in the event of component end of life
- Extremely slim low power fanless design
- Installation/Size Advantage!
- Gas-proof connectors and mounting holes enable rugged applications.

Dimension



Packing List

1 x IEM-LX single board computer	1 x Utility CD
1 x Mini jumper pack	1 x QIG (quick installation guide)

Ordering Information

Part No.	Description
IEM-LX-800-R10	AMD LX800 500MHz processor, CRT/LCD, LAN & Audio
IEM-DB-7S-R20	ATX size 7-slot ETX baseboard for ETX CPU board



Headquarter

IEI Technology Corp.

TEL: +886-2-86916798 FAX: +886-2-66160028 sales@ieiworld.com www.ieiworld.com No. 29, Jhongsing Rd.,Sijhih City,Taipei County, 221, Taiwan

America-United States

IEI Technology USA Corp.

TEL: +1-562-690-6677 FAX: +1-562-690-0898 sales@usa.ieiworld.com www.usa.ieiworld.com 515 N. Puente St., Brea, CA 92821

China

Extremely Slim Design, Easy Integration

Armorlink SH Corp.

TEL: +86-021-54429000 FAX: +86-021-54429100 sales@ieiworld.com.cn www.ieiworld.com.cn No.515, Shenfu Road, Minhang District, Shanghai, China