

TOSHIBA DIODE SILICON EPITAXIAL SCHOTTKY BARRIER TYPE


1SS369

LOW VOLTAGE HIGH SPEED SWITCHING

- Small Package
- Low Forward Voltage : $V_F(3)=0.54V$ (TYP.)
- Low Reverse Current : $I_R=5\mu A$ (MAX.)

MAXIMUM RATINGS ($T_a=25^{\circ}C$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Maximum (Peak) Reverse Voltage	V_{RM}	45	V
Reverse Voltage	V_R	40	V
Maximum (Peak) Forward Current	I_{FM}	300	mA
Average Forward Current	I_O	100	mA
Surge Current (10ms)	I_{FSM}	1	A
Power Dissipation	$P_{\ast}$	150	mW
Junction Temperature	T_j	125	$^{\circ}C$
Storage Temperature Range	T_{stg}	$-55\sim 125$	$^{\circ}C$
Operating Temperature Range	T_{opr}	$-40\sim 100$	$^{\circ}C$



Weight : 1.9mg

※ Mounted on a glass epoxy circuit board of 20×20mm, pad dimension of 4×4mm.


ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}C$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	$V_F(1)$	$I_F=1mA$	—	0.28	—	V
	$V_F(2)$	$I_F=10mA$	—	0.36	—	
	$V_F(3)$	$I_F=100mA$	—	0.54	0.60	
Reverse Current	I_R	$V_R=40V$	—	—	5	μA
Total Capacitance	C_T	$V_R=0, f=1MHz$	—	18	25	pF

PIN ASSIGNMENT (TOP VIEW)






MARKING



961001EAA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.



961001EAA2'

- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.