

N-Channel Power MOSFET

800V, 3A, 4.2Ω

FEATURES





- Low $R_{DS(ON)}$ 3.3Ω (Typ.)
- Low gate charge typical @ 19nC (Typ.)
- Low C_{rss} typical @ 10.2pF (Typ.)
- Improved dv/dt capability

APPLICATION

- Power Supply
- Lighting

KEY PERFORMANCE PARAMETERS

PARAMETER	VALUE	UNIT
V_{DS}	800	V
$R_{DS(on)}$ (max)	4.2	Ω
Q_g	19	nC



Notes: MSL 3 (Moisture Sensitivity Level) for TO-252 (D-PAK) per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT			UNIT
			IPAK/DPAK	ITO-220	TO-220	
Drain-Source Voltage		V _{DS}	800			V
Gate-Source Voltage		V _{GS}	±30			V
Continuous Drain Current ^(Note 1)	T _C = 25°C	I _D	3			A
	T _C = 100°C		1.83			
Pulsed Drain Current ^(Note 2)		I _{DM}	12			A
Single Pulsed Avalanche Energy ^(Note 3)		E _{AS}	48			mJ
Single Pulsed Avalanche Current ^(Note 3)		I _{AS}	3			A
Repetitive Avalanche Energy ^(Note 3)		E _{AR}	9.4			mJ
Repetitive Avalanche Energy ^(Note 4)		dV/dt	4.5			V/ns
Total Power Dissipation @ T _C = 25°C		P _{DTOT}	94	32	94	W
Operating Junction and Storage Temperature Range		T _J , T _{STG}	- 55 to +150			°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	LIMIT			UNIT
		IPAK/DPAK	ITO-220	TO-220	
Junction to Case Thermal Resistance	$R_{\theta Jc}$	1.33	3.9	1.33	°C/W
Junction to Ambient Thermal Resistance	$R_{\theta JA}$	110	62.5		°C/W

Notes: $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins. $R_{\theta JA}$ is guaranteed by design while $R_{\theta CA}$ is determined by the user's board design. $R_{\theta JA}$ shown below for single device operation on FR-4 PCB in still air

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static ^(Note 5)						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	BV _{DSS}	800	--	--	V
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	V _{GS(TH)}	2	--	4	V
Gate Body Leakage	V _{GS} = ±30V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V _{DS} = 800V, V _{GS} = 0V	I _{DSS}	--	--	10	μA
Drain-Source On-State Resistance	V _{GS} = 10V, I _D = 1.5A	R _{DS(ON)}	--	3.3	4.2	Ω
Forward Transfer Conductance	V _{DS} = 30V, I _D = 1.5A	g _{fs}	--	3.7	--	S
Dynamic ^(Note 6)						
Total Gate Charge	V _{DS} = 640V, I _D = 3A, V _{GS} = 10V	Q _g	--	19	--	nC
Gate-Source Charge		Q _{gs}	--	4	--	
Gate-Drain Charge		Q _{gd}	--	7.6	--	
Input Capacitance	V _{DS} = 25V, V _{GS} = 0V, f = 1.0MHz	C _{iss}	--	696	--	pF
Output Capacitance		C _{oss}	--	65	--	
Reverse Transfer Capacitance		C _{rss}	--	10.2	--	
Gate Resistance	F = 1MHz, open drain	R _g	--	3.2	--	Ω
Switching ^(Note 7)						
Turn-On Delay Time	V _{GS} = 10V, I _D = 3A, V _{DD} = 400V, R _G =25Ω	t _{d(on)}	--	48	--	ns
Turn-On Rise Time		t _r	--	36	--	
Turn-Off Delay Time		t _{d(off)}	--	106	--	
Turn-Off Fall Time		t _f	--	41	--	
Source-Drain Diode ^(Note 5)						
Source Current	Integral reverse diode in the MOSFET	I _S	--	--	3	A
Source Current (Pulse)		I _{SM}	--	--	12	A
Diode Forward Voltage	I _S = 3A, V _{GS} = 0V	V _{SD}	--	--	1.5	V
Reverse Recovery Time	V _{GS} = 0V, I _S =3A,	t _{rr}	--	370	--	ns
Reverse Recovery Charge	dI _F /dt = 100A/us	Q _{rr}	--	1.8	--	μC

Notes:

- Current limited by package
- Pulse width limited by the maximum junction temperature
- $L = 10\text{mH}, I_{AS} = 3A, V_{DD} = 50V, R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$
- $I_{SD} \leq 3A, dI/dt \leq 200A/\mu s, V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$
- Pulse test: $PW \leq 300\mu s$, duty cycle $\leq 2\%$
- For DESIGN AID ONLY, not subject to production testing.
- Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

PART NO.	PACKAGE	PACKING
TSM3N80CZ C0G	TO-220	50pcs / Tube
TSM3N80CI C0G	ITO-220	50pcs / Tube
TSM3N80CH C5G	TO-251 (IPAK)	75pcs / Tube
TSM3N80CP ROG	TO-252 (DPAK)	2,500pcs / 13" Reel


Note:

1. Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
2. Halogen-free according to IEC 61249-2-21 definition


CHARACTERISTICS CURVES

($T_C = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate Charge



On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Voltage




CHARACTERISTICS CURVES

($T_c = 25^\circ\text{C}$ unless otherwise noted)


Drain Current vs. Case Temperature




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area(TO-220, I/D-PAK)



Capacitance vs. Drain-Source Voltage




Maximum Safe Operating Area(ITO-220)




CHARACTERISTICS CURVES

($T_C = 25^\circ\text{C}$ unless otherwise noted)

Normalized Thermal Transient Impedance, Junction-to-Ambient (TO-220, I/D-PAK)




Normalized Thermal Transient Impedance, Junction-to-Ambient (ITO-220)




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-220



MARKING DIAGRAM




Y = Year Code
M = Month Code for Halogen Free Product

O = Jan	P = Feb	Q = Mar	R = Apr
S = May	T = Jun	U = Jul	V = Aug
W = Sep	X = Oct	Y = Nov	Z = Dec


L = Lot Code (1~9, A~Z)

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

ITO-220




MARKING DIAGRAM




- G** = Halogen Free
- Y** = Year Code
- WW** = Week Code (01~52)
- F** = Factory Code

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-251(IPAK)




MARKING DIAGRAM




Y = Year Code
M = Month Code for Halogen Free Product
O =Jan **P** =Feb **Q** =Mar **R** =Apr
S =May **T** =Jun **U** =Jul **V** =Aug
W =Sep **X** =Oct **Y** =Nov **Z** =Dec
L = Lot Code (1~9, A~Z)

PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)


TO-252(DPAK)



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



Y = Year Code

M = Month Code for Halogen Free Product

O =Jan **P** =Feb **Q** =Mar **R** =Apr

S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec

L = Lot Code (1~9, A~Z)

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.