




# BCM1480

## PRODUCT Brief



### QUAD-CORE 64-BIT MIPS® PROCESSOR WITH SPI-4/HT (NEW!)

#### FEATURES

- **Four 64-bit MIPS® CPUs, scalable from 800 MHz-1.2 GHz**
  - Quad-issue in-order pipeline with dual-execute and dual-memory pipes
  - Enhanced skew pipeline enables a zero load-to-use penalty
  - 32-KB instruction cache and 32-KB data cache (ECC protected)
- **Fast on-chip multiprocessor bus**
  - Connects the CPUs, L2 cache, memory controller, and I/O bridges
  - Runs at half the CPU core frequency and is 256 bits wide
- **On-chip L2 cache**
  - 1 MB shared by four CPUs and I/O agents
  - Eight-way associative, ECC protected
  - Any way can be programmed as fast on-chip RAM
- **DDR memory controller**
  - Memory bandwidth as high as 100 Gbps
  - Configurable as 2x64-bit or 4x32-bit wide channels
  - Runs up to 400-MHz clock rate, 800-MHz data rate
  - Support for DDR1, DDR2, and FCRAM
- **Three independent, 19.2 full-duplex ports**
  - Configurable as 16/8-bit HyperTransport™ (HT) (formerly LDT) or Channelized OIF SPI-4 Phase 2
  - Runs up to 600 MHz DDR for aggregate bandwidth of 38.4 Gbps per port
  - Includes Intelligent Hash and Filter Engine on each port to route packets
  - Supports glueless connectivity of multiple **BCM1480** devices to build a distributed shared-memory system with hardware-based coherency
- **On-chip switch**
  - Connects multiprocessor bus to high-speed interfaces
  - 256-Gbps bisection bandwidth
  - Supports both packet transfer and memory transactions
- **Integrated network and system I/O**
  - Four Gigabit-Ethernet MACs configurable as packet FIFO interfaces
  - 64-bit PCI-X interface at 133 MHz
  - Generic I/O for direct connect to boot ROM, flash memory
  - Two SMBus serial configuration interfaces
  - PCMCIA control interface and up to 16 interrupts
  - Four UART interfaces
- **On-chip debug capability**
  - EJTAG
  - Bus trace unit (internal logic analyzer)
- **Support for leading operating systems, including VxWorks®, Linux®, QNX®, and NetBSD**
- **Evaluation board platform available with samples (includes tools, firmware, and software drivers)**


#### SUMMARY OF BENEFITS

- **Industry-leading performance**
  - 2.5 Dhrystone MIPS/MHz per CPU
  - 20 Million packets per second of L3 forwarding
  - 128 Gbps (@ 1.0 GHz) on-chip bus bandwidth, with 100 Gbps memory bandwidth and over 145 Gbps I/O Bandwidth
- **Low-power dissipation of 23W @ 1 GHz**
- **High functional integration, reducing overall system cost**
- **Programming ease and flexibility based on MIPS64™ instruction set architecture (ISA)**
- **Software compatible with BCM1250 and BCM112x**
- **Broad tools and system software support**


#### APPLICATIONS

Because of its world-class performance, power efficiency, and integration, the **BCM1480** processor is ideal for a broad variety of applications, including:

- Enterprise-class routers and switches
- Multifunction security platforms (VPN/SSL/IDS)
- High-end RAID Arrays
- SAN routers/gateways/switches
- Wireless infrastructure platforms (e.g., RNC, GGSN, MSC)
- High-density computing



## OVERVIEW



The **BCM1480** device is an MIPS64 processor core-based system-on-a-chip (SOC) that offers industry-leading performance, high functional integration, and low-power levels required by next-generation computing, storage, and networking applications.

The **BCM1480** is a scalable chip multiprocessor (CMP) system consisting of four Broadcom SB-1 high-performance MIPS64 CPUs, a shared 1-MB L2 cache, a DDR memory controller, and integrated I/O. All major blocks of the processor are connected together via the ZBbus, which is a high-speed, split-transaction multiprocessor bus. The bus implements the standard MESI protocol to ensure coherency between the four CPUs, L2 cache, I/O agents, and memory. In addition, the **BCM1480** supports an interchip ccNUMA protocol for cache coherent distributed shared memory systems. The three high-speed HT ports provide interchip communications to other **BCM1480** processors or HT bridging I/O chips. Each port can optionally be configured as an SPI-4 Phase 2 packet interface for connectivity to 10 Gbps network devices. Four Gigabit-Ethernet MACs (10/100/1000) enable easy interfacing to LANs or control backplanes. To enable higher data rates (or in cases where Ethernet protocol processing is not required), the Gigabit-Ethernet MACs can be configured as 8-bit and/or 16-bit packet FIFOs. The **BCM1480** also integrates a 64-bit, 133-MHz PCI-X local bus for direct connection to I/O devices. Four serial ports are available for use as UARTs for console ports.

To enable low-chip count systems, the **BCM1480** also includes a configurable generic bus that allows glueless connection of a boot ROM or flash memory and simple I/O peripherals. On-chip debug, trace, and performance monitoring functions assist both hardware and software designers in debugging and tuning the system. The system can be run in either big-endian or little-endian mode.

### Implementation of MIPS64 ISA

The SB-1 CPU core is a high-performance implementation of the standard MIPS64 ISA that incorporates the MIPS-3D and MIPS-MDMX application-specific extensions (ASEs). The core supports a 4-issue enhanced skew pipeline and can dispatch up to two memory and two ALU (integer, floating point, MDMX, or MIPS-3D) instructions per cycle.

### Next Generation Broadband Processors

	BCM1255	BCM1280	BCM1455	BCM1480
<b># of CPUs</b>	2	2	4	4
<b>L2 Cache</b>	512 KB	1 MB	1 MB	1 MB
<b>DDR2 Support</b>	Yes	Yes	Yes	Yes
<b># of MACs</b>	4 GMII	4 GMII	4 GMII	4 GMII
<b>PCI-X</b>	1 x 64-bit	1 x 64-bit	1 x 64-bit	1 x 64-bit
<b># of SPI-4/HT Ports</b>	0	3	0	3

**Broadcom**®, the pulse logo, and **Connecting everything**® are trademarks of Broadcom Corporation and/or its subsidiaries in the United States and certain other countries. All other trademarks are the property of their respective owners.

Connecting  
everything®

### BROADCOM CORPORATION

16215 Alton Parkway, P.O. Box 57013  
Irvine, CA 92619-7013

© 2004 by BROADCOM CORPORATION. All rights reserved.

