

# NTD110N02R, STD110N02R

## MOSFET – Power, N-Channel, DPAK

24 V, 110 A

### Features

- Planar HD3e Process for Fast Switching Performance
- Low  $R_{DS(on)}$  to Minimize Conduction Loss
- Low  $C_{iss}$  to Minimize Driver Loss
- Low Gate Charge
- Optimized for High Side Switching Requirements in High-Efficiency DC-DC Converters
- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise noted)

| Rating                                                                                                                                                                                                                  | Symbol          | Value          | Unit               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------------|--------------------|
| Drain-to-Source Voltage                                                                                                                                                                                                 | $V_{DS}$        | 24             | V                  |
| Gate-to-Source Voltage – Continuous                                                                                                                                                                                     | $V_{GS}$        | $\pm 20$       | V                  |
| Thermal Resistance – Junction-to-Case                                                                                                                                                                                   | $R_{\theta JC}$ | 1.35           | $^\circ\text{C/W}$ |
| Total Power Dissipation @ $T_C = 25^\circ\text{C}$                                                                                                                                                                      | $P_D$           | 110            | W                  |
| Drain Current                                                                                                                                                                                                           | $I_D$           | 110            | A                  |
| – Continuous @ $T_C = 25^\circ\text{C}$ , Chip                                                                                                                                                                          | $I_D$           | 110            | A                  |
| – Continuous @ $T_C = 25^\circ\text{C}$                                                                                                                                                                                 | $I_D$           | 110            | A                  |
| Limited by Package                                                                                                                                                                                                      | $I_D$           | 32             | A                  |
| – Continuous @ $T_A = 25^\circ\text{C}$                                                                                                                                                                                 | $I_D$           | 32             | A                  |
| Limited by Wires                                                                                                                                                                                                        | $I_D$           | 110            | A                  |
| – Single Pulse ( $t_p = 10 \mu\text{s}$ )                                                                                                                                                                               | $I_D$           | 110            | A                  |
| Thermal Resistance                                                                                                                                                                                                      | $R_{\theta JA}$ | 52             | $^\circ\text{C/W}$ |
| – Junction-to-Ambient (Note 1)                                                                                                                                                                                          | $P_D$           | 2.88           | W                  |
| – Total Power Dissipation @ $T_A = 25^\circ\text{C}$                                                                                                                                                                    | $I_D$           | 17.5           | A                  |
| – Drain Current – Continuous @ $T_A = 25^\circ\text{C}$                                                                                                                                                                 | $I_D$           | 17.5           | A                  |
| Thermal Resistance                                                                                                                                                                                                      | $R_{\theta JA}$ | 100            | $^\circ\text{C/W}$ |
| – Junction-to-Ambient (Note 2)                                                                                                                                                                                          | $P_D$           | 1.5            | W                  |
| – Total Power Dissipation @ $T_A = 25^\circ\text{C}$                                                                                                                                                                    | $I_D$           | 12.5           | A                  |
| – Drain Current – Continuous @ $T_A = 25^\circ\text{C}$                                                                                                                                                                 | $I_D$           | 12.5           | A                  |
| Operating and Storage Temperature Range                                                                                                                                                                                 | $T_J, T_{stg}$  | $-55$ to $175$ | $^\circ\text{C}$   |
| Single Pulse Drain-to-Source Avalanche Energy – Starting $T_J = 25^\circ\text{C}$<br>( $V_{DD} = 50 \text{ Vdc}$ , $V_{GS} = 10 \text{ Vdc}$ ,<br>$I_L = 15.5 \text{ Apk}$ , $L = 1.0 \text{ mH}$ , $R_G = 25 \Omega$ ) | $E_{AS}$        | 120            | mJ                 |
| Maximum Lead Temperature for Soldering Purposes, ( $1/8"$ from case for 10 s)                                                                                                                                           | $T_L$           | 260            | $^\circ\text{C}$   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



1. When surface mounted to an FR4 board using 0.5 sq in drain pad size.
2. When surface mounted to an FR4 board using the minimum recommended pad size.



ON Semiconductor®


<http://onsemi.com>

| $V_{(BR)DSS}$ | $R_{DS(on)}$ TYP      | $I_D$ MAX |
|---------------|-----------------------|-----------|
| 24 V          | 4.1 m $\Omega$ @ 10 V | 110 A     |



DPAK  
CASE 369AA  
(Surface Mount)  
STYLE 2

### MARKING DIAGRAM & PIN ASSIGNMENT



A = Assembly Location\*  
Y = Year  
WW = Work Week  
T110N2 = Device Code  
G = Pb-Free Package

\* The Assembly Location code (A) is front side optional. In cases where the Assembly Location is stamped in the package, the front side assembly code may be blank.

### ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

# NTD110N02R, STD110N02R

## ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25°C unless otherwise noted)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|                                                                                                                                                               |                      |    |    |           |       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----|----|-----------|-------|
| Drain-to-Source Breakdown Voltage (Note 3)<br>(V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA)                                                                | V <sub>(BR)DSS</sub> | 24 | 28 |           | V     |
| Positive Temperature Coefficient                                                                                                                              |                      |    | 15 |           | mV/°C |
| Zero Gate Voltage Drain Current<br>(V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 0 V)<br>(V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125°C) | I <sub>DSS</sub>     |    |    | 1.5<br>10 | μA    |
| Gate-Body Leakage Current (V <sub>GS</sub> = ±20 V, V <sub>DS</sub> = 0 V)                                                                                    | I <sub>GSS</sub>     |    |    | ±100      | nA    |

### ON CHARACTERISTICS (Note 3)

|                                                                                                                                                                                                                                                              |                     |     |                          |            |       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-----|--------------------------|------------|-------|
| Gate Threshold Voltage (Note 3)<br>(V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA)                                                                                                                                                             | V <sub>GS(th)</sub> | 1.0 | 1.5                      | 2.0        | V     |
| Negative Threshold Temperature Coefficient                                                                                                                                                                                                                   |                     |     | 5.0                      |            | mV/°C |
| Static Drain-to-Source On-Resistance (Note 3)<br>(V <sub>GS</sub> = 10 V, I <sub>D</sub> = 110 A)<br>(V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 55 A)<br>(V <sub>GS</sub> = 10 V, I <sub>D</sub> = 20 A)<br>(V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 20 A) | R <sub>DS(on)</sub> |     | 4.1<br>5.5<br>3.9<br>5.5 | 4.6<br>6.2 | mΩ    |
| Forward Transconductance (V <sub>DS</sub> = 10 V, I <sub>D</sub> = 15 A) (Note 3)                                                                                                                                                                            | g <sub>FS</sub>     |     | 44                       |            | Mhos  |

### DYNAMIC CHARACTERISTICS

|                      |                                                              |                  |  |      |      |    |
|----------------------|--------------------------------------------------------------|------------------|--|------|------|----|
| Input Capacitance    | (V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 0 V, f = 1.0 MHz) | C <sub>iss</sub> |  | 2710 | 3440 | pF |
| Output Capacitance   |                                                              | C <sub>oss</sub> |  | 1105 | 1670 |    |
| Transfer Capacitance |                                                              | C <sub>rss</sub> |  | 450  | 640  |    |

### SWITCHING CHARACTERISTICS (Note 4)

|                     |                                                                                                    |                     |  |      |    |    |
|---------------------|----------------------------------------------------------------------------------------------------|---------------------|--|------|----|----|
| Turn-On Delay Time  | (V <sub>GS</sub> = 10 V, V <sub>DD</sub> = 10 V,<br>I <sub>D</sub> = 40 A, R <sub>G</sub> = 3.0 Ω) | t <sub>d(on)</sub>  |  | 11   | 22 | ns |
| Rise Time           |                                                                                                    | t <sub>r</sub>      |  | 39   | 80 |    |
| Turn-Off Delay Time |                                                                                                    | t <sub>d(off)</sub> |  | 27   | 40 |    |
| Fall Time           |                                                                                                    | t <sub>f</sub>      |  | 21   | 40 |    |
| Gate Charge         | (V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 40 A,<br>V <sub>DS</sub> = 10 V) (Note 3)               | Q <sub>T</sub>      |  | 23.6 | 28 | nC |
|                     |                                                                                                    | Q <sub>GS</sub>     |  | 5.1  |    |    |
|                     |                                                                                                    | Q <sub>GD</sub>     |  | 11   |    |    |

### SOURCE-DRAIN DIODE CHARACTERISTICS

|                                |                                                                                                                                                                                     |                 |  |                      |     |    |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|--|----------------------|-----|----|
| Forward On-Voltage             | (I <sub>S</sub> = 20 A, V <sub>GS</sub> = 0 V) (Note 3)<br>(I <sub>S</sub> = 55 A, V <sub>GS</sub> = 0 V)<br>(I <sub>S</sub> = 20 A, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 125°C) | V <sub>SD</sub> |  | 0.82<br>0.99<br>0.65 | 1.2 | V  |
| Reverse Recovery Time          | (I <sub>S</sub> = 30 A, V <sub>GS</sub> = 0 V,<br>di <sub>S</sub> /dt = 100 A/μs) (Note 3)                                                                                          | t <sub>rr</sub> |  | 36.5                 |     | ns |
|                                |                                                                                                                                                                                     | t <sub>a</sub>  |  | 30                   |     |    |
|                                |                                                                                                                                                                                     | t <sub>b</sub>  |  | 25                   |     |    |
| Reverse Recovery Stored Charge |                                                                                                                                                                                     | Q <sub>rr</sub> |  | 0.048                |     | μC |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.

4. Switching characteristics are independent of operating junction temperatures.

# NTD110N02R, STD110N02R




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance versus Gate-to-Source Voltage




Figure 4. On-Resistance versus Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature









Figure 6. Drain-to-Source Leakage Current versus Voltage

# NTD110N02R, STD110N02R



## NTD110N02R, STD110N02R





Figure 12. Thermal Response

### ORDERING INFORMATION


| Device         | Package           | Shipping <sup>†</sup> |
|----------------|-------------------|-----------------------|
| NTD110N02RT4G  | DPAK<br>(Pb-Free) | 2500 / Tape & Reel    |
| STD110N02RT4G* | DPAK<br>(Pb-Free) | 2500 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.



SCALE 1:1



STYLE 1:  
PIN 1. BASE  
2. COLLECTOR  
3. EMITTER  
4. COLLECTOR

STYLE 2:  
PIN 1. GATE  
2. DRAIN  
3. SOURCE  
4. DRAIN

STYLE 3:  
PIN 1. ANODE  
2. CATHODE  
3. ANODE  
4. CATHODE


STYLE 4:  
PIN 1. CATHODE  
2. ANODE  
3. GATE  
4. ANODE

STYLE 5:  
PIN 1. GATE  
2. ANODE  
3. CATHODE  
4. ANODE

STYLE 6:  
PIN 1. MT1  
2. MT2  
3. GATE  
4. MT2

STYLE 7:  
PIN 1. GATE  
2. COLLECTOR  
3. EMITTER  
4. COLLECTOR

#### SOLDERING FOOTPRINT\*



SCALE 3:1 (mm/inches)


\*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

#### NOTES:

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
- CONTROLLING DIMENSION: INCHES.
- THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS b3, L3 and Z.
- DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.006 INCHES PER SIDE.
- DIMENSIONS D AND E ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
- DATUMS A AND B ARE DETERMINED AT DATUM PLANE H.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.086     | 0.094 | 2.18        | 2.38  |
| A1  | 0.000     | 0.005 | 0.00        | 0.13  |
| b   | 0.025     | 0.035 | 0.63        | 0.89  |
| b2  | 0.030     | 0.045 | 0.76        | 1.14  |
| b3  | 0.180     | 0.215 | 4.57        | 5.46  |
| c   | 0.018     | 0.024 | 0.46        | 0.61  |
| c2  | 0.018     | 0.024 | 0.46        | 0.61  |
| D   | 0.235     | 0.245 | 5.97        | 6.22  |
| E   | 0.250     | 0.265 | 6.35        | 6.73  |
| e   | 0.090 BSC |       | 2.29 BSC    |       |
| H   | 0.370     | 0.410 | 9.40        | 10.41 |
| L   | 0.055     | 0.070 | 1.40        | 1.78  |
| L1  | 0.108 REF |       | 2.74 REF    |       |
| L2  | 0.020 BSC |       | 0.51 BSC    |       |
| L3  | 0.035     | 0.050 | 0.89        | 1.27  |
| L4  |           | 0.040 |             | 1.01  |
| Z   | 0.155     |       | 3.93        |       |

#### GENERIC MARKING DIAGRAM\*



XXXXXX = Device Code  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
WW = Work Week  
G = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking.

|                  |                     |                                                                                                                                                                                     |
|------------------|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON13126D         | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | DPAK (SINGLE GAUGE) | PAGE 1 OF 1                                                                                                                                                                         |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)