

## 74F153 Dual 4-Input Multiplexer

### General Description


The F153 is a high-speed dual 4-input multiplexer with common select inputs and individual enable inputs for each section. It can select two lines of data from four sources. The two buffered outputs present data in the true (non-inverted) form. In addition to multiplexer operation, the F153 can generate any two functions of three variables.

### Ordering Code:


| Order Number | Package Number | Package Description                                                         |
|--------------|----------------|-----------------------------------------------------------------------------|
| 74F153SC     | M16A           | 16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow |
| 74F153SJ     | M16D           | 16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74F153PC     | N16E           | 16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide       |

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

### Logic Symbols



### Connection Diagram



## Unit Loading/Fan Out

| Pin Names       | Description                      | U.L.<br>HIGH/LOW | Input $I_{IH}/I_{IL}$<br>Output $I_{OH}/I_{OL}$ |
|-----------------|----------------------------------|------------------|-------------------------------------------------|
| $I_{0a}-I_{3a}$ | Side A Data Inputs               | 1.0/1.0          | 20 $\mu A$ /–0.6 mA                             |
| $I_{0b}-I_{3b}$ | Side B Data Inputs               | 1.0/1.0          | 20 $\mu A$ /–0.6 mA                             |
| $S_0, S_1$      | Common Select Inputs             | 1.0/1.0          | 20 $\mu A$ /–0.6 mA                             |
| $\bar{E}_a$     | Side A Enable Input (Active LOW) | 1.0/1.0          | 20 $\mu A$ /–0.6 mA                             |
| $\bar{E}_b$     | Side B Enable Input (Active LOW) | 1.0/1.0          | 20 $\mu A$ /–0.6 mA                             |
| $Z_a$           | Side A Output                    | 50/33.3          | –1 mA/20 mA                                     |
| $Z_b$           | Side B Output                    | 50/33.3          | –1 mA/20 mA                                     |

## Truth Table

| Select Inputs |       | Inputs (a or b) |       |       |       |       |     | Output |
|---------------|-------|-----------------|-------|-------|-------|-------|-----|--------|
| $S_0$         | $S_1$ | $\bar{E}$       | $I_0$ | $I_1$ | $I_2$ | $I_3$ | $Z$ |        |
| X             | X     | H               | X     | X     | X     | X     | L   |        |
| L             | L     | L               | L     | X     | X     | X     | L   |        |
| L             | L     | L               | H     | X     | X     | X     | H   |        |
| H             | L     | L               | X     | L     | X     | X     | L   |        |
| H             | L     | L               | X     | H     | X     | X     | H   |        |
| L             | H     | L               | X     | X     | L     | X     | L   |        |
| L             | H     | L               | X     | X     | H     | X     | H   |        |
| H             | H     | L               | X     | X     | X     | L     | L   |        |
| H             | H     | L               | X     | X     | X     | H     | H   |        |

H = HIGH Voltage Level  
L = LOW  
X = Immaterial

## Functional Description


The F153 is a dual 4-input multiplexer. It can select two bits of data from up to four sources under the control of the common Select inputs ( $S_0, S_1$ ). The two 4-input multiplexer circuits have individual active LOW Enables ( $\bar{E}_a, \bar{E}_b$ ) which can be used to strobe the outputs independently. When the Enables ( $\bar{E}_a, \bar{E}_b$ ) are HIGH, the corresponding outputs ( $Z_a, Z_b$ ) are forced LOW. The F153 is the logic implementation of a 2-pole, 4-position switch, where the position of the switch is determined by the logic levels supplied to the two Select inputs. The logic equations for the outputs are as follows:

$$Z_a = \bar{E}_a \cdot (I_{0a} \cdot \bar{S}_1 \cdot \bar{S}_0 + I_{1a} \cdot \bar{S}_1 \cdot S_0 + I_{2a} \cdot S_1 \cdot \bar{S}_0 + I_{3a} \cdot S_1 \cdot S_0)$$

$$Z_b = \bar{E}_b \cdot (I_{0b} \cdot \bar{S}_1 \cdot \bar{S}_0 + I_{1b} \cdot \bar{S}_1 \cdot S_0 + I_{2b} \cdot S_1 \cdot \bar{S}_0 + I_{3b} \cdot S_1 \cdot S_0)$$

The F153 can be used to move data from a group of registers to a common output bus. The particular register from which the data came would be determined by the state of the Select inputs. A less obvious application is as a function generator. The F153 can generate two functions of three variables. This is useful for implementing highly irregular random logic.

## Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

**Absolute Maximum Ratings**(Note 1)

|                                                                        |                                      |
|------------------------------------------------------------------------|--------------------------------------|
| Storage Temperature                                                    | −65°C to +150°C                      |
| Ambient Temperature under Bias                                         | −55°C to +125°C                      |
| Junction Temperature under Bias                                        | −55°C to +150°C                      |
| V <sub>CC</sub> Pin Potential to Ground Pin                            | −0.5V to +7.0V                       |
| Input Voltage (Note 2)                                                 | −0.5V to +7.0V                       |
| Input Current (Note 2)                                                 | −30 mA to +5.0 mA                    |
| Voltage Applied to Output<br>in HIGH State (with V <sub>CC</sub> = 0V) |                                      |
| Standard Output                                                        | −0.5V to V <sub>CC</sub>             |
| 3-STATE Output                                                         | −0.5V to +5.5V                       |
| Current Applied to Output<br>in LOW State (Max)                        | twice the rated I <sub>OL</sub> (mA) |

**Recommended Operating Conditions**

|                              |                |
|------------------------------|----------------|
| Free Air Ambient Temperature | 0°C to +70°C   |
| Supply Voltage               | +4.5V to +5.5V |

**Note 1:** Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

**Note 2:** Either voltage limit or current limit is sufficient to protect inputs.


**DC Electrical Characteristics**

| Symbol           | Parameter                         | Min                                       | Typ        | Max  | Units | V <sub>CC</sub> | Conditions                                           |
|------------------|-----------------------------------|-------------------------------------------|------------|------|-------|-----------------|------------------------------------------------------|
| V <sub>IH</sub>  | Input HIGH Voltage                | 2.0                                       |            |      | V     |                 | Recognized as a HIGH Signal                          |
| V <sub>IL</sub>  | Input LOW Voltage                 |                                           |            | 0.8  | V     |                 | Recognized as a LOW Signal                           |
| V <sub>CD</sub>  | Input Clamp Diode Voltage         |                                           |            | −1.2 | V     | Min             | I <sub>IN</sub> = −18 mA                             |
| V <sub>OH</sub>  | Output HIGH Voltage               | 10% V <sub>CC</sub><br>5% V <sub>CC</sub> | 2.5<br>2.7 |      | V     | Min             | I <sub>OH</sub> = −1 mA<br>I <sub>OH</sub> = −1 mA   |
| V <sub>OL</sub>  | Output LOW Voltage                | 10% V <sub>CC</sub>                       |            | 0.5  | V     | Min             | I <sub>OL</sub> = 20 mA                              |
| I <sub>IH</sub>  | Input HIGH Current                |                                           |            | 5.0  | μA    | Max             | V <sub>IN</sub> = 2.7V                               |
| I <sub>BVI</sub> | Input HIGH Current Breakdown Test |                                           |            | 7.0  | μA    | Max             | V <sub>IN</sub> = 7.0V                               |
| I <sub>CEX</sub> | Output High Leakage Current       |                                           |            | 50   | μA    | Max             | V <sub>OUT</sub> = V <sub>CC</sub>                   |
| V <sub>ID</sub>  | Input Leakage Test                | 4.75                                      |            |      | V     | 0.0             | I <sub>ID</sub> = 1.9 μA<br>All Other Pins Grounded  |
| I <sub>OD</sub>  | Output Leakage Circuit Current    |                                           |            | 3.75 | μA    | 0.0             | V <sub>IOD</sub> = 150 mV<br>All Other Pins Grounded |
| I <sub>IL</sub>  | Input LOW Current                 |                                           |            | −0.6 | mA    | Max             | V <sub>IN</sub> = 0.5V                               |
| I <sub>OS</sub>  | Output Short-Circuit Current      | −60                                       |            | −150 | mA    | Max             | V <sub>OUT</sub> = 0V                                |
| I <sub>CCL</sub> | Power Supply Current              |                                           | 12         | 20   | mA    | Max             | V <sub>O</sub> = LOW                                 |

**AC Electrical Characteristics**



| Symbol           | Parameter                        | T <sub>A</sub> = +25°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |     |      | T <sub>A</sub> = 0°C to +70°C<br>V <sub>CC</sub> = +5.0V<br>C <sub>L</sub> = 50 pF |      | Units |
|------------------|----------------------------------|-----------------------------------------------------------------------------|-----|------|------------------------------------------------------------------------------------|------|-------|
|                  |                                  | Min                                                                         | Typ | Max  | Min                                                                                | Max  |       |
| t <sub>PLH</sub> | Propagation Delay                | 4.5                                                                         | 8.1 | 10.5 | 4.5                                                                                | 12.0 | ns    |
| t <sub>PHL</sub> | S <sub>n</sub> to Z <sub>n</sub> | 3.5                                                                         | 7.0 | 9.0  | 3.5                                                                                | 10.5 |       |
| t <sub>PLH</sub> | Propagation Delay                | 4.5                                                                         | 7.1 | 9.0  | 4.5                                                                                | 10.5 | ns    |
| t <sub>PHL</sub> | $\bar{E}_n$ to Z <sub>n</sub>    | 3.0                                                                         | 5.7 | 7.0  | 2.5                                                                                | 8.0  |       |
| t <sub>PLH</sub> | Propagation Delay                | 3.0                                                                         | 5.3 | 7.0  | 3.0                                                                                | 8.0  | ns    |
| t <sub>PHL</sub> | I <sub>n</sub> to Z <sub>n</sub> | 2.5                                                                         | 5.1 | 6.5  | 2.5                                                                                | 7.5  |       |

# Physical Dimensions inches (millimeters) unless otherwise noted



**16-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150 Narrow  
Package Number M16A**

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)





DIMENSIONS ARE IN MILLIMETERS

## NOTES:


- CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M16DRevB1



**16-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M16D**

# Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



16-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300 Wide  
Package Number N16E

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)