




SERIES 97**Half-Pitch****FEATURES**

- Low Profile
- Half the Size of Standard DIP Switches
- 2, 4, 6, 8 & 10 Positions Available
- Less Mass for Easy Vacuum Pick & Place

APPLICATIONS

Used in any DIP application where space is at a premium such as notebook computers, hand-held radios, industrial control products, CD-ROM drives, cellular base stations and coin changers.

**Fig. 1 Series 97C DIMENSIONS** in inches (and millimeters)**Fig. 2 Series 97R DIMENSIONS** in inches (and millimeters)**SPECIFICATIONS****Electrical Ratings**

Contact Rating: 25 mA at 24 Vdc switching; 100 mA at 50 Vdc non-switching

Contact Resistance: 100 mΩ max, initially

Insulation Resistance: 100 MΩ minimum at 100 Vdc

Dielectric Strength: 300 Vac for one minute

Switch Capacitance: 5pF maximum

Contact Arrangement: SPST

Mechanical Ratings

Life: 1,000 cycles minimum

Operation Force: 500 gF

Mechanical Shock: MIL-STD-202F, Method, 213B, Test Condition A. Gravity: 50G's (peak value), 11 m/sec. Direction and times: 6 sides and 3 times in each direction.

Vibration: MIL-STD-202F, Method 201A. Passed 6 hours (2 hours in each) of three perpendicular planes at a cycle of 10-55-10Hz/1 minute.

Operating Temperature Range: -40 to 85°C

Storage Temperature Range: -40 to 85°C

Materials

Base and Cover: UL94V-0 Nylon, black

Actuators: UL94V-0 Nylon thermoplastic, white

Base Contacts: Alloy copper with gold-plating over nickel


Terminals: Brass with gold-plating

Tape Seal: Kapton

Soldering Information

Vapor phase and IR-reflow soldering can be applied. With stands 255°C peak temperature.

Cleaning: Tape sealed versions are capable of withstanding washing processes using alcohol-based solvents only. Water or other water-based solvent washing processes are not recommended. Care should be taken to avoid flux adhering to the switch body from the circuit

CIRCUITRY

board soldering process. The switch should be allowed to cool for at least 3 minutes between the end of the solder process and the beginning of the wash process. The solvent stage of the cleaning process is not to exceed 1 minute and the whole wash process is not to exceed 3 minutes. Ultrasonic or pressure wash cleaning is not recommended.

Actuation: Switch slides should be actuated from a low angle in the intended direction of travel. The application of excess force from a high angle can cause permanent damage to the contact system. Tape seals must be removed to properly actuate the switches.

Packaging Information

Tube: 125 pcs/tube (2 positions), 75 pcs/tube (4 positions), 54 pcs/tube (6 positions), 40 pcs/tube (8 positions), 33 pcs/tube (10 positions).

Tape and Reel: 97C: 4,000 pcs/reel (all positions). 97R: 2500 pcs/reel (all positions).

DIP switches are shipped in the "ON" position.

ORDERING INFORMATION

Series: 97C see fig. 1, 97R see fig. 2

Positions: 02 = .148 (3,76), 04 = .248 (6,30), 06 = .348 (8,84), 08 = .448 (11,38), 10 = .548 (13,92)

97C06SRT

T = RoHS compliant

Packaging: Blank = Tube, R = Tape and Reel (see pkg note)

Seal: Blank = Unsealed, S = Top Tape Seal